§ 1915.1009 beta-Naphthylamine.

NOTE: The requirements applicable to shipyard employment under this section are identical to those set forth at \$1910.1003 of this chapter.

[61 FR 31430, June 20, 1996]

§1915.1010 Benzidine.

NOTE: The requirements applicable to shipyard employment under this section are identical to those set forth at §1910.1003 of this chapter.

[61 FR 31430, June 20, 1996]

§1915.1011 4-Aminodiphenyl.

Note: The requirements applicable to shipyard employment under this section are identical to those set forth at §1910.1003 of this chapter.

[61 FR 31430, June 20, 1996]

§ 1915.1012 Ethyleneimine.

NOTE: The requirements applicable to shipyard employment under this section are identical to those set forth at §1910.1003 of this chapter.

[61 FR 31430, June 20, 1996]

§ 1915.1013 beta-Propiolactone.

NOTE: The requirements applicable to shipyard employment under this section are identical to those set forth at §1910.1003 of this chapter.

[61 FR 31430, June 20, 1996]

§ 1915.1014 2-Acetylaminofluorene.

Note: The requirements applicable to shipyard employment under this section are identical to those set forth at \$1910.1003 of this chapter.

[61 FR 31430, June 20, 1996]

§ 1915.1015 4-Dimethylaminoazobenzene.

NOTE: The requirements applicable to shipyard employment under this section are identical to those set forth at §1910.1003 of this chapter.

[61 FR 31430, June 20, 1996]

§1915.1016 N-Nitrosodimethylamine.

Note: The requirements applicable to shipyard employment under this section are identical to those set forth at §1910.1003 of this chapter.

[61 FR 31430, June 20, 1996]

§1915.1017 Vinyl chloride.

NOTE: The requirements applicable to ship-yard employment under this section are identical to those set forth at §1910.1017 of this chapter.

[61 FR 31430, June 20, 1996]

§1915.1018 Inorganic arsenic.

NOTE: The requirements applicable to shipyard employment under this section are identical to those set forth at §1910.1018 of this chapter.

[61 FR 31431, June 20, 1996]

§ 1915.1020 Access to employee exposure and medical records.

NOTE: The requirements applicable to shipyard employment under this section are identical to those set forth at §1910.1020 of this chapter.

[61 FR 31431, June 20, 1996]

§1915.1024 Beryllium.

- (a) Scope and application. (1) This standard applies to occupational exposure to beryllium in all forms, compounds, and mixtures in shipyards, except those articles and materials exempted by paragraphs (a)(2) and (a)(3) of this standard.
- (2) This standard does not apply to articles, as defined in the Hazard Communication standard (HCS) (29 CFR 1910.1200(c)), that contain beryllium and that the employer does not process.
- (3) This standard does not apply to materials containing less than 0.1% beryllium by weight where the employer has objective data demonstrating that employee exposure to beryllium will remain below the action level as an 8-hour TWA under any foreseeable conditions.
- (b) Definitions. As used in this standard:

Action level means a concentration of airborne beryllium of 0.1 micrograms per cubic meter of air $(\mu g/m^3)$ calculated as an 8-hour time-weighted average (TWA).

Airborne exposure and airborne exposure to beryllium mean the exposure to airborne beryllium that would occur if the employee were not using a respirator.

Assistant Secretary means the Assistant Secretary of Labor for Occupational Safety and Health, United