

(iii) Employees, other than blasters, including machine tenders and abrasive recovery men, working in areas where unsafe concentrations of abrasive materials and dusts are present shall be protected by eye and respiratory protective equipment in accordance with the requirements of subpart I of this part.

(iv) The blaster shall be protected against injury from exposure to the blast by appropriate protective clothing, including gloves.

(v) Since surges from drops in pressure in the hose line can be of sufficient proportions to throw the blaster off the staging, the blaster shall be protected by a safety belt when blasting is being done from elevations where adequate protection against falling cannot be provided by railings.

[47 FR 16986, Apr. 20, 1982, as amended at 61 FR 26351, May 24, 1996]

§ 1915.35 Painting.

(a) *Paints mixed with toxic vehicles or solvents.* (1) When paints mixed with toxic vehicles or solvents are sprayed, the following conditions shall apply:

(i) In confined spaces, employees continuously exposed to such spraying shall be protected by air line respirators in accordance with the requirements of subpart I of this part.

(ii) In tanks or compartments, employees continuously exposed to such spraying shall be protected by air line respirators in accordance with the requirements of subpart I. Where mechanical ventilation is provided, employees shall be protected by respirators in accordance with the requirements of subpart I of this part.

(iii) In large and well ventilated areas, employees exposed to such spraying shall be protected by respirators in accordance with the requirements of subpart I of this part.

(2) Where brush application of paints with toxic solvents is done in confined spaces or in other areas where lack of ventilation creates a hazard, employees shall be protected by filter respirators in accordance with the requirements of subpart I of this part.

(3) When flammable paints or vehicles are used, precautions shall be taken in accordance with the requirements of § 1915.36.

(4) The metallic parts of air moving devices, including fans, blowers, and jet-type air movers, and all duct work shall be electrically bonded to the vessel's structure.

(b) *Paints and tank coatings dissolved in highly volatile, toxic and flammable solvents.* Several organic coatings, adhesives and resins are dissolved in highly toxic, flammable and explosive solvents with flash points below 80 °F. Work involving such materials shall be done only when all of the following special precautions have been taken:

(1) Sufficient exhaust ventilation shall be provided to keep the concentration of solvent vapors below ten (10) percent of the lower explosive limit. Frequent tests shall be made by a competent person to ascertain the concentration.

(2) If the ventilation fails or if the concentration of solvent vapors reaches or exceeds ten (10) percent of the lower explosive limit, painting shall be stopped and the compartment shall be evacuated until the concentration again falls below ten (10) percent of the lower explosive limit. If the concentration does not fall when painting is stopped, additional ventilation to bring the concentration to below ten (10) percent of the lower explosive limit shall be provided.

(3) Ventilation shall be continued after the completion of painting until the space or compartment is gas free. The final determination as to whether the space or compartment is gas free shall be made after the ventilating equipment has been shut off for at least 10 minutes.

(4) Exhaust ducts shall discharge clear of working areas and away from sources of possible ignition. Periodic tests shall be made to ensure that the exhausted vapors are not accumulating in other areas within or around the vessel or dry dock.

(5) All motors and control equipment shall be of the explosion-proof type. Fans shall have nonferrous blades. Portable air ducts shall also be of nonferrous materials. All motors and associated control equipment shall be properly maintained and grounded.

(6) Only non-sparking paint buckets, spray guns and tools shall be used. Metal parts of paint brushes and rollers

§ 1915.36

29 CFR Ch. XVII (7-1-22 Edition)

shall be insulated. Staging shall be erected in a manner which ensures that it is non-sparking.

(7) Only explosion proof lights, approved by the Underwriters' Laboratories for use in Class I, Group D atmospheres, or approved as permissible by the Mine Safety and Health Administration or the U.S. Coast Guard, shall be used.

(8) A competent person shall inspect all power and lighting cables to ensure that the insulation is in excellent condition, free of all cracks and worn spots, that there are no connections within fifty (50) feet of the operation, that lines are not overloaded, and that they are suspended with sufficient slack to prevent undue stress or chafing.

(9) The face, eyes, head, hands, and all other exposed parts of the bodies of employees handling such highly volatile paints shall be protected. All footwear shall be non-sparking, such as rubbers, rubber boots or rubber soled shoes without nails. Coveralls or other outer clothing shall be of cotton. Rubber, rather than plastic, gloves shall be used because of the danger of static sparks.

(10) No matches, lighted cigarettes, cigars, or pipes, and no cigarette lighters or ferrous articles shall be taken into the area where work is being done.

(11) All solvent drums taken into the compartment shall be placed on non-ferrous surfaces and shall be grounded to the vessel. Metallic contact shall be maintained between containers and drums when materials are being transferred from one to another.

(12) Spray guns, paint pots, and metallic parts of connecting tubing shall be electrically bonded, and the bonded assembly shall be grounded to the vessel.

(13) All employees continuously in a compartment in which such painting is being performed shall be protected by air line respirators in accordance with the requirements of subpart I of this part and by suitable protective clothing. Employees entering such compartments for a limited time shall be protected by filter cartridge type respirators in accordance with the requirements of subpart I of this part.

(14) All employees doing exterior paint spraying with such paints shall be protected by suitable filter cartridge type respirators in accordance with the requirements of subpart I of this part and by suitable protective clothing.

[47 FR 16986, Apr. 20, 1982, as amended at 61 FR 26351, May 24, 1996; 67 FR 44541, July 3, 2002]

§ 1915.36 Flammable liquids.

(a) In all cases when liquid solvents, paint and preservative removers, paints or vehicles, other than those covered by §1915.35(b), are capable of producing a flammable atmosphere under the conditions of use, the following precautions shall be taken:

(1) Smoking, open flames, arcs and spark-producing equipment shall be prohibited in the area.

(2) Ventilation shall be provided in sufficient quantities to keep the concentration of vapors below ten (10) percent of their lower explosive limit. Frequent tests shall be made by a competent person to ascertain the concentration.

(3) Scrapings and rags soaked with these materials shall be kept in a covered metal container.

(4) Only explosion proof lights, approved by the Underwriters' Laboratories for use in Class I, Group D atmospheres, or approved as permissible by the Mine Safety and Health Administration or the U.S. Coast Guard, shall be used.

(5) A competent person shall inspect all power and lighting cables to ensure that the insulation is in excellent condition, free of all cracks and worn spots, that there are no connections within fifty (50) feet of the operation, that lines are not overloaded, and that they are suspended with sufficient slack to prevent undue stress or chafing.

(6) Suitable fire extinguishing equipment shall be immediately available in the work area and shall be maintained in a state of readiness for instant use.