Reporting and recordkeeping requirements, Watermelon promotion.

For the reasons set forth in the preamble, 7 CFR part 1210 is amended as follows:

PART 1210—WATERMELON RESEARCH AND PROMOTION PLAN

■ 1. The authority citation for 7 CFR part 1210 continues to read as follows:

Authority: 7 U.S.C. 4901–4916 and 7 U.S.C. 7401.

Subpart C—Administrative Requirements

- 2. The heading for subpart C is revised to read as set forth above.
- 3. In § 1210.501, paragraphs (a), (b), (d), and (g) are revised to read as follows:

§ 1210.501 Realignment of districts.

* * * * *

- (a) District 1—The State of Florida.
- (b) District 2—The States of Kentucky, North Carolina, South Carolina, Tennessee, Virginia and West Virginia.

 * * * * * *
- (d) *District 4*—The States of Connecticut, Delaware, Illinois, Indiana,

Maine, Maryland, Massachusetts, Michigan, New Hampshire, New Jersey, New York, Ohio, Pennsylvania, Rhode Island, Vermont, Wisconsin, and Washington, DC.

* * * * *

- (g) District 7—The States of Alabama, Alaska, Arizona, Arkansas, Colorado, Hawaii, Idaho, Iowa, Kansas, Louisiana, Minnesota, Mississippi, Missouri, Montana, Nebraska, Nevada, New Mexico, North Dakota, Oklahoma, Oregon, South Dakota, Utah, Washington, and Wyoming.
- 4. Section 1210.502 is revised to read as follows:

§ 1210.502 Importer members.

Pursuant to § 1210.320(d) of the Plan, there are twelve importer representatives on the Board based on the proportionate percentage of assessments paid by importers to the Board.

Dated: January 25, 2018.

Bruce Summers,

Acting Administrator.

[FR Doc. 2018-01802 Filed 1-30-18; 8:45 am]

BILLING CODE 3410-02-P

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 121

[Docket No.: FAA-2013-0485; Amdt. No. 121-376B]

RIN 2120-AJ94

Revisions to Operational Requirements for the Use of Enhanced Flight Vision Systems (EFVS) and to Pilot Compartment View Requirements for Vision Systems; Correcting Amendment

Correction

In rule document 2018–00225 appearing on pages 1186–1188 in the issue of Wednesday, January 10, 2018, make the following correction:

Appendix F to Part 121

On page 1187, beginning in the third column, Appendix F to Part 121 should read as follows:

Appendix F to Part 121—Proficiency Check Requirements

* * * * *

Maneuvers/Procedures	Required		Permitted				
	Simulated Instrument Conditions	Inflight	Visual Simulator	Nonvisual Simulator	Training Device	Waiver Provisions of § 121.441(d)	
* *	*	*		*	*	*	
III. Instrument procedures:							
(a) Area departure and area arrival. During each of these maneuvers the applicant must—	В			В		B*	
(1) Adhere to actual or simulated ATC clearances (including assigned radials); and							
(2) Properly use available navigation facilities.							
Either area arrival or area departure, but not both, may be waived under § 121.441(d).							
(b) Holding. This maneuver includes entering, maintaining, and leaving holding patterns. It may be performed in connection with either area departure or area arrival.	В			В		В	
(c) ILS and other instrument approaches. There must be the following:							
(1) At least one normal ILS approach.	В		В				

	Required		Permitted				
Maneuvers/Procedures	Simulated Instrument Conditions	Inflight	Visual Simulator	Nonvisual Simulator	Training Device	Waiver Provisions of § 121.441(d)	
(2) At least one manually controlled ILS approach with a simulated failure of one powerplant. The simulated failure should occur before initiating the final approach course and must continue to touchdown or through the missed approach procedure.	В						
(3) At least one nonprecision approach procedure that is representative of the non-precision approach procedures that the certificate holder is likely to use.	В		В				
(4) Demonstration of at least one nonprecision approach procedure on a letdown aid other than the approach procedure performed under subparagraph (3) of this paragraph that the certificate holder is approved to use.	В				В		
(5) For each type of EFVS operation the certificate holder is authorized to conduct, at least one instrument approach must be made using an EFVS.	В	B*					
Each instrument approach must be performed according to any procedures and limitations approved for the approach facility used. The instrument approach begins when the airplane is over the initial approach fix for the approach procedure being used (or turned over to the final approach controller in the case of a GCA approach) and ends when the airplane touches down on the runway or when transition to a missed approach configuration is completed. Instrument conditions need not be simulated below 100' above touchdown zone elevation.							
(d) Circling approaches. If the certificate holder is approved for circling minimums below 1000–3, at least one circling approach must be made under the following conditions.			B*			B*	
(1) The portion of the approach to the authorized minimum circling approach altitude must be made under simulated instrument conditions.	В						

	Required		Permitted				
Maneuvers/Procedures	Simulated Instrument Conditions	Inflight	Visual Simulator	Nonvisual Simulator	Training Device	Waiver Provisions of § 121.441(d)	
(2) The approach must be made to the authorized minimum circling approach attitude followed by a change in heading and the necessary maneuvering by visual reference to maintain a flight path that permits a normal landing on a runway at least 90[degrees] from the final approach course of the simulated instrument portion of the approach.							
(3) The circling approach must be performed without excessive maneuvering, and without exceeding the normal operating limits of the airplane. The angle of bank should not exceed 30[degrees]							
If local conditions beyond the control of the pilot prohibit the maneuver or prevent it from being performed as required, it may be waived as provided in § 121.441(d): Provided, however, that the maneuver may not be waived under this provision for two successive proficiency checks.							
The circling approach maneuver is not required for a second-in-command if the certificate holder's manual prohibits a second-in-command from performing a circling approach in operations under this part.							
(e) Missed Approach							
(1) Each pilot must perform at least one missed approach from an ILS approach.			B*				
(2) Each pilot in command must perform at least one additional missed approach. A complete approved missed approach procedure must be accomplished at least once. At the discretion of the person conducting a check a simulated powerplant failure may be required during any of the missed approaches. These maneuvers may be performed either independently or in conjunction with maneuvers required under Sections III or V of this appendix. At least one missed approach must be performed in flight.			P*				