

NBS 12-79-1358



TECHNICAL ASSOCIATION OF THE  
PULP AND PAPER INDUSTRY

COLLABORATIVE REFERENCE PROGRAM  
FOR PAPER

REPORT NO. 55S  
STRENGTH TESTS



U.S. DEPARTMENT OF COMMERCE  
National Bureau of Standards

NBS COLLABORATIVE REFERENCE PROGRAMS

TAPPI Paper and Board (6 times per year)

|                           |                               |
|---------------------------|-------------------------------|
| Bursting strength         | Smoothness                    |
| Tearing strength          | Surface pick strength         |
| Tensile breaking strength | K & N ink absorption          |
| Elongation to break       | pH                            |
| Tensile energy absorption | Opacity                       |
| Folding endurance         | Blue reflectance (brightness) |
| Stiffness                 | Specular gloss, 75°           |
| Air resistance            | Thickness                     |
| Grammage                  | Concora (flat crush)          |
|                           | Ring crush                    |

FKBG-API Containerboard (48 times per year)

Mullen burst of linerboard  
Concora test of medium

MCCA Color and Appearance (4 times per year)

Gloss at 60°  
Color and color difference  
Retroreflectivity

Rubber (4 times per year)

Tensile strength, ultimate elongation and tensile stress  
Hardness  
Mooney viscosity  
Vulcanization properties

ASTM Textiles (3 times per year)

Flammability (FF3-71 and FF5-74)

ASTM Cement (2 times per year)

Chemical (11 chemical components)  
Physical (8 characteristics)

AASHTO Bituminous

Asphalt cement (2 times per year)  
Cutbacks (once a year)



Collaborative Reference Programs  
B360 Polymer Building  
National Bureau of Standards  
Washington, D.C. 20234

TECHNICAL ASSOCIATION OF THE  
PULP AND PAPER INDUSTRY

**COLLABORATIVE REFERENCE PROGRAM  
FOR PAPER**

Report No. 55S  
STRENGTH TESTS

R. G. Powell  
TAPPI-NBS Research Associate  
Collaborative Testing Services, Inc.

J. Horlick  
Office of Testing Laboratory Evaluation Technology  
Office of Engineering Standards  
National Engineering Laboratory

NBSIR 79-1358

U. S. DEPARTMENT OF COMMERCE  
National Bureau of Standards







## TAPPI-NBS COLLABORATIVE REFERENCE PROGRAM

### BACKGROUND AND PURPOSE

In 1969, the National Bureau of Standards and the Technical Association of the Pulp and Paper Industry established a collaborative reference program to provide a participating laboratory with a means to check periodically the level and uniformity of its testing in comparison with that of other laboratories.

The interchange of paper and board products and of the raw materials for these products requires agreement among raw material suppliers, paper and board producers, converters, distributors, retailers, commercial testing laboratories, user organizations and the ultimate consumer as to the meaning of test results, an agreement that cannot be achieved without accurate and precise testing. This program is designed to help assure agreement.

### HOW THE PROGRAM WORKS

Participants Select the Tests in which they wish to participate. This choice is made on joining the program, but additional tests may be added at any time. Also new participants may enter the program at any time.

Test Samples are Distributed Bimonthly; i.e. every 2 months.

Provisional Values are Provided with the Samples for one or both of the test levels, depending on method. The provisional values permit serious discrepancies to be detected without delay. (It is left to the discretion of the laboratory supervisor as to whether these values should be known to the operator.)

Each Participant Tests the Samples, following instructions provided for each test method. The full check on a single instrument should normally take no more than 30 minutes. The test results are then sent to NBS for analysis. The participant is also asked to report other information relevant to an accurate analysis, such as test conditions and the instruments used.

Industry Means, Best Values and Other Statistics are developed from the data by NBS. The best values are estimates based on a careful examination of all data, both current and past, with special attention to results obtained by the National Bureau of Standards and other recognized reference laboratories in this and other countries.

A Quick Report is Prepared for each participating laboratory reporting data on time. This report shows the industry mean values, and the deviations of the laboratory's results from these values for each test method.

A Longer Summary Report, Showing the Data from all Participants, is also prepared. In the summary report, of which this report is an example, each laboratory is identified by a code number so that the information is maintained on a confidential basis. However, instruments are identified by type so participants can compare their results with those obtained on similar instruments of different manufacture. This report includes test averages, best values and standard deviations for individual participants and for the group as a whole. A participant should be able to readily determine the level and variability of his results in comparison with those of the other laboratories.

Repeatability and Reproducibility Statements such as Contained in ASTM, TAPPI and ISO Standards are included at the end of the report. Participants can check their performance level against the precision statement given in the test method or specification.



TABLE OF CONTENTS

Analyses In This Report

PAGE

-----

|    |  |
|----|--|
| 1  | Introduction   |
| 11 | Description of Program                                     |
| iv | Metric Conversion Table                                    |
| 1  | Key to Tables and Graphs                                   |
| 5  | 10-1 Bursting Strength - Up to 45 psi                      |
| 8  | 10-2 Bursting Strength - Up to 45 psi, Air Clamps          |
| 11 | 11-1 Bursting Strength - Up to 100 psi                     |
| 14 | 15-1 Tearing Strength - Deep Cutout                        |
| 19 | 17-1 Tearing Strength - No Cutout                          |
| 21 | 19-1 Tensile Breaking Strength - Packaging Papers          |
| 24 | 20-1 Tensile Breaking Strength - Printing Papers, CRE      |
| 27 | 20-2 Tensile Breaking Strength - Printing Papers, pendulum |
| 30 | 25-1 Tensile Energy Absorption - Packaging Papers          |
| 32 | 26-1 Tensile Energy Absorption - Printing Papers           |
| 34 | 28-1 Elongation to Break - Packaging Papers                |
| 37 | 29-1 Elongation to Break - Printing Papers                 |
| 40 | 30-1 Folding Endurance, MIT type                           |
| 43 | 30-2 Folding Endurance, MIT type, log (base 10)            |
| 46 | 35-1 Stiffness, Gurley                                     |
| 49 | 36-1 Stiffness, Taber                                      |
| 52 | 49-1 Surface Pick Strength, IGT                            |
| 54 | 50-1 Surface Pick Strength, Wax                            |
| 57 | 91-1 Concora (Flat Crush)                                  |
| 59 | 96-1 Ring Crush  |
| 62 | Summary  |

Diagram of Elmendorf tear testers, deep cutout vs. no cutout

Analyses In The G Report

|      |  |
|------|--|
| 40-1 | Air Resistance, Gurley Oil type                    |
| 40-2 | Air Resistance, Sheffield type                     |
| 41-1 | Air Resistance, Gurley Mercury type                |
| 44-1 | Smoothness, Parker Printsurf                       |
| 45-1 | Smoothness, Sheffield type                         |
| 45-2 | Smoothness, Bekk type                              |
| 47-1 | Smoothness, Bendtsen type                          |
| 56-1 | K & N Ink Absorption                               |
| 57-1 | pH, Cold Extraction                                |
| 57-2 | pH, Hot Extraction                                 |
| 60-1 | Opacity, White (89%) Backing                       |
| 60-2 | Opacity, Paper Backing, B & L type                 |
| 60-3 | Opacity, Paper Backing, Elrepho type               |
| 65-1 | Blue Reflectance (Brightness), Directional         |
| 65-2 | Blue Reflectance, Diffuse, Elrepho (Gloss Trap)    |
| 65-3 | Blue Reflectance, Diffuse, Elrepho (No Gloss Trap) |
| 75-1 | Specular Gloss, 75 degree                          |
| 90-1 | Thickness (Caliper)                                |
| 95-1 | Grammage (Basis Weight)                            |

TABLE OF CONVERSION FACTORS TO METRIC (SI) UNITS

| <u>Physical<br/>Quantity</u>  | <u>To Convert<br/>From</u> | <u>To</u>        | <u>Multiply<br/>by</u> |
|-------------------------------|----------------------------|------------------|------------------------|
| Bursting strength             | psi                        | kPa              | 6.895                  |
|                               | kg/cm <sup>2</sup>         | kPa              | 98.07                  |
|                               | bar                        | kPa              | 100.00                 |
| Tearing strength              | g                          | mN               | 9.807                  |
| Tensile strength              | lb/in.                     | kN/m             | .1751                  |
|                               | lb/0.5 in.                 | kN/m             | .3502                  |
|                               | lb/15 mm                   | kN/m             | .2965                  |
|                               | kg/15 mm                   | kN/m             | .6538                  |
|                               | kg/25 mm                   | kN/m             | .3923                  |
|                               | kg/mm                      | kN/m             | 9.807                  |
| Tensile energy absorption     | ft-lb/ft <sup>2</sup>      | J/m <sup>2</sup> | 14.59                  |
|                               | in.-lb/in. <sup>2</sup>    | J/m <sup>2</sup> | 175.1                  |
|                               | kg-m/m <sup>2</sup>        | J/m <sup>2</sup> | 9.807                  |
| Bending stiffness             | g·cm                       | μN·m             | 98.07                  |
| Flat-crush strength (Concora) | lb                         | N                | 4.448                  |
| Ring-crush (TAPPI)            | lb                         | N                | 4.448                  |
|                               | (ISO)                      | lb/6.00 in.      | kN/m                   |
| Thickness                     | mil                        | μm               | 25.40                  |

## KEY TO TABLES AND GRAPHS

- MEAN - The average of individual TEST DETERMINATIONS. The number of TEST DETERMINATIONS in the mean is given in the upper right corner of the first table (TEST D.) and again at the bottom of this table.
- GRAND MEAN - (GR. MEAN) The average of the individual laboratory MEANS, excluding laboratories flagged (see column F) with an X, #, or +. The GRAND MEAN is given in US customary units and, where applicable, in SI metric units.
- SD OF MEANS - (SD MEANS) The standard deviation of the laboratory MEANS about the GRAND MEAN; an index of the among-laboratory precision.
- DEV - The deviation or difference of the laboratory MEAN from the GRAND MEAN.
- N. DEV - The normal deviate or ratio of the DEV to the SD OF MEANS; an indication of the degree of divergence of the laboratory MEAN from the GRAND MEAN. A N. DEV of more than 2 or less than -2 may indicate that the participant is not following the procedure considered standard for this analysis.
- SDR - The standard deviation of repeated measurements; that is, of individual test determinations about their MEAN.
- AVERAGE SDR - The average of the individual laboratory SDR's; an index of the within-laboratory precision of repeated measurements.
- R. SDR - The relative standard deviation of repeated measurements; that is, the ratio of the SDR to the AVERAGE SDR: an indication of the ability of a participant to repeat his measurements relative to the average ability. The greater the number of TEST DETERMINATIONS the closer the R. SDR should be to unity. If R. SDR is outside the limits given below, the participant may not be following the procedure considered standard for this analysis:

| <u>No. of test<br/>Determinations</u> | <u>Lower limit<br/>for R. SDR</u> | <u>Upper limit<br/>for R. SDR</u> |
|---------------------------------------|-----------------------------------|-----------------------------------|
| 3                                     | 0.09                              | 2.58                              |
| 5                                     | 0.27                              | 2.06                              |
| 8                                     | 0.40                              | 1.77                              |
| 10                                    | 0.46                              | 1.67                              |
| 15                                    | 0.56                              | 1.53                              |
| 20                                    | 0.61                              | 1.45                              |
| 25                                    | 0.65                              | 1.39                              |

- VAR - Code for instrument type or variation in condition, see second table.
- F - Flag, with following meaning:
- + - Excluded from grand means because VAR non-standard for this analysis
  - # - Excluded because data were not understood or because of a non-coded variation reported by the laboratory. (See NOTES following Table 1 for each method.)
  - M - Excluded because data for one sample are missing
  - X - Excluded because plotted point would fall outside of the 99% error ellipse, (see below for explanation of Graph)
  - \* - Included in grand means but plotted point falls outside of the 95% error ellipse. The participant should take this as a warning to reexamine his testing procedure
  - S - Included in grand mean but only after omission of one of more 'wild' values; that is, test determinations more than 3 times AVERAGE SDR from the laboratory's MEAN. Not more than 20% of the test determination may be excluded in this manner without rejecting the laboratory.
  - O - Included in grand mean and inside 95% error ellipse.
- COORDINATES - Distances along major and minor axes of error ellipse. If special additive or concurrent model of the measuring process applies to this method, the distance along the minor axis represents the random error within a laboratory while that along the major axis also includes a systematic laboratory component of error.

- 95% ELLIPSE - Lengths of the major and minor axes of the ellipse and the angle that the major axis makes with the horizontal axis.
- AVG R. SDR - Average of the R. SDR for the two samples; an indication of the laboratory's precision of repeated measurements.
- Graph - For each laboratory the MEAN for the second sample is plotted against the MEAN for the first sample, with each point representing a laboratory. The horizontal and vertical lines are the GRAND MEANS. The dashed line is drawn at 45°. The solid sloping line, which may or may not lie close to the 45° line, is along the major axis of the error ellipse. The ellipse is drawn so that , on the average, it will include 95% of the points representing the laboratories.

Plotted symbols are as explained above (under F), except that an 'S' is plotted as an 'O'. A participant whose plotted point falls outside of the ellipse should carefully reexamine the testing procedure he is following.

The graph is plotted with an ellipse when there are 20 or more laboratories in the analysis. When there are 10 through 19 laboratories in the analysis the graph is plotted but the ellipse is omitted. When there are fewer than 10 laboratories retained in the analysis the graph is not plotted.

The International System of Units (SI) is used on the plots wherever possible to aid participants in familiarizing themselves with SI. Grand means in SI units are given at the top of the plot, and supplementary scales in SI units are drawn along the axes allowing the reader to compare means and variability in common units and SI units for the same data.

- Summary - In addition to several quantities already defined above the summary shows the following values for each test method:  
(At end of report)
- REPL CRP - The number of replicate test determinations used in this Collaborative Reference Program.
- REPL TAPPI - The number of replicate test determinations in a test result required by the applicable TAPPI Standard or assumed here if there is no TAPPI Standard. This quantity is needed in the computation of TAPPI repeatability and reproducibility from the SD OF MEANS and the AVER SDR. See TAPPI Standard T1206 for definitions and computations.
- REPEAT - TAPPI repeatability, a measure of the within-laboratory precision of a test result.
- REPROD - TAPPI reproducibility, a measure of the between-laboratory precision of a test result.
- Best values - Given at the end of Table 1 for each method for which sufficient information is available. These best values are estimates based on a careful examination of all data, both current and past, with special attention to results obtained by the National Bureau of Standards and other recognized reference laboratories in this and other countries. All participants using equipment that is standard for the analysis should be able to achieve results within the plus-minus (+) limits, when these are shown along with the best values.

TAPPI STANDARD T403 G9-76, BURSTING STRENGTH OF PAPER - PERKINS MODEL C

| LAB CODE | SAMPLE H63 MEAN | PRINTING 77 GRAMS PER SQUARE METER |        |      |        | SAMPLE J39 MEAN | PRINTING 149 GRAMS PER SQUARE METER |        |      |        | TEST D. = 15 |   |       |
|----------|-----------------|------------------------------------|--------|------|--------|-----------------|-------------------------------------|--------|------|--------|--------------|---|-------|
|          |                 | DEV                                | N. DEV | SDR  | R. SDR |                 | DEV                                 | N. DEV | SDR  | R. SDR | VAR          | F | LAB   |
| L121     | 16.89           | .21                                | .16    | .70  | .67    | 26.80           | -2.09                               | -0.99  | 1.52 | 1.03   | 10C          | Ø | L121  |
| L131     | 15.00           | -1.69                              | -1.28  | .76  | .73    | 26.60           | -2.29                               | -1.09  | .91  | .61    | 10C          | Ø | L131  |
| L134     | 16.40           | -.29                               | -.22   | .57  | .55    | 32.37           | 3.48                                | 1.65   | 1.17 | .79    | 10C          | * | L134  |
| L150     | 17.67           | .98                                | .74    | 1.18 | 1.13   | 29.27           | .38                                 | .18    | .92  | .62    | 10C          | Ø | L150  |
| L158     | 15.00           | -.69                               | -.52   | 1.20 | 1.15   | 28.47           | -.42                                | -.20   | .92  | .62    | 10C          | Ø | L158  |
| L167     | 17.43           | .75                                | .56    | .68  | .65    | 28.00           | -.89                                | -.42   | 1.20 | .81    | 10C          | Ø | L167  |
| L183     | 15.57           | -1.11                              | -.84   | 1.08 | 1.03   | 26.00           | -2.89                               | -1.37  | 1.66 | 1.12   | 10C          | Ø | L183  |
| L191     | 16.73           | .05                                | .03    | .73  | .70    | 30.00           | 1.11                                | .53    | 1.64 | 1.10   | 10C          | Ø | L191  |
| L203A    | 15.77           | -.92                               | -.70   | .82  | .79    | 28.67           | -.22                                | -.11   | 1.59 | 1.07   | 10C          | Ø | L203A |
| L203B    | 16.47           | -.22                               | -.17   | .95  | .92    | 29.57           | .68                                 | .32    | 2.27 | 1.53   | 10C          | Ø | L203B |
| L207     | 19.20           | 2.51                               | 1.90   | 1.19 | 1.14   | 32.10           | 3.21                                | 1.52   | 1.84 | 1.24   | 10C          | Ø | L207  |
| L212     | 16.53           | -.15                               | -.12   | .74  | .71    | 31.53           | 2.64                                | 1.26   | 1.49 | 1.01   | 10C          | Ø | L212  |
| L223A    | 19.28           | 2.59                               | 1.96   | 1.06 | 1.02   | 33.53           | 4.64                                | 2.20   | 1.71 | 1.15   | 10C          | Ø | L223A |
| L225     | 16.90           | .21                                | .16    | 1.21 | 1.16   | 29.80           | .91                                 | .43    | 1.86 | 1.25   | 10C          | Ø | L225  |
| L222     | 14.60           | -2.09                              | -1.58  | 1.07 | 1.03   | 27.27           | -1.62                               | -.77   | 1.29 | .87    | 10C          | Ø | L222  |
| L237A    | 15.73           | -.95                               | -.72   | .88  | .85    | 26.37           | -2.52                               | -1.20  | 1.30 | .88    | 10C          | Ø | L237A |
| L237B    | 16.33           | -.35                               | -.27   | .94  | .90    | 27.10           | -1.79                               | -.85   | .60  | .41    | 10C          | Ø | L237B |
| L243     | 17.67           | .98                                | .74    | 1.32 | 1.27   | 29.37           | .48                                 | .23    | 1.38 | .93    | 10C          | Ø | L243  |
| L249     | 13.68           | -3.01                              | -2.27  | .79  | .76    | 25.59           | -3.30                               | -1.57  | 1.35 | .91    | 10C          | Ø | L249  |
| L261     | 16.17           | -.52                               | -.39   | .82  | .79    | 27.28           | -1.61                               | -.76   | 1.66 | 1.12   | 10C          | Ø | L261  |
| L264     | 16.80           | .11                                | .08    | 1.08 | 1.04   | 28.73           | -.16                                | -.07   | 1.58 | 1.06   | 10C          | Ø | L264  |
| L278     | 16.90           | .21                                | .16    | 1.02 | .98    | 27.90           | -.99                                | -.47   | 1.78 | 1.20   | 10C          | Ø | L278  |
| L279     | 15.73           | -.95                               | -.72   | 1.57 | 1.50   | 27.10           | -1.79                               | -.85   | 1.27 | .85    | 10C          | Ø | L279  |
| L299     | 18.93           | 2.25                               | 1.70   | 1.43 | 1.37   | 34.00           | 5.11                                | 2.43   | 1.89 | 1.27   | 10C          | Ø | L299  |
| L305     | 16.63           | -.05                               | -.04   | 1.03 | .98    | 27.70           | -1.19                               | -.56   | .92  | .62    | 10C          | Ø | L305  |
| L311     | 17.93           | 1.25                               | .94    | .80  | .77    | 30.07           | 1.18                                | .56    | 1.22 | .82    | 10C          | Ø | L311  |
| L312     | 16.72           | .03                                | .02    | .89  | .85    | 28.61           | -.28                                | -.13   | .88  | .59    | 10C          | Ø | L312  |
| L315     | 18.73           | 2.05                               | 1.55   | 1.31 | 1.25   | 31.57           | 2.68                                | 1.27   | 1.85 | 1.25   | 10C          | Ø | L315  |
| L325     | 16.47           | -.22                               | -.17   | .88  | .84    | 29.47           | .58                                 | .27    | 1.94 | 1.31   | 10C          | Ø | L325  |
| L330     | 17.90           | 1.21                               | .92    | 1.16 | 1.11   | 29.90           | 1.01                                | .48    | 1.39 | .93    | 10C          | Ø | L330  |
| L331     | 16.33           | -.35                               | -.27   | 1.05 | 1.00   | 27.13           | -1.76                               | -.83   | 1.25 | .84    | 10C          | Ø | L331  |
| L333     | 14.81           | -1.88                              | -1.42  | 1.29 | 1.24   | 26.61           | -2.28                               | -1.08  | 2.12 | 1.43   | 10C          | Ø | L333  |
| L339     | 12.88           | -3.80                              | -2.88  | 1.40 | 1.34   | 25.13           | -3.76                               | -1.78  | 1.51 | 1.02   | 10C          | * | L339  |
| L344     | 16.87           | .19                                | .14    | .90  | .86    | 32.37           | 3.48                                | 1.65   | 1.71 | 1.15   | 10C          | Ø | L344  |
| L356     | 17.50           | .81                                | .61    | 1.26 | 1.21   | 26.91           | -1.98                               | -.94   | 1.94 | 1.31   | 10C          | Ø | L356  |
| L358     | 16.23           | -.45                               | -.34   | .68  | .65    | 29.64           | .75                                 | .36    | 1.16 | .78    | 10C          | Ø | L358  |
| L360     | 16.73           | .05                                | .03    | 1.54 | 1.48   | 28.69           | -.20                                | -.10   | 1.92 | 1.30   | 10C          | Ø | L360  |
| L366     | 17.40           | .71                                | .54    | 1.27 | 1.22   | 28.70           | -.19                                | -.09   | 1.81 | 1.22   | 10C          | Ø | L366  |
| L390     | 18.27           | 1.58                               | 1.19   | 1.07 | 1.02   | 30.47           | 1.58                                | .75    | 1.33 | .90    | 10C          | Ø | L390  |
| L563     | 16.70           | .01                                | .01    | 1.16 | 1.12   | 29.30           | .41                                 | .20    | 1.41 | .95    | 10C          | Ø | L563  |
| L568     | 16.97           | .28                                | .21    | 1.14 | 1.10   | 28.67           | -.22                                | -.11   | 1.18 | .79    | 10C          | Ø | L568  |
| L599     | 17.41           | .72                                | .54    | 1.06 | 1.02   | 29.01           | .12                                 | .06    | 1.68 | 1.13   | 10C          | Ø | L599  |

GR. MEAN = 16.69 PSI

SD MEANS = 1.32 PSI

GRAND MEAN = 28.89 PSI

SD OF MEANS = 2.11 PSI

TEST DETERMINATIONS = 15

42 LABS IN GRAND MEANS

AVERAGE SDR = 1.04 PSI

AVERAGE SDR = 1.48 PSI

GR. MEAN = 115.1 KILOPASCAL

GRAND MEAN = 199.2 KILOPASCAL

|      |       |       |      |      |      |       |       |       |      |      |     |   |      |
|------|-------|-------|------|------|------|-------|-------|-------|------|------|-----|---|------|
| L128 | 18.33 | 1.65  | 1.24 | .62  | .59  | 30.53 | 1.64  | .78   | 1.30 | .88  | 10B | * | L128 |
| L242 | 19.45 | 2.76  | 2.09 | 1.15 | 1.10 | 29.48 | .59   | .28   | 1.33 | .90  | 10C | * | L242 |
| L251 | 18.12 | 1.44  | 1.09 | 1.45 | 1.39 | 30.16 | 1.27  | .60   | 1.22 | .82  | 10V | * | L251 |
| L269 | 24.47 | 7.78  | 5.88 | 1.55 | 1.49 | 37.40 | 8.51  | 4.04  | 1.80 | 1.22 | 10A | * | L269 |
| L484 | 15.67 | -1.02 | -.77 | .77  | .74  | 26.50 | -2.39 | -1.13 | 1.21 | .82  | 10M | * | L484 |

TOTAL NUMBER OF LABORATORIES REPORTING = 47

Best values: H63 16.8 ± 2.2 psi

J39 29.0 ± 3.4 psi

ANALYSIS T10=1 TABLE 2


BURSTING STRENGTH, PSI

TAPPI STANDARD T403 GS=76, BURSTING STRENGTH OF PAPER = PERKINS MODEL C

| LAB CODE | F | MEANS        |       | COORDINATES |       | AVG                     |     | PROPERTY==TEST   | INSTRUMENT==CONDITIONS |
|----------|---|--------------|-------|-------------|-------|-------------------------|-----|--|------------------------|
|          |   | H63          | J39   | MAJOR       | MINOR | R.SDR                   | VAR |  |                        |
| L335     | * | 12.88        | 25.13 | -5.11       | 1.55  | 1.18                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L249     | 0 | 13.68        | 25.59 | -4.34       | 1.07  | .83                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L232     | 0 | 14.60        | 27.27 | -2.42       | 1.06  | .95                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L333     | 0 | 14.81        | 26.61 | -2.90       | .57   | 1.33                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L131     | 0 | 15.00        | 26.60 | -2.82       | .39   | .67                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L183     | 0 | 15.57        | 26.00 | -3.07       | -0.40 | 1.08                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L484     | * | 15.67        | 26.50 | -2.59       | -0.24 | .78                     | 10M | BURSTING STRENGTH UP T0 45 PSI, REGMED MT/MOT,                 | MANUAL CLAMP           |
| L279     | 0 | 15.73        | 27.10 | -2.03       | -0.01 | 1.18                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L237A    | 0 | 15.73        | 26.37 | -2.67       | -0.36 | .86                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L203A    | 0 | 15.77        | 28.67 | -0.63       | .70   | .93                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L158     | 0 | 16.00        | 28.47 | -0.70       | .40   | .88                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L261     | 0 | 16.17        | 27.28 | -1.66       | -0.31 | .95                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L358     | 0 | 16.23        | 29.64 | .44         | .76   | .72                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L331     | 0 | 16.33        | 27.13 | -1.71       | -0.53 | .92                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L237B    | 0 | 16.33        | 27.10 | -1.74       | -0.54 | .65                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L134     | * | 16.40        | 32.37 | 2.92        | 1.91  | .67                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L326     | 0 | 16.47        | 29.47 | .40         | .47   | 1.07                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L203B    | 0 | 16.47        | 29.57 | .49         | .52   | 1.22                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L212     | 0 | 16.53        | 31.53 | 2.25        | 1.40  | .86                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L305     | 0 | 16.63        | 27.70 | -1.07       | -0.52 | .80                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L563     | 0 | 16.70        | 29.30 | .37         | .19   | 1.03                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L312     | 0 | 16.72        | 28.61 | -0.23       | -0.16 | .72                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L360     | 0 | 16.73        | 28.69 | -0.16       | -0.14 | 1.39                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L291     | 0 | 16.73        | 30.00 | 1.00        | .49   | .90                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L264     | 0 | 16.80        | 28.73 | -0.08       | -0.17 | 1.05                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L344     | 0 | 16.87        | 32.37 | 3.15        | 1.49  | 1.01                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L121     | 0 | 16.89        | 26.80 | -1.74       | -1.18 | .85                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L278     | 0 | 16.90        | 27.90 | -0.77       | -0.66 | 1.09                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L225     | 0 | 16.90        | 29.80 | .90         | .25   | 1.21                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L568     | 0 | 16.97        | 28.67 | -0.06       | -0.35 | .94                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L366     | 0 | 17.40        | 28.70 | .17         | -0.72 | 1.22                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L599     | 0 | 17.41        | 29.01 | .45         | -0.58 | 1.07                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L167     | 0 | 17.43        | 28.00 | -0.43       | -1.08 | .73                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L356     | 0 | 17.50        | 26.91 | -1.36       | -1.66 | 1.26                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L150     | 0 | 17.67        | 29.27 | .80         | -0.66 | .88                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L243     | 0 | 17.67        | 29.37 | .89         | -0.63 | 1.10                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L330     | 0 | 17.90        | 29.90 | 1.47        | -0.58 | 1.02                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L311     | 0 | 17.93        | 30.07 | 1.63        | -0.53 | .80                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L251     | * | 18.12        | 30.16 | 1.80        | -0.66 | 1.11                    | 10V | BURSTING STRENGTH UP T0 45 PSI, L*W, MANUAL CLAMP, 20C, 65% RH |                        |
| L390     | 0 | 18.27        | 30.47 | 2.14        | -0.64 | .96                     | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L128     | * | 18.33        | 30.53 | 2.23        | -0.66 | .74                     | 10B | BURSTING STRENGTH UP T0 45 PSI, PERKINS B,                     | MANUAL CLAMP           |
| L315     | 0 | 18.73        | 31.57 | 3.33        | -0.52 | 1.25                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L299     | 0 | 18.93        | 34.00 | 5.56        | .46   | 1.32                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L207     | 0 | 19.20        | 32.10 | 4.02        | -0.68 | 1.19                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L223A    | 0 | 19.28        | 33.53 | 5.32        | -0.67 | 1.09                    | 10C | BURSTING STRENGTH UP T0 45 PSI, PERKINS C,                     | MANUAL CLAMP           |
| L242     | * | 19.45        | 29.48 | 1.84        | -2.14 | 1.00                    | 10T | BURSTING STRENGTH UP T0 45 PSI, L*W, MANUAL CLAMP              |                        |
| L269     | * | 24.47        | 37.40 | 11.19       | -2.78 | 1.35                    | 10A | BURSTING STRENGTH UP T0 45 PSI, PERKINS A,                     | MANUAL CLAMP           |
| GMEANS:  |   | 16.69        | 28.89 |             |       | 1.00                    |     |  |                        |
|          |   | 95% ELLIPSE: |       | 6.07        | 2.05  | WITH GAMMA = 61 DEGREES |     |  |                        |

# BURSTING STRENGTH, MODEL C

SAMPLE H63 = 16.7 PSI      SAMPLE J39 = 28.9 PSI  
 SAMPLE H63 = 115 KILOPASCAL      SAMPLE J39 = 199 KILOPASCAL



TAPPI STANDARD T403 6S-76, BURSTING STRENGTH OF PAPER - PERKINS MODEL C-A OR C WITH AIR OR HYDRAULIC CLAMPS

| LAB CODE | SAMPLE H63 |       | PRINTING 77 GRAMS PER SQUARE METER |      |        |       | SAMPLE J39 |        | PRINTING 149 GRAMS PER SQUARE METER |        |     |   | TEST D. = 15 |  |  |
|----------|------------|-------|------------------------------------|------|--------|-------|------------|--------|-------------------------------------|--------|-----|---|--------------|--|--|
|          | MEAN       | DEV   | N. DEV                             | SDR  | R. SDR | MEAN  | DEV        | N. DEV | SDR                                 | R. SDR | VAR | F | LAB          |  |  |
| L100     | 17.79      | 1.13  | .69                                | .85  | .74    | 29.05 | .35        | .18    | 1.37                                | .93    | 10D | 0 | L100         |  |  |
| L105     | 12.67      | -3.99 | -2.46                              | .86  | .75    | 24.37 | -4.33      | -2.25  | 1.66                                | 1.13   | 10D | 0 | L105         |  |  |
| L122     | 17.73      | 1.08  | .66                                | 1.03 | .90    | 30.80 | 2.10       | 1.09   | .56                                 | .38    | 10F | 0 | L122         |  |  |
| L125     | 13.40      | -3.26 | -2.01                              | 1.64 | 1.43   | 24.80 | -3.90      | -2.02  | 2.24                                | 1.52   | 10D | 0 | L125         |  |  |
| L141     | 16.57      | -.09  | -.06                               | 1.39 | 1.21   | 28.20 | -.50       | -.26   | 1.80                                | 1.22   | 10D | 0 | L141         |  |  |
| L148     | 17.87      | 1.21  | .74                                | .92  | .80    | 28.53 | -.17       | -.09   | 1.73                                | 1.17   | 10D | 0 | L148         |  |  |
| L159     | 15.41      | -1.25 | -.77                               | 1.19 | 1.04   | 27.55 | -1.15      | -.60   | 1.23                                | .84    | 10D | 0 | L159         |  |  |
| L162     | 15.47      | -1.19 | -.73                               | .74  | .65    | 27.13 | -1.57      | -.81   | 1.77                                | 1.20   | 10D | 0 | L162         |  |  |
| L163     | 16.63      | -.02  | -.02                               | 1.04 | .91    | 28.80 | .10        | .05    | 1.84                                | 1.25   | 10D | 0 | L163         |  |  |
| L166     | 15.37      | -.29  | -.18                               | 1.53 | 1.34   | 29.17 | .47        | .24    | 1.81                                | 1.02   | 10D | 0 | L166         |  |  |
| L176     | 19.32      | 2.68  | 1.65                               | .62  | .54    | 30.13 | 1.43       | .74    | 1.19                                | .81    | 10D | 0 | L176         |  |  |
| L185     | 18.00      | 1.34  | .83                                | .76  | .66    | 31.00 | 2.30       | 1.19   | 1.77                                | 1.21   | 10D | 0 | L185         |  |  |
| L190C    | 15.97      | -.69  | -.43                               | 1.52 | 1.33   | 28.37 | -.33       | -.17   | .93                                 | .64    | 10D | 0 | L190C        |  |  |
| L217     | 17.67      | 1.01  | .62                                | .82  | .71    | 28.67 | -.03       | -.02   | 1.35                                | .91    | 10P | 0 | L217         |  |  |
| L224     | 17.23      | .58   | .35                                | 1.40 | 1.23   | 29.07 | .37        | .19    | 1.46                                | .99    | 10D | 0 | L224         |  |  |
| L226B    | 17.71      | 1.05  | .65                                | 1.06 | .93    | 28.98 | .28        | .14    | 1.42                                | .96    | 10D | 0 | L226B        |  |  |
| L226C    | 14.37      | -2.29 | -1.41                              | 1.04 | .91    | 26.53 | -2.17      | -1.12  | 1.76                                | 1.19   | 10D | 0 | L226C        |  |  |
| L255     | 16.20      | -.46  | -.28                               | .77  | .68    | 26.67 | -2.03      | -1.05  | .72                                 | .49    | 10D | 0 | L255         |  |  |
| L257A    | 17.60      | .94   | .58                                | 1.30 | 1.14   | 31.60 | 2.90       | 1.50   | 2.13                                | 1.45   | 10D | 0 | L257A        |  |  |
| L257B    | 17.13      | .48   | .29                                | 1.41 | 1.23   | 31.60 | 2.90       | 1.50   | 1.30                                | .88    | 10D | 0 | L257B        |  |  |
| L257C    | 17.60      | .94   | .58                                | 1.30 | 1.14   | 32.00 | 3.30       | 1.71   | 1.65                                | 1.12   | 10D | 0 | L257C        |  |  |
| L262     | 17.57      | .91   | .56                                | 1.05 | .92    | 30.60 | 1.90       | .98    | 1.53                                | 1.04   | 10D | 0 | L262         |  |  |
| L275     | 13.88      | -2.78 | -1.71                              | 1.33 | 1.16   | 26.29 | -2.41      | -1.25  | 1.73                                | 1.18   | 10D | 0 | L275         |  |  |
| L280     | 18.26      | 1.60  | .99                                | .88  | .77    | 29.73 | 1.03       | .53    | 1.00                                | .68    | 10D | 0 | L280         |  |  |
| L285     | 16.60      | -.66  | -.04                               | 1.55 | 1.36   | 29.47 | .77        | .40    | 1.51                                | 1.02   | 10D | 0 | L285         |  |  |
| L309     | 13.73      | -2.93 | -1.81                              | 1.27 | 1.11   | 26.57 | -2.13      | -1.10  | 1.39                                | .95    | 10D | 0 | L309         |  |  |
| L352     | 16.50      | -.16  | -.10                               | .86  | .75    | 26.54 | -2.16      | -1.12  | 1.18                                | .80    | 10D | 0 | L352         |  |  |
| L378     | 18.07      | 1.41  | .87                                | 1.44 | 1.26   | 28.67 | -.03       | -.02   | 1.54                                | 1.05   | 10D | 0 | L378         |  |  |
| L575     | 18.51      | 1.85  | 1.14                               | 1.68 | 1.47   | 28.93 | .23        | .12    | 1.71                                | 1.16   | 10D | 0 | L575         |  |  |
| L581     | 17.67      | 1.01  | .62                                | 1.45 | 1.27   | 29.13 | .43        | .22    | 1.55                                | 1.06   | 10D | 0 | L581         |  |  |
| L587     | 16.93      | .28   | .17                                | .73  | .64    | 30.77 | 2.07       | 1.07   | 1.08                                | .74    | 10D | 0 | L587         |  |  |

GR. MEAN = 16.66 PSI  
SD MEANS = 1.62 PSI

GRAND MEAN = 28.70 PSI  
SD OF MEANS = 1.93 PSI

TEST DETERMINATIONS = 15  
31 LABS IN GRAND MEANS

GR. MEAN = 114.9 KILOPASCAL  
AVERAGE SDR = 1.14 PSI

GRAND MEAN = 197.9 KILOPASCAL  
AVERAGE SDR = 1.47 PSI

L442 145.33 128.67 79.25 20.14 17.63 281.27 252.57 130.85 44.50 30.25 10Q \* L442  
TOTAL NUMBER OF LABORATORIES REPORTING = 32

Best values: H63 17.0 ± 2.8 psi  
J39 28.9 ± 2.6 psi

TAPPI STANDARD T403 69-76, BURSTING STRENGTH OF PAPER - PERKINS MODEL C-A OR C WITH AIR OR HYDRAULIC CLAMPS

| LAB<br>CODE | P | MEANS        |        | COORDINATES |       | AVG                     |     | PROPERTY--- | TEST     | INSTRUMENT--- | CONDITIONS                                    |
|-------------|---|--------------|--------|-------------|-------|-------------------------|-----|-------------|----------|---------------|---|
|             |   | H63          | J39    | MAJOR       | MINOR | R.SDR                   | VAR |             |          |               |   |
| L105        | Ø | 12.67        | 24.37  | -5.88       | .39   | .94                     | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L125        | Ø | 13.40        | 24.80  | -5.08       | .09   | 1.48                    | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L309        | Ø | 13.73        | 26.57  | -3.49       | .95   | 1.03                    | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L275        | Ø | 13.88        | 26.29  | -3.62       | .66   | 1.17                    | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L226C       | Ø | 14.37        | 26.53  | -3.13       | .43   | 1.05                    | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L159        | Ø | 15.41        | 27.55  | -1.68       | .25   | .94                     | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L162        | Ø | 15.47        | 27.13  | -1.97       | -.05  | .93                     | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L190C       | Ø | 15.97        | 28.37  | -.69        | .33   | .98                     | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L255        | Ø | 16.20        | 26.67  | -1.87       | -.92  | .59                     | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L166        | Ø | 16.37        | 29.17  | .18         | .52   | 1.18                    | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L352        | Ø | 16.50        | 26.54  | -1.78       | -1.23 | .78                     | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L141        | Ø | 16.57        | 28.20  | -.45        | -.24  | 1.22                    | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L285        | Ø | 16.60        | 29.47  | .56         | .53   | 1.19                    | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L163        | Ø | 16.63        | 28.80  | .06         | .08   | 1.08                    | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L587        | Ø | 16.93        | 30.77  | 1.78        | 1.08  | .69                     | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L257B       | Ø | 17.13        | 31.60  | 2.56        | 1.45  | 1.06                    | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L224        | Ø | 17.23        | 29.07  | .65         | -.22  | 1.11                    | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L262        | Ø | 17.57        | 30.60  | 2.05        | .48   | .98                     | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L257C       | Ø | 17.60        | 32.00  | 3.16        | 1.33  | 1.13                    | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L257A       | Ø | 17.60        | 31.60  | 2.85        | 1.08  | 1.29                    | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L581        | Ø | 17.67        | 29.13  | .97         | -.51  | 1.16                    | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L217        | Ø | 17.67        | 28.67  | .61         | -.81  | .81                     | 10F | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS C, H <sub>2</sub> O CLAMP, TRANSDUCER |
| L226B       | Ø | 17.71        | 28.98  | .87         | -.64  | .95                     | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L122        | Ø | 17.73        | 30.80  | 2.31        | .48   | .64                     | 10F | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS C, H <sub>2</sub> O CLAMP, TRANSDUCER |
| L100        | Ø | 17.79        | 29.05  | .98         | -.66  | .84                     | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L148        | Ø | 17.87        | 28.53  | .63         | -1.05 | .99                     | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L185        | Ø | 18.00        | 31.00  | 2.63        | .40   | .93                     | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L378        | Ø | 18.07        | 28.67  | .86         | -1.12 | 1.15                    | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L280        | Ø | 18.26        | 29.73  | 1.81        | -.60  | .73                     | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L575        | Ø | 18.51        | 28.93  | 1.34        | -1.29 | 1.32                    | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L176        | Ø | 19.33        | 30.13  | 2.79        | -1.19 | .67                     | 10D | BURSTING    | STRENGTH | UP TØ 45 PSI, | PERKINS CA ØR C, AIR CLAMP                    |
| L442        | * | 145.33       | 281.27 | 277.46      | 58.00 | 23.94                   | 10Q | BURSTING    | STRENGTH | UP TØ 45 PSI, | FRANK, HYD. CL.                               |
| GMEANS:     |   | 16.66        | 28.70  |             |       | 1.00                    |     |             |          |               |   |
|             |   | 95% ELLIPSE: |        | 6.28        | 2.10  | WITH GAMMA = 51 DEGREES |     |             |          |               |   |


# BURSTING STRENGTH, MODEL C-A

SAMPLE H63 = 16.7 PSI

SAMPLE J39 = 28.7 PSI

SAMPLE H63 = 115 KILOPASCAL

SAMPLE J39 = 198 KILOPASCAL



ANALYSIS T11-1 TABLE 1  
BURSTING STRENGTH, HIGH RANGE, PSI  
TAPPI STANDARD T403 CS-76, BURSTING STRENGTH OF PAPER - PERKINS MODEL C OR C-A

| LAB CODE                    | SAMPLE E77 MEAN | TUBE WINDING 132 GRAMS PER SQUARE METER |        |     |        | R. SDR                        | SAMPLE K29 MEAN | KRAFT 123 GRAMS PER SQUARE METER |        |      |        | TEST D. = 15             |       |     |
|-----------------------------|-----------------|---|--------|-----|--------|-------------------------------|-----------------|----------------------------------|--------|------|--------|--------------------------|-------|-----|
|                             |                 | DEV                                     | N. DEV | SDR | R. SDR |                               |                 | DEV                              | N. DEV | SDR  | R. SDR | VAR                      | F     | LAB |
| L100                        | 69.5            | -5.1                                    | -1.57  | 4.4 | .88    | 59.3                          | -0.1            | -0.03                            | 2.6    | .63  | 11D    | 0                        | L100  |     |
| L103                        | 74.9            | .3                                      | .09    | 4.4 | .88    | 63.3                          | 3.9             | 1.59                             | 2.9    | .70  | 11C    | 0                        | L103  |     |
| L107                        | 80.1            | 5.5                                     | 1.70   | 4.1 | .82    | 63.7                          | 4.3             | 1.74                             | 4.9    | 1.20 | 11C    | 0                        | L107  |     |
| L122                        | 73.1            | -1.5                                    | -0.45  | 5.4 | 1.10   | 58.9                          | -0.5            | -0.21                            | 5.1    | 1.23 | 11F    | 0                        | L122  |     |
| L128                        | 71.7            | -2.9                                    | -0.90  | 3.8 | .76    | 59.1                          | -0.3            | -0.11                            | 2.2    | .54  | 11D    | 0                        | L128  |     |
| L141                        | 74.1            | -0.5                                    | -0.15  | 5.7 | 1.16   | 61.2                          | 1.8             | .72                              | 5.3    | 1.29 | 11D    | 0                        | L141  |     |
| L148                        | 75.8            | 1.2                                     | .37    | 4.3 | .87    | 60.9                          | 1.5             | .60                              | 4.6    | 1.11 | 11D    | 0                        | L148  |     |
| L159                        | 73.0            | -1.6                                    | -0.48  | 7.4 | 1.49   | 54.5                          | -4.9            | -1.97                            | 4.4    | 1.08 | 11D    | 0                        | L159  |     |
| L170                        | 80.2            | 5.6                                     | 1.73   | 3.4 | .68    | 61.3                          | 1.9             | .79                              | 1.7    | .41  | 11C    | 0                        | L170  |     |
| L176                        | 78.6            | 4.0                                     | 1.23   | 5.6 | 1.13   | 59.5                          | .1              | .06                              | 3.9    | .96  | 11D    | 0                        | L176  |     |
| L182                        | 75.9            | 1.3                                     | .39    | 6.2 | 1.25   | 61.3                          | 1.9             | .76                              | 5.7    | 1.38 | 11D    | 0                        | L182  |     |
| L218                        | 77.7            | 3.1                                     | .96    | 6.1 | 1.23   | 60.8                          | 1.4             | .57                              | 5.2    | 1.27 | 11D    | 0                        | L218  |     |
| L232                        | 61.3            | -13.3                                   | -4.10  | 8.2 | 1.65   | 43.2                          | -16.2           | -6.59                            | 9.9    | 2.41 | 11C    | #                        | L232  |     |
| L237A                       | 73.6            | -1.0                                    | -0.32  | 1.9 | .39    | 61.4                          | 2.0             | .80                              | 3.1    | .77  | 11C    | 0                        | L237A |     |
| L237B                       | 72.4            | -2.2                                    | -0.68  | 1.5 | .29    | 60.2                          | .8              | .31                              | 2.5    | .60  | 11C    | 0                        | L237B |     |
| L238A                       | 78.3            | 3.7                                     | 1.14   | 7.1 | 1.44   | 59.2                          | -0.2            | -0.10                            | 4.4    | 1.06 | 11Y    | 0                        | L238A |     |
| L243                        | 72.8            | -1.8                                    | -0.55  | 3.9 | .79    | 59.4                          | .0              | .00                              | 4.1    | 1.01 | 11C    | 0                        | L243  |     |
| L278                        | 72.8            | -1.8                                    | -0.56  | 5.0 | 1.01   | 57.9                          | -1.5            | -0.62                            | 4.5    | 1.11 | 11C    | 0                        | L278  |     |
| L279                        | 72.1            | -2.5                                    | -0.77  | 5.0 | 1.01   | 57.2                          | -2.2            | -0.89                            | 5.6    | 1.36 | 11C    | 0                        | L279  |     |
| L280                        | 73.4            | -1.2                                    | -0.38  | 4.5 | .91    | 58.3                          | -1.1            | -0.46                            | 4.8    | 1.18 | 11D    | 0                        | L280  |     |
| L303                        | 70.6            | -4.0                                    | -1.22  | 5.4 | 1.09   | 56.2                          | -3.2            | -1.30                            | 3.1    | .75  | 11C    | 0                        | L303  |     |
| L330                        | 74.7            | .1                                      | .02    | 6.9 | 1.39   | 60.6                          | 1.2             | .49                              | 4.8    | 1.16 | 11C    | 0                        | L330  |     |
| L331                        | 71.1            | -3.5                                    | -1.07  | 5.5 | 1.10   | 55.9                          | -3.5            | -1.43                            | 3.1    | .75  | 11C    | 0                        | L331  |     |
| L333                        | 78.3            | 3.7                                     | 1.12   | 5.9 | 1.19   | 61.3                          | 1.9             | .79                              | 3.7    | .90  | 11C    | 0                        | L333  |     |
| L344                        | 72.0            | -2.6                                    | -0.81  | 2.7 | .54    | 60.3                          | .9              | .35                              | 2.8    | .69  | 11C    | 0                        | L344  |     |
| L356                        | 72.7            | -1.9                                    | -0.58  | 5.0 | 1.01   | 58.4                          | -1.0            | -0.40                            | 5.6    | 1.37 | 11C    | 0                        | L356  |     |
| L362                        | 67.9            | -6.7                                    | -2.07  | 6.0 | 1.21   | 55.0                          | -4.4            | -1.78                            | 5.0    | 1.22 | 11D    | 0                        | L362  |     |
| L378                        | 77.8            | 3.2                                     | .98    | 4.4 | .88    | 60.0                          | .6              | .25                              | 3.6    | .88  | 11D    | 0                        | L378  |     |
| L565                        | 71.8            | -2.8                                    | -0.87  | 2.8 | .57    | 59.8                          | .4              | .16                              | 1.8    | .45  | 11D    | 0                        | L565  |     |
| L575                        | 79.0            | 4.4                                     | 1.34   | 6.2 | 1.26   | 61.2                          | 1.8             | .71                              | 4.8    | 1.18 | 11D    | 0                        | L575  |     |
| L581                        | 74.9            | .3                                      | .08    | 4.3 | .87    | 56.6                          | -2.8            | -1.13                            | 4.8    | 1.17 | 11D    | 0                        | L581  |     |
| L599                        | 75.3            | .7                                      | .22    | 4.8 | .96    | 57.9                          | -1.5            | -0.59                            | 4.1    | 1.00 | 11C    | 0                        | L599  |     |
| L604                        | 76.2            | 1.6                                     | .49    | 7.1 | 1.43   | 59.3                          | -0.1            | -0.04                            | 5.8    | 1.43 | 11C    | 0                        | L604  |     |
| L622                        | 75.9            | 1.3                                     | .39    | 5.8 | 1.18   | 56.8                          | -2.6            | -1.06                            | 3.6    | .88  | 11E    | 0                        | L622  |     |
| L650                        | 71.6            | -3.0                                    | -0.92  | 6.2 | 1.24   | 56.4                          | -3.0            | -1.22                            | 5.2    | 1.27 | 11D    | 0                        | L650  |     |
| L651                        | 81.5            | 6.9                                     | 2.11   | 8.0 | 1.61   | 65.9                          | 6.5             | 2.66                             | 6.6    | 1.62 | 11D    | *                        | L651  |     |
| GR. MEAN = 74.6 PSI         |                 | AVERAGE SDR = 5.0 PSI                   |        |     |        | GRAND MEAN = 59.4 PSI         |                 | AVERAGE SDR = 4.1 PSI            |        |      |        | TEST DETERMINATIONS = 15 |       |     |
| SD MEANS = 3.3 PSI          |                 |   |        |     |        | SD OF MEANS = 2.5 PSI         |                 |                                  |        |      |        | 35 LABS IN GRAND MEANS   |       |     |
| GR. MEAN = 514.4 KILOPASCAL |                 |   |        |     |        | GRAND MEAN = 409.5 KILOPASCAL |                 |                                  |        |      |        |                          |       |     |
| L242                        | 76.3            | 1.7                                     | .53    | 4.5 | .91    | 61.9                          | 2.5             | 1.02                             | 6.2    | 1.51 | 11T    | *                        | L242  |     |
| L251                        | 69.6            | -5.0                                    | -1.52  | 6.8 | 1.38   | 55.9                          | -3.5            | -1.41                            | 4.1    | 1.00 | 11V    | *                        | L251  |     |
| L393                        | 73.4            | -1.2                                    | -0.37  | 5.6 | 1.13   | 58.8                          | -0.6            | -0.24                            | 2.9    | .72  | 11E    | *                        | L393  |     |
| L394                        | 88.0            | 13.4                                    | 4.12   | 6.6 | 1.34   | 70.5                          | 11.1            | 4.50                             | 3.8    | .92  | 11H    | *                        | L394  |     |
| L484                        | 82.0            | 7.4                                     | 2.27   | 2.3 | .46    | 68.5                          | 9.1             | 3.71                             | 1.6    | .39  | 11H    | *                        | L484  |     |
| L570                        | 78.7            | 4.1                                     | 1.25   | 6.6 | 1.32   | 64.9                          | 5.5             | 2.22                             | 3.9    | .95  | 11H    | *                        | L570  |     |
| L576                        | 79.8            | 5.2                                     | 1.61   | 6.1 | 1.23   | 64.5                          | 5.1             | 2.09                             | 5.8    | 1.41 | 11P    | *                        | L576  |     |
| L593                        | 89.5            | 14.9                                    | 4.57   | 8.5 | 1.71   | 74.3                          | 14.9            | 6.04                             | 5.6    | 1.36 | 11J    | *                        | L593  |     |
| L598                        | 80.4            | 5.8                                     | 1.78   | 6.7 | 1.34   | 67.2                          | 7.8             | 3.17                             | 6.4    | 1.55 | 11*    | *                        | L598  |     |

TOTAL NUMBER OF LABORATORIES REPORTING = 45

Best values: E77 74 ± 5 psi  
K29 59 ± 4 psi

The following laboratories were omitted from the grand means because of extreme test results: 232

ANALYSIS T11-1 TABLE 2

BURSTING STRENGTH, HIGH RANGE, PSI

TAPPI STANDARD T403 GS=76, BURSTING STRENGTH OF PAPER = PERKINS MODEL C OR C-A

| LAB CODE | P | MEANS        |      | COORDINATES |       | AVG R.SDR               | VAR | PROPERTY | TEST     | INSTRUMENT    | CONDITIONS                      |
|----------|---|--------------|------|-------------|-------|-------------------------|-----|----------|----------|---------------|---------------------------------|
|          |   | E77          | K29  | MAJOR       | MINOR |                         |     |          |          |               |                                 |
| L232     | # | 61.3         | 43.2 | -20.1       | -6.3  | 2.03                    | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L362     | Ø | 67.9         | 55.0 | -8.0        | .0    | 1.21                    | 11D | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L100     | Ø | 69.5         | 59.3 | -4.3        | 2.7   | .75                     | 11D | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L251     | * | 69.6         | 55.9 | -6.1        | -2    | 1.19                    | 11V | BURSTING | STRENGTH | 40 = 100 PSI, | L*W, MANUAL CLAMP, 20C, 65% RH  |
| L303     | Ø | 70.6         | 56.2 | -5.1        | -5    | .92                     | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L331     | Ø | 71.1         | 55.9 | -4.8        | -1.0  | .93                     | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L650     | Ø | 71.6         | 56.4 | -4.2        | -9    | 1.25                    | 11D | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L128     | Ø | 71.7         | 59.1 | -2.6        | 1.4   | .65                     | 11D | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L565     | Ø | 71.8         | 59.8 | -2.2        | 1.9   | .51                     | 11D | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L344     | Ø | 72.0         | 60.3 | -1.7        | 2.2   | .61                     | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L279     | Ø | 72.1         | 57.2 | -3.3        | -5    | 1.19                    | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L237B    | Ø | 72.4         | 60.2 | -1.4        | 1.9   | .45                     | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L356     | Ø | 72.7         | 58.4 | -2.1        | .2    | 1.19                    | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L278     | Ø | 72.8         | 57.9 | -2.3        | -3    | 1.06                    | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L243     | Ø | 72.8         | 59.4 | -1.5        | 1.0   | .90                     | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L159     | Ø | 73.0         | 54.5 | -4.0        | -3.2  | 1.28                    | 11D | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L122     | Ø | 73.1         | 58.9 | -1.5        | .4    | 1.17                    | 11F | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, B. CLAMP, TRANSDUCER |
| L280     | Ø | 73.4         | 58.3 | -1.6        | -3    | 1.04                    | 11D | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L393     | * | 73.4         | 58.8 | -1.3        | .2    | .92                     | 11H | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS AB, HYDRAULIC CLAMP     |
| L237A    | Ø | 73.6         | 61.4 | .2          | 2.2   | .58                     | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L141     | Ø | 74.1         | 61.2 | .6          | 1.7   | 1.22                    | 11D | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L330     | Ø | 74.7         | 60.6 | .7          | 1.0   | 1.28                    | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L581     | Ø | 74.9         | 56.6 | -1.3        | -2.5  | 1.02                    | 11D | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L103     | Ø | 74.9         | 63.3 | 2.4         | 3.1   | .79                     | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L599     | Ø | 75.3         | 57.9 | -2          | -1.6  | .98                     | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L148     | Ø | 75.8         | 60.9 | 1.8         | .6    | .99                     | 11D | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L182     | Ø | 75.9         | 61.3 | 2.1         | .9    | 1.32                    | 11D | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L622     | Ø | 75.9         | 56.8 | -4          | -2.9  | 1.03                    | 11E | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L604     | Ø | 76.2         | 59.3 | 1.3         | -1.0  | 1.43                    | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L242     | * | 76.3         | 61.9 | 2.8         | 1.2   | 1.21                    | 11T | BURSTING | STRENGTH | 40 = 100 PSI, | L*W, MANUAL CLAMP               |
| L218     | Ø | 77.7         | 60.8 | 3.4         | -5    | 1.25                    | 11D | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L378     | Ø | 77.8         | 60.0 | 3.0         | -1.2  | .88                     | 11D | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L333     | Ø | 78.3         | 61.3 | 4.1         | -4    | 1.04                    | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L238A    | Ø | 78.3         | 59.2 | 3.0         | -2.2  | 1.25                    | 11Y | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L176     | Ø | 78.6         | 59.5 | 3.4         | -2.1  | 1.04                    | 11D | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L570     | * | 78.7         | 64.9 | 6.4         | 2.4   | 1.14                    | 11H | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS AB, HYDRAULIC CLAMP     |
| L575     | Ø | 79.0         | 61.2 | 4.6         | -9    | 1.22                    | 11D | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L576     | * | 79.8         | 64.5 | 7.2         | 1.4   | 1.32                    | 11P | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS LC, MANUAL CLAMP        |
| L107     | Ø | 80.1         | 63.7 | 7.0         | .5    | 1.01                    | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L170     | Ø | 80.2         | 61.3 | 5.8         | -1.5  | .55                     | 11C | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS C, MANUAL CLAMP         |
| L598     | * | 80.4         | 67.2 | 9.1         | 3.4   | 1.45                    | 11* | BURSTING | STRENGTH | 40 = 100 PSI, | MESSMER, MANUAL CLAMP           |
| L651     | * | 81.5         | 65.9 | 9.3         | 1.7   | 1.61                    | 11D | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS CA, AIR CLAMP           |
| L484     | * | 82.0         | 68.5 | 11.2        | 3.6   | .42                     | 11H | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS AB, HYDRAULIC CLAMP     |
| L394     | * | 88.0         | 70.5 | 17.3        | 1.9   | 1.13                    | 11H | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS AB, HYDRAULIC CLAMP     |
| L593     | * | 89.5         | 74.3 | 20.6        | 4.3   | 1.53                    | 11J | BURSTING | STRENGTH | 40 = 100 PSI, | PERKINS JUMBO, HAND DRIVEN      |
| GMBANS:  |   | 74.6         | 59.4 |             |       | 1.00                    |     |          |          |               |                                 |
|          |   | 95% ELLIPSE: |      | 9.7         | 4.2   | WITH GAMMA = 33 DEGREES |     |          |          |               |                                 |


# BURSTING STRENGTH, HIGH RANGE

SAMPLE E77 = 74.6 PSI

SAMPLE K29 = 59.4 PSI

SAMPLE E77 = 514 KILOPASCAL

SAMPLE K29 = 410 KILOPASCAL



TAPPI STANDARD T414 TS-65, ANY MAKE BLEND OR P WITH DEEP CUTOUT IS STANDARD FOR THIS ANALYSIS

| LAB CODE | SAMPLE E76 116 GRAMS PER SQUARE METER |       |        |     |        | SAMPLE E80 69 GRAMS PER SQUARE METER |       |        |     |        | TEST D. = 15 |   |       |
|----------|---------------------------------------|-------|--------|-----|--------|--------------------------------------|-------|--------|-----|--------|--------------|---|-------|
|          | MEAN                                  | DEV   | N. DEV | SDR | R. SDR | MEAN                                 | DEV   | N. DEV | SDR | R. SDR | VAR          | F | LAB   |
| L100     | 64.5                                  | -1.4  | 0.36   | 2.6 | 1.01   | 53.9                                 | -3.8  | -1.03  | 1.0 | .68    | 15M          | 0 | L100  |
| L103     | 82.1                                  | -3.7  | 0.98   | 1.5 | .60    | 55.1                                 | -2.5  | 0.68   | .9  | .62    | 15T          | 0 | L103  |
| L105     | 84.6                                  | -1.3  | 0.34   | 3.3 | 1.31   | 55.1                                 | -2.5  | 0.68   | 1.1 | .72    | 15T          | 0 | L105  |
| L107     | 88.5                                  | 2.7   | .69    | 4.7 | 1.88   | 65.6                                 | 8.0   | 2.16   | 9.7 | 6.55   | 15T          | * | L107  |
| L121     | 82.9                                  | -2.9  | 0.77   | 3.0 | 1.19   | 57.9                                 | .2    | .06    | 1.2 | .81    | 15T          | 0 | L121  |
| L122     | 60.6                                  | -5.3  | -1.38  | 2.3 | .93    | 54.1                                 | -3.5  | 0.95   | 1.0 | .68    | 15C          | 0 | L122  |
| L124     | 87.6                                  | 1.7   | .45    | 3.3 | 1.31   | 60.3                                 | 2.6   | .71    | .7  | .48    | 15T          | 0 | L124  |
| L126     | 88.3                                  | 2.4   | .62    | 2.3 | .93    | 59.1                                 | 1.4   | .39    | 2.2 | 1.46   | 15T          | 0 | L126  |
| L128     | 84.9                                  | 0.9   | 0.25   | 1.5 | .59    | 56.0                                 | -1.6  | 0.45   | 1.7 | 1.15   | 15T          | 0 | L128  |
| L131     | 82.1                                  | -3.7  | 0.98   | 5.0 | 1.98   | 54.9                                 | -2.7  | 0.74   | 1.8 | 1.24   | 15A          | 0 | L131  |
| L134     | 86.3                                  | .5    | .12    | 2.1 | .83    | 56.7                                 | 0.9   | 0.25   | 1.0 | .65    | 15C          | 0 | L134  |
| L139     | 92.1                                  | 6.3   | 1.63   | 1.6 | .65    | 63.8                                 | 6.2   | 1.67   | 1.7 | 1.15   | 15T          | 0 | L139  |
| L141     | 85.9                                  | .1    | .01    | 3.1 | 1.22   | 57.6                                 | 0.0   | 0.01   | .8  | .56    | 15T          | 0 | L141  |
| L143     | 67.5                                  | 1.6   | .41    | 4.1 | 1.61   | 57.7                                 | .0    | .01    | 2.8 | 1.88   | 15T          | 0 | L143  |
| L145     | 82.1                                  | -3.7  | 0.98   | 2.8 | 1.10   | 72.7                                 | 15.0  | 4.08   | 1.8 | 1.22   | 15T          | # | L145  |
| L148     | 84.8                                  | -1.1  | 0.28   | 3.1 | 1.23   | 65.1                                 | 7.4   | 2.01   | 1.7 | 1.13   | 15T          | * | L148  |
| L150     | 87.9                                  | 2.1   | .54    | 2.6 | 1.02   | 57.9                                 | .3    | .08    | 1.2 | .79    | 15T          | 0 | L150  |
| L151     | 93.7                                  | 7.8   | 2.03   | 2.7 | 1.08   | 66.0                                 | 8.4   | 2.27   | 1.6 | 1.09   | 15C          | 0 | L151  |
| L158     | 82.3                                  | -3.6  | 0.94   | 4.9 | 1.96   | 58.4                                 | .8    | .20    | 2.2 | 1.47   | 15R          | 0 | L158  |
| L159     | 67.7                                  | 1.9   | .48    | 3.0 | 1.18   | 58.0                                 | .4    | .10    | 2.7 | 1.83   | 15L          | 0 | L159  |
| L162     | 87.1                                  | 1.2   | .31    | 2.5 | .99    | 57.6                                 | 0.0   | 0.01   | 1.1 | .76    | 15T          | 0 | L162  |
| L163     | 64.9                                  | -1.0  | 0.27   | 2.8 | 1.12   | 57.5                                 | 0.2   | 0.05   | 1.8 | 1.20   | 15T          | 0 | L163  |
| L166     | 88.7                                  | 2.8   | .73    | 2.5 | .98    | 58.2                                 | .6    | .15    | 1.4 | .93    | 15T          | 0 | L166  |
| L167     | 85.3                                  | 0.5   | 0.14   | 1.0 | .39    | 60.7                                 | 3.0   | .82    | 1.0 | .66    | 15C          | 0 | L167  |
| L170     | 83.5                                  | -2.3  | 0.61   | .9  | .36    | 54.4                                 | -3.2  | 0.88   | .8  | .56    | 15T          | 0 | L170  |
| L173B    | 84.8                                  | -1.1  | 0.28   | 1.7 | .66    | 61.6                                 | 4.0   | 1.07   | 1.1 | .76    | 15T          | 0 | L173B |
| L176     | 87.9                                  | 2.0   | .52    | 2.3 | .92    | 58.0                                 | .4    | .10    | 1.7 | 1.15   | 15T          | 0 | L176  |
| L182A    | 79.1                                  | -6.7  | -1.76  | 3.9 | 1.55   | 52.3                                 | -5.4  | -1.46  | 1.3 | .87    | 15A          | 0 | L182A |
| L182T    | 90.3                                  | 4.4   | 1.15   | 3.2 | 1.29   | 60.1                                 | 2.5   | .67    | 1.2 | .85    | 15T          | 0 | L182T |
| L183     | 87.1                                  | 1.2   | .31    | 2.8 | 1.12   | 56.1                                 | -1.5  | 0.41   | .6  | .43    | 15T          | 0 | L183  |
| L185     | 87.5                                  | -2.3  | 0.61   | 2.6 | 1.03   | 58.1                                 | .5    | .13    | 1.4 | .92    | 15T          | 0 | L185  |
| L189     | 86.2                                  | .3    | .08    | 2.6 | 1.03   | 56.2                                 | -1.4  | 0.39   | 1.2 | .82    | 15T          | 0 | L189  |
| L190C    | 84.6                                  | -1.3  | 0.34   | 2.5 | .59    | 58.3                                 | .6    | .17    | 1.7 | 1.13   | 15T          | 0 | L190C |
| L190R    | 85.1                                  | .2    | .05    | 2.4 | .95    | 56.9                                 | 0.7   | 0.19   | 1.6 | 1.07   | 15C          | 0 | L190R |
| L191     | 79.4                                  | -6.5  | -1.69  | 2.4 | .95    | 51.0                                 | -6.6  | -1.80  | 2.5 | 1.70   | 15T          | 0 | L191  |
| L195     | 89.5                                  | 3.6   | .94    | 2.6 | 1.02   | 56.1                                 | -1.5  | 0.41   | 1.2 | .81    | 15C          | 0 | L195  |
| L206     | 68.9                                  | 3.0   | .79    | 1.9 | .75    | 60.3                                 | 2.6   | .72    | 1.8 | 1.22   | 15R          | 0 | L206  |
| L207     | 74.4                                  | -11.5 | -2.99  | 1.6 | .65    | 47.1                                 | -10.5 | -2.85  | 2.5 | 1.67   | 15R          | * | L207  |
| L211     | 83.7                                  | -2.1  | 0.56   | 1.8 | .71    | 55.7                                 | -1.9  | 0.52   | 1.2 | .83    | 15R          | 0 | L211  |
| L212     | 80.8                                  | -5.1  | -1.33  | 3.8 | 1.49   | 56.0                                 | -1.6  | 0.45   | 1.5 | 1.03   | 15T          | 0 | L212  |
| L213     | 83.2                                  | -2.7  | 0.70   | 2.4 | .94    | 59.9                                 | 2.2   | .60    | 1.2 | .81    | 15T          | 0 | L213  |
| L217     | 86.4                                  | .5    | .14    | 1.8 | .72    | 56.9                                 | 0.7   | 0.20   | 1.1 | .77    | 15R          | 0 | L217  |
| L223     | 86.3                                  | .4    | .11    | 2.4 | .95    | 58.0                                 | .4    | .10    | 1.3 | .86    | 15R          | 0 | L223  |
| L224     | 84.7                                  | -1.1  | 0.30   | 1.7 | .68    | 58.8                                 | 1.2   | .31    | 1.0 | .69    | 15T          | 0 | L224  |
| L225     | 86.9                                  | 1.0   | .26    | 1.7 | .68    | 56.5                                 | -1.2  | 0.32   | 1.6 | 1.08   | 15T          | 0 | L225  |
| L226B    | 61.1                                  | -4.8  | -1.26  | 4.7 | 1.85   | 60.4                                 | 2.8   | .75    | 1.7 | 1.17   | 15T          | * | L226B |
| L226C    | 79.2                                  | -6.7  | -1.75  | 2.4 | .94    | 54.3                                 | -3.4  | 0.92   | 1.5 | 1.01   | 15T          | 0 | L226C |
| L228     | 84.5                                  | -1.3  | 0.35   | 1.6 | .63    | 55.5                                 | -2.2  | 0.59   | 1.4 | .96    | 15T          | 0 | L228  |
| L230     | 76.7                                  | 0.9   | 0.239  | 1.9 | .76    | 51.4                                 | -6.2  | -1.68  | 1.2 | .81    | 15R          | 0 | L230  |
| L232     | 85.9                                  | 1.1   | .27    | 2.8 | 1.12   | 60.5                                 | 2.9   | .78    | 1.6 | 1.08   | 15T          | 0 | L232  |
| L236     | 87.7                                  | 1.8   | .47    | 3.1 | 1.24   | 55.6                                 | -2.0  | 0.56   | 1.1 | .76    | 15T          | 0 | L236  |
| L237A    | 83.5                                  | -2.3  | 0.61   | 2.2 | .87    | 57.3                                 | 0.4   | 0.10   | 1.3 | .91    | 15T          | 0 | L237A |
| L237B    | 83.7                                  | -2.1  | 0.56   | 1.7 | .68    | 55.8                                 | -1.8  | 0.50   | 1.3 | .90    | 15T          | 0 | L237B |
| L238A    | 83.5                                  | -2.4  | 0.63   | 2.9 | 1.14   | 54.0                                 | -3.6  | 0.99   | .8  | .51    | 15T          | 0 | L238A |
| L243     | 89.3                                  | 3.5   | .90    | 2.7 | 1.07   | 60.4                                 | 2.8   | .75    | 1.2 | .80    | 15T          | 0 | L243  |
| L244     | 92.9                                  | 7.1   | 1.84   | 2.1 | .81    | 58.1                                 | .4    | .11    | 1.0 | .65    | 15C          | * | L244  |
| L249     | 88.9                                  | 3.0   | .78    | 3.8 | 1.51   | 61.8                                 | 4.1   | 1.11   | 1.4 | .95    | 15T          | 0 | L249  |
| L254     | 84.7                                  | -1.1  | 0.30   | 2.5 | 1.00   | 58.0                                 | .4    | .10    | 1.0 | .68    | 15T          | 0 | L254  |
| L255     | 85.5                                  | 0.3   | 0.09   | 1.9 | .76    | 55.5                                 | -2.1  | 0.57   | .8  | .57    | 15T          | 0 | L255  |
| L257A    | 85.5                                  | 0.4   | 0.11   | 1.6 | .63    | 59.9                                 | 2.2   | .60    | 1.9 | 1.30   | 15C          | 0 | L257A |
| L257B    | 85.6                                  | 0.3   | 0.07   | 2.0 | .80    | 60.0                                 | 2.4   | .64    | 1.7 | 1.15   | 15C          | 0 | L257B |
| L257C    | 85.2                                  | 0.7   | 0.18   | 3.1 | 1.23   | 60.5                                 | 2.9   | .78    | 1.8 | 1.20   | 15C          | 0 | L257C |
| L259     | 89.1                                  | 3.2   | .83    | 2.3 | .92    | 60.1                                 | 2.4   | .66    | 1.2 | .79    | 15T          | 0 | L259  |
| L261     | 82.4                                  | -3.5  | 0.91   | 2.8 | 1.10   | 56.9                                 | 0.7   | 0.19   | 1.2 | .83    | 15T          | 0 | L261  |
| L262     | 86.5                                  | .6    | .15    | 2.0 | .78    | 55.4                                 | -2.2  | 0.61   | 1.6 | 1.11   | 15T          | 0 | L262  |

TAPPI STANDARD T414 TS-65. ANY MAKE ELMENDORF WITH DEEP CUTOUT IS STANDARD FOR THIS ANALYSIS

| LAB CODE | PRINTING<br>E76 116 GRAMS PER SQUARE METER |       |        |     |       | WRITING<br>E80 69 GRAMS PER SQUARE METER |       |        |     |       | TEST D. # 15 |   |      |
|----------|--|-------|--------|-----|-------|--|-------|--------|-----|-------|--------------|---|------|
|          | MEAN                                       | DEV   | N.DEV  | SDR | R.SDR | MEAN                                     | DEV   | N.DEV  | SDR | R.SDR | VAR          | F | LAB  |
| L264     | 76.3                                       | -9.6  | -2.51  | 2.8 | 1.12  | 59.5                                     | 1.8   | .49    | 3.0 | 2.02  | 15T          | X | L264 |
| L273     | 87.1                                       | 1.2   | .31    | 2.7 | 1.05  | 62.7                                     | 5.1   | 1.38   | 1.1 | .75   | 15T          | Ø | L273 |
| L275     | 89.3                                       | 3.5   | .90    | 1.8 | .70   | 56.5                                     | -1.1  | -.30   | 1.6 | 1.05  | 15T          | Ø | L275 |
| L278     | 86.4                                       | .5    | .14    | 2.3 | .91   | 51.1                                     | -6.6  | -1.79  | 1.5 | 1.04  | 15T          | * | L278 |
| L279     | 83.6                                       | -2.3  | -.60   | 3.0 | 1.21  | 57.1                                     | -.6   | -.16   | 1.8 | 1.24  | 15T          | Ø | L279 |
| L280     | 87.8                                       | 1.9   | .50    | 2.0 | .78   | 56.0                                     | -1.6  | -.45   | .9  | .63   | 15L          | Ø | L280 |
| L281     | 86.1                                       | .2    | .05    | 2.9 | 1.14  | 54.7                                     | -2.9  | -.79   | 1.5 | 1.04  | 15T          | Ø | L281 |
| L285     | 89.5                                       | 3.6   | .94    | 2.3 | .92   | 60.9                                     | 3.3   | .89    | 1.8 | 1.24  | 15T          | Ø | L285 |
| L288     | 88.8                                       | 2.9   | .76    | 2.0 | .78   | 60.6                                     | 2.9   | .80    | .7  | .50   | 15Q          | Ø | L288 |
| L291     | 81.9                                       | -4.0  | -1.05  | 1.6 | .65   | 54.3                                     | -3.4  | -.92   | 1.1 | .75   | 15A          | Ø | L291 |
| L303     | 87.2                                       | 1.3   | .34    | 2.2 | .89   | 57.9                                     | .3    | .08    | 1.5 | 1.01  | 15L          | Ø | L303 |
| L305     | 88.9                                       | 3.1   | .80    | 3.0 | 1.19  | 60.3                                     | 2.6   | .71    | 1.3 | .87   | 15T          | Ø | L305 |
| L309     | 86.1                                       | .3    | .07    | 1.9 | .76   | 57.5                                     | -.1   | -.03   | 1.7 | 1.17  | 15T          | Ø | L309 |
| L312     | 82.1                                       | -3.7  | -.98   | 3.0 | 1.18  | 56.5                                     | -1.1  | -.30   | 1.9 | 1.30  | 15T          | Ø | L312 |
| L315     | 90.3                                       | 4.4   | 1.15   | 4.0 | 1.60  | 59.3                                     | 1.7   | .46    | 1.5 | 1.05  | 15T          | Ø | L315 |
| L324     | 74.9                                       | -10.9 | -2.86  | 4.1 | 1.64  | 55.9                                     | -1.8  | -.48   | 1.2 | .85   | 15T          | X | L324 |
| L328     | 84.2                                       | -1.6  | -.43   | 2.6 | 1.05  | 52.4                                     | -5.3  | -1.43  | 3.4 | 2.29  | 15T          | Ø | L328 |
| L331     | 93.0                                       | 7.1   | 1.86   | 3.4 | 1.34  | 66.9                                     | 9.3   | 2.52   | 2.9 | 1.98  | 15T          | * | L331 |
| L336     | 85.9                                       | -.0   | -.00   | 2.4 | .95   | 56.6                                     | -1.0  | -.28   | 1.6 | 1.08  | 15T          | Ø | L336 |
| L344     | 93.7                                       | 7.9   | 2.05   | 2.4 | .94   | 62.3                                     | 4.6   | 1.25   | 2.5 | 1.69  | 15C          | Ø | L344 |
| L345     | 84.1                                       | -1.7  | -.46   | 4.2 | 1.68  | 56.5                                     | -1.1  | -.30   | 1.4 | .96   | 15T          | Ø | L345 |
| L352     | 91.0                                       | 5.1   | 1.34   | 2.3 | .92   | 61.1                                     | 3.5   | .94    | .9  | .63   | 15C          | Ø | L352 |
| L360     | 68.1                                       | 2.2   | .57    | 2.6 | 1.04  | 57.2                                     | -.4   | -.12   | 1.7 | 1.15  | 15T          | Ø | L360 |
| L362     | 84.4                                       | -1.5  | -.39   | 2.6 | 1.05  | 56.0                                     | -1.6  | -.45   | 1.5 | 1.03  | 15T          | Ø | L362 |
| L366     | 82.7                                       | -3.1  | -.82   | 2.5 | .99   | 54.1                                     | -3.5  | -.95   | .7  | .50   | 15T          | Ø | L366 |
| L376     | 90.8                                       | 4.9   | 1.28   | 2.1 | .84   | 63.1                                     | 5.4   | 1.47   | 1.9 | 1.27  | 15T          | Ø | L376 |
| L378     | 86.3                                       | .4    | .10    | 2.6 | 1.03  | 58.4                                     | .8    | .20    | 1.5 | 1.05  | 15T          | Ø | L378 |
| L382     | 88.9                                       | 3.0   | .78    | 3.3 | 1.30  | 60.5                                     | 2.9   | .78    | 1.3 | .88   | 15T          | Ø | L382 |
| L388     | 79.9                                       | -6.0  | -1.57  | 3.5 | 1.38  | 47.9                                     | -9.8  | -2.65  | 1.0 | .67   | 15T          | * | L388 |
| L390     | 88.3                                       | 2.4   | .62    | 2.2 | .88   | 60.5                                     | 2.8   | .77    | 1.8 | 1.20  | 15T          | Ø | L390 |
| L442     | 95.3                                       | 9.4   | 2.46   | 2.6 | 1.05  | 60.8                                     | 3.2   | .86    | 1.4 | .95   | 15R          | * | L442 |
| L484     | 88.4                                       | 2.5   | .66    | 1.8 | .72   | 63.3                                     | 5.7   | 1.54   | 3.5 | 2.39  | 15T          | Ø | L484 |
| L554     | 91.2                                       | 5.3   | 1.39   | 2.7 | 1.07  | 60.4                                     | 2.8   | .75    | 1.1 | .76   | 15C          | Ø | L554 |
| L557     | 90.0                                       | 4.1   | 1.08   | 2.3 | .92   | 61.5                                     | 3.8   | 1.04   | 1.6 | 1.08  | 15T          | Ø | L557 |
| L558     | 86.7                                       | .9    | .22    | 1.3 | .53   | 54.8                                     | -2.8  | -.77   | 1.0 | .69   | 15T          | Ø | L558 |
| L559     | 89.5                                       | 3.7   | .95    | 1.8 | .70   | 65.7                                     | 8.0   | 2.18   | 1.3 | .88   | 15T          | Ø | L559 |
| L565     | 83.6                                       | -2.3  | -.60   | 2.5 | 1.00  | 53.7                                     | -3.9  | -1.06  | 1.9 | 1.27  | 15T          | Ø | L565 |
| L566     | 81.6                                       | -4.3  | -1.12  | 1.7 | .68   | 54.4                                     | -3.2  | -.88   | 1.4 | .92   | 15T          | Ø | L566 |
| L575     | 82.3                                       | -3.6  | -.94   | 3.3 | 1.30  | 52.5                                     | -5.2  | -1.41  | .8  | .57   | 15L          | Ø | L575 |
| L576     | 52.3                                       | 6.4   | 1.67   | 3.3 | 1.31  | 59.5                                     | 1.9   | .51    | 1.7 | 1.14  | 15T          | Ø | L576 |
| L580     | 86.3                                       | .4    | .10    | 1.5 | .61   | 59.6                                     | 2.0   | .53    | 1.1 | .72   | 15T          | Ø | L580 |
| L581     | 88.5                                       | 2.7   | .69    | 2.8 | 1.09  | 58.7                                     | 1.1   | .29    | 1.5 | 1.05  | 15Q          | Ø | L581 |
| L587     | 84.1                                       | -1.7  | -.46   | 1.9 | .76   | 57.2                                     | -.4   | -.12   | 1.5 | 1.00  | 15T          | Ø | L587 |
| L596     | 79.7                                       | -6.1  | -1.61  | 3.2 | 1.27  | 52.3                                     | -5.4  | -1.46  | 2.4 | 1.61  | 15T          | Ø | L596 |
| L597     | 81.0                                       | -4.9  | -1.28  | 2.0 | .79   | 54.4                                     | -3.2  | -.88   | 2.3 | 1.56  | 15T          | Ø | L597 |
| L599     | 88.9                                       | 3.1   | .80    | 2.7 | 1.07  | 59.4                                     | 1.8   | .48    | 1.4 | .95   | 15T          | Ø | L599 |
| L600     | 86.1                                       | .3    | .07    | 2.7 | 1.08  | 61.2                                     | 3.6   | .96    | 1.4 | .93   | 15T          | Ø | L600 |
| L604     | 75.2                                       | -10.7 | -2.79  | 3.1 | 1.23  | 47.5                                     | -10.2 | -2.76  | 2.6 | 1.74  | 15T          | * | L604 |
| L606     | 91.7                                       | 5.8   | 1.51   | 3.2 | 1.28  | 61.3                                     | 3.7   | 1.00   | 1.4 | .95   | 15T          | Ø | L606 |
| L618     | 19.5                                       | -66.4 | -17.35 | .9  | .36   | 13.9                                     | -43.8 | -11.88 | .5  | .35   | 15T          | # | L618 |
| L622     | 82.0                                       | -3.9  | -1.01  | 3.0 | 1.19  | 50.8                                     | -6.8  | -1.86  | 1.0 | .69   | 15T          | Ø | L622 |
| L651     | 90.3                                       | 4.4   | 1.15   | 2.3 | .89   | 59.6                                     | 2.0   | .53    | .8  | .56   | 15T          | Ø | L651 |
| L670     | 80.9                                       | -5.0  | -1.31  | 3.3 | 1.31  | 55.9                                     | -1.7  | -.46   | 3.1 | 2.08  | 15T          | Ø | L670 |
| L676     | 84.4                                       | -1.5  | -.39   | 2.6 | 1.05  | 58.9                                     | 1.2   | .33    | 2.1 | 1.40  | 15T          | Ø | L676 |

GR. MEAN = 85.9 GRAMS      GRAND MEAN = 57.6 GRAMS      TEST DETERMINATIONS = 15  
SD MEANS = 3.8 GRAMS      SD OF MEANS = 3.7 GRAMS      115 LABS IN GRAND MEANS  
AVERAGE SDR = 2.5 GRAMS      AVERAGE SDR = 1.5 GRAMS  
GR. MEAN = 842.2 MILLINEWTON      GRAND MEAN = 565.3 MILLINEWTON

|       |      |      |      |     |      |      |      |      |     |      |     |   |       |
|-------|------|------|------|-----|------|------|------|------|-----|------|-----|---|-------|
| L242  | 88.9 | 3.1  | .80  | 3.0 | 1.19 | 58.9 | 1.3  | .35  | 1.4 | .94  | 15U | * | L242  |
| L251  | 85.5 | -.4  | -.11 | 1.5 | .60  | 56.4 | -1.2 | -.34 | 1.1 | .76  | 15K | * | L251  |
| L299  | 86.5 | .7   | .17  | 3.6 | 1.42 | 58.4 | .8   | .20  | 1.7 | 1.17 | 15V | * | L299  |
| L311  | 87.5 | 1.6  | .41  | 1.3 | .52  | 58.3 | .6   | .17  | 1.2 | .83  | 15V | * | L311  |
| L396M | 86.6 | .7   | .19  | 3.7 | 1.45 | 57.8 | .2   | .04  | 1.5 | 1.03 | 15V | * | L396M |
| L610  | 84.1 | -1.7 | -.46 | 2.4 | .95  | 55.1 | -2.6 | -.70 | 1.3 | .87  | 15E | * | L610  |

TOTAL NUMBER OF LABORATORIES REPORTING = 125

Best values: E76 86 + 6 grams  
E80 58 + 5 grams

The following laboratories were omitted from the grand means because of extreme test results: 145

Data from the following laboratories appear to be off by a multiplicative factor: 618

Data from the following laboratories appeared to be off by a multiplicative factor: 299,

311, 396M. Code 15V was assigned temporarily to put in a factor of 2.

Please see the diagram on the inside of the back cover of this report which shows how to distinguish between an Elmendorf tear tester with DEEP CUTOUT and an older model tester with NO CUTOUT.

ANALYSIS T15-1 TABLE 2

TEARING STRENGTH, GRAMS

TAPPI STANDARD T414 TS=65, ANY MAKE ELMENDORF WITH DEEP CUTOUT IS STANDARD FOR THIS ANALYSIS


| LAB CODE | F | MHANS |      | COORDINATES |       | AVG E.SDR | VAR | PROPERTY | TEST     | INSTRUMENT | CONDITIONS                        |
|----------|---|-------|------|-------------|-------|-----------|-----|----------|----------|------------|-----------------------------------|
|          |   | E76   | E80  | MAJOR       | MINOR |           |     |          |          |            |                                   |
| L618     | # | 19.5  | 13.9 | -78.3       | 14.0  | .36       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L207     | * | 74.4  | 47.1 | -15.5       | .3    | 1.16      | 15R | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF, DIGITAL READOUT |
| L324     | X | 74.9  | 55.9 | -9.2        | 6.2   | 1.24      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L604     | * | 75.2  | 47.5 | -14.8       | =0    | 1.48      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L264     | X | 76.3  | 59.5 | =5.7        | 7.9   | 1.57      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L230     | 0 | 76.7  | 51.4 | -10.9       | 1.8   | .78       | 15R | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF, DIGITAL READOUT |
| L182A    | 0 | 79.1  | 52.3 | -8.6        | .7    | 1.21      | 15A | TEARING  | STRENGTH | STANDARD   | APPITA                            |
| L226C    | 0 | 79.2  | 54.3 | -7.2        | 2.2   | .97       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L191     | 0 | 79.4  | 51.0 | -9.3        | =.4   | 1.32      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L596     | 0 | 79.7  | 52.3 | -8.2        | .3    | 1.44      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L388     | * | 79.9  | 47.9 | -11.1       | =2.9  | 1.03      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L122     | 0 | 80.6  | 54.1 | -6.2        | 1.1   | .80       | 15C | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (W.AIR CLAMP)    |
| L212     | 0 | 80.8  | 56.0 | -4.8        | 2.3   | 1.26      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L670     | 0 | 80.9  | 55.9 | -4.8        | 2.2   | 1.69      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L597     | 0 | 81.0  | 54.4 | -5.8        | 1.0   | 1.17      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L226B    | 0 | 81.1  | 60.4 | -1.6        | 5.3   | 1.51      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L566     | 0 | 81.6  | 54.4 | -5.3        | .6    | .80       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L291     | 0 | 81.9  | 54.3 | -5.2        | .3    | .70       | 15A | TEARING  | STRENGTH | STANDARD   | APPITA                            |
| L622     | 0 | 82.0  | 50.8 | -7.5        | =2.3  | .94       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L145     | # | 82.1  | 72.7 | 7.6         | 13.5  | 1.16      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L131     | 0 | 82.1  | 54.9 | -4.6        | .6    | 1.61      | 15A | TEARING  | STRENGTH | STANDARD   | APPITA                            |
| L12      | 0 | 82.1  | 56.5 | -3.5        | 1.8   | 1.24      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L13      | 0 | 82.1  | 55.1 | -4.4        | .8    | .61       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L158     | 0 | 82.3  | 58.4 | -2.1        | 3.0   | 1.72      | 15R | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF, DIGITAL READOUT |
| L575     | 0 | 82.3  | 52.5 | -6.2        | -1.3  | .94       | 15L | TEARING  | STRENGTH | STANDARD   | LORENTZ-WETTRES                   |
| L261     | 0 | 82.4  | 56.9 | -3.0        | 1.9   | .66       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L366     | 0 | 82.7  | 54.1 | -4.7        | =.4   | .75       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L121     | 0 | 82.9  | 57.9 | -2.0        | 2.2   | 1.00      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L213     | 0 | 83.2  | 59.9 | -4          | 3.5   | .87       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L238A    | 0 | 83.5  | 54.0 | -4.3        | -1.0  | .83       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L170     | 0 | 83.5  | 54.4 | -3.9        | =.7   | .46       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L185     | 0 | 83.5  | 58.1 | -1.4        | 2.0   | .97       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L237A    | 0 | 83.5  | 57.3 | -2.0        | 1.3   | .89       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L555     | 0 | 83.6  | 53.7 | -4.3        | -1.3  | 1.14      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L279     | 0 | 83.6  | 57.1 | -2.1        | 1.2   | 1.22      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L237B    | 0 | 83.7  | 55.8 | -2.8        | .1    | .79       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L211     | 0 | 83.7  | 55.7 | -2.9        | .1    | .77       | 15R | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF, DIGITAL READOUT |
| L610     | * | 84.1  | 55.1 | -3.0        | =.7   | .91       | 15H | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF, AMBIENT COND.   |
| L587     | 0 | 84.1  | 57.2 | -1.6        | .9    | .88       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L345     | 0 | 84.1  | 56.5 | -2.0        | .4    | 1.32      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L328     | 0 | 84.2  | 52.4 | -4.8        | =2.7  | 1.67      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L676     | 0 | 84.4  | 58.9 | =.2         | 1.9   | 1.22      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L362     | 0 | 84.4  | 56.0 | -2.2        | =.2   | 1.04      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L100     | 0 | 84.5  | 53.9 | -3.6        | -1.8  | .85       | 15M | TEARING  | STRENGTH | STANDARD   | T. M. MIRFIELD (APPITA-ELMENDORF) |
| L228     | 0 | 84.5  | 55.5 | -2.5        | =.7   | .79       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L105     | 0 | 84.6  | 55.1 | -2.7        | =.9   | 1.01      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L190C    | 0 | 84.6  | 58.3 | =.5         | 1.3   | 1.06      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L224     | 0 | 84.7  | 58.8 | =.0         | 1.6   | .68       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L254     | 0 | 84.7  | 58.0 | =.6         | 1.0   | .84       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L148     | * | 84.8  | 65.1 | 4.3         | 6.1   | 1.18      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L173B    | 0 | 84.8  | 61.6 | 1.9         | 3.6   | .71       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L163     | 0 | 84.9  | 57.5 | =.9         | .6    | 1.16      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L128     | 0 | 84.9  | 56.0 | -1.8        | =.5   | .87       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L257C    | 0 | 85.2  | 60.5 | 1.5         | 2.6   | 1.21      | 15C | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (W.AIR CLAMP)    |
| L167     | 0 | 85.3  | 60.7 | 1.7         | 2.6   | .52       | 15C | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (W.AIR CLAMP)    |
| L251     | * | 85.5  | 56.4 | -1.2        | =.6   | .68       | 15K | TEARING  | STRENGTH | STANDARD   | LORENTZ-WETTRES, 20 C, 65% RH     |
| L257A    | 0 | 85.5  | 59.9 | 1.2         | 1.9   | .97       | 15C | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (W.AIR CLAMP)    |
| L255     | 0 | 85.5  | 55.5 | -1.7        | -1.3  | .66       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L257B    | 0 | 85.6  | 60.0 | 1.4         | 1.9   | .98       | 15C | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (W.AIR CLAMP)    |
| L336     | 0 | 85.9  | 56.6 | =.7         | =.7   | 1.01      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L141     | 0 | 85.9  | 57.6 | .0          | =.1   | .89       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L190R    | 0 | 86.1  | 56.9 | =.4         | =.6   | 1.01      | 15C | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (W.AIR CLAMP)    |
| L283     | 0 | 86.1  | 54.7 | -1.9        | =2.2  | 1.09      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L60C     | 0 | 86.1  | 61.2 | 2.6         | 2.4   | 1.01      | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |
| L309     | 0 | 86.1  | 57.5 | .1          | =.3   | .97       | 15T | TEARING  | STRENGTH | STANDARD   | THWING-ELMENDORF (SCALE T0 100)   |

TAPPI STANDARD T414 TS-65. ANY MAKE ELMENDORF WITH DEEP CUTOUT IS STANDARD FOR THIS ANALYSIS

| LAB CODE | F | MEANS        |      | COORDINATES |       | AVG R. SDR | VAR | PROPERTY==TEST          | INSTRUMENT==CONDITIONS                        |
|----------|---|--------------|------|-------------|-------|------------|-----|-------------------------|---|
|          |   | E76          | E80  | MAJOR       | MINOR |            |     |                         |   |
| L189     | Ø | 86.2         | 56.2 | 0.8         | -1.3  | .92        | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L580     | Ø | 86.3         | 59.6 | 1.6         | 1.2   | .66        | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L378     | Ø | 86.3         | 58.4 | .8          | .3    | 1.04       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L223     | Ø | 86.3         | 58.0 | .6          | -0.0  | .91        | 15R | TEARING STRENGTH,       | STANDARD, TEWING=ELMENDORF, DIGITAL READOUT   |
| L134     | Ø | 86.3         | 56.7 | -0.3        | -1.0  | .74        | 15C | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (W.AIR CLAMP)      |
| L217     | Ø | 86.4         | 56.9 | -0.1        | -0.9  | .75        | 15R | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF, DIGITAL READOUT   |
| L278     | * | 86.4         | 51.1 | -4.2        | -5.1  | .98        | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L262     | Ø | 86.5         | 55.4 | -1.1        | -2.0  | .94        | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L299     | * | 86.5         | 58.4 | 1.0         | .1    | 1.30       | 15V | TEARING STRENGTH,       | STANDARD, TEWING=ELMENDORF (SCALE TØ 100)X2   |
| L396M    | * | 86.6         | 57.8 | .6          | -0.4  | 1.24       | 15V | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)X2   |
| L558     | Ø | 86.7         | 54.8 | -1.3        | -2.6  | .61        | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L225     | Ø | 86.9         | 56.5 | -0.1        | -1.5  | .88        | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L232     | Ø | 86.9         | 60.5 | 2.7         | 1.4   | 1.10       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L162     | Ø | 87.1         | 57.6 | .8          | -0.8  | .87        | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L273     | Ø | 87.1         | 62.7 | 4.4         | 2.9   | .90        | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L183     | Ø | 87.1         | 56.1 | -0.2        | -1.9  | .78        | 15T | TEARING STRENGTH,       | STANDARD, TEWING=ELMENDORF (SCALE TØ 100)     |
| L303     | Ø | 87.2         | 57.9 | 1.2         | -0.7  | .95        | 15L | TEARING STRENGTH,       | STANDARD, LORENTZ=WETTRES                     |
| L311     | * | 87.5         | 58.3 | 1.6         | -0.6  | .67        | 15V | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)X2   |
| L143     | Ø | 87.5         | 57.7 | 1.2         | -1.1  | 1.74       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L124     | Ø | 87.6         | 60.3 | 3.0         | .7    | .90        | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L236     | Ø | 87.7         | 55.6 | -0.1        | -2.7  | 1.00       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L159     | Ø | 87.7         | 58.0 | 1.6         | -1.0  | 1.50       | 15L | TEARING STRENGTH,       | STANDARD, LORENTZ=WETTRES                     |
| L280     | Ø | 87.8         | 56.0 | .3          | -2.5  | .71        | 15L | TEARING STRENGTH,       | STANDARD, LORENTZ=WETTRES                     |
| L176     | Ø | 87.9         | 58.0 | 1.7         | -1.1  | 1.03       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L150     | Ø | 87.9         | 57.9 | 1.7         | -1.2  | .91        | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L360     | Ø | 88.1         | 57.2 | 1.3         | -1.8  | 1.10       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L126     | Ø | 88.3         | 59.1 | 2.7         | -0.6  | 1.20       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L390     | Ø | 88.3         | 60.5 | 3.7         | .4    | 1.04       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L484     | Ø | 88.4         | 63.3 | 5.7         | 2.4   | 1.55       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L107     | * | 88.5         | 65.6 | 7.4         | 3.9   | 4.22       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L581     | Ø | 88.5         | 58.7 | 2.7         | -1.1  | 1.07       | 15Q | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF, AIR CLAMP, DIGITL |
| L166     | Ø | 88.7         | 58.2 | 2.4         | -1.5  | .96        | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L288     | Ø | 88.8         | 60.6 | 4.1         | .1    | .64        | 15Q | TEARING STRENGTH,       | STANDARD, TEWING=ELMENDORF, AIR CLAMP, DIGITL |
| L249     | Ø | 88.9         | 61.8 | 5.0         | .9    | 1.23       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L382     | Ø | 88.9         | 60.5 | 4.2         | .0    | 1.09       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L206     | Ø | 88.9         | 60.3 | 4.0         | -0.2  | .99        | 15R | TEARING STRENGTH,       | STANDARD, TEWING=ELMENDORF, DIGITAL READOUT   |
| L242     | * | 88.9         | 58.9 | 3.1         | -1.2  | 1.07       | 15U | TEARING STRENGTH,       | STANDARD, AUSTRALIAN OPT. CØ.                 |
| L305     | Ø | 88.9         | 60.3 | 4.0         | -0.2  | 1.03       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L599     | Ø | 88.9         | 59.4 | 3.4         | -0.8  | 1.01       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L259     | Ø | 89.1         | 60.1 | 4.0         | -0.4  | .85        | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L243     | Ø | 89.3         | 60.4 | 4.4         | -0.4  | .94        | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L275     | Ø | 89.3         | 56.5 | 1.7         | -3.2  | .88        | 15T | TEARING STRENGTH,       | STANDARD, TEWING=ELMENDORF (SCALE TØ 100)     |
| L195     | Ø | 89.5         | 56.1 | 1.6         | -3.6  | .91        | 15C | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (W.AIR CLAMP)      |
| L285     | Ø | 89.5         | 60.9 | 4.9         | -0.1  | 1.08       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L559     | Ø | 89.5         | 65.7 | 8.2         | 3.3   | .79        | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L557     | Ø | 90.0         | 61.5 | 5.6         | -0.1  | 1.00       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L651     | Ø | 90.3         | 59.6 | 4.5         | -1.6  | .73        | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L315     | Ø | 90.3         | 59.3 | 4.3         | -1.8  | 1.33       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L182T    | Ø | 90.3         | 60.1 | 4.9         | -1.2  | 1.07       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L376     | Ø | 90.8         | 63.1 | 7.3         | .5    | 1.05       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L352     | Ø | 91.0         | 61.1 | 6.1         | -1.0  | .77        | 15C | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (W.AIR CLAMP)      |
| L554     | Ø | 91.2         | 60.4 | 5.8         | -1.7  | .92        | 15C | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (W.AIR CLAMP)      |
| L606     | Ø | 91.7         | 61.3 | 6.7         | -1.3  | 1.11       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L139     | Ø | 92.1         | 63.8 | 8.8         | .2    | .90        | 15T | TEARING STRENGTH,       | STANDARD, TEWING=ELMENDORF (SCALE TØ 100)     |
| L576     | Ø | 92.3         | 59.5 | 5.9         | -3.0  | 1.23       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L244     | * | 92.9         | 58.1 | 5.4         | -4.5  | .73        | 15C | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (W.AIR CLAMP)      |
| L331     | * | 93.0         | 66.9 | 11.6        | 1.8   | 1.66       | 15T | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (SCALE TØ 100)     |
| L151     | Ø | 93.7         | 66.0 | 11.4        | .7    | 1.08       | 15C | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (W.AIR CLAMP)      |
| L344     | Ø | 93.7         | 62.3 | 8.9         | -2.1  | 1.32       | 15C | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF (W.AIR CLAMP)      |
| L442     | * | 95.3         | 60.8 | 9.0         | -4.2  | 1.00       | 15R | TEARING STRENGTH,       | STANDARD, THWING=ELMENDORF, DIGITAL READOUT   |
| GMEANS:  |   | 85.9         | 57.6 |             |       | 1.00       |     |                         |   |
|          |   | 95% ELLIPSE: | 12.3 | 4.8         |       |            |     | WITH GAMMA = 43 DEGREES |   |

# TEARING STRENGTH, DEEP CUTOUT


SAMPLE E76 = 86. GRAMS                      SAMPLE E80 = 58. GRAMS  
 SAMPLE E76 = 842 MILLINEWTON          SAMPLE E80 = 565 MILLINEWTON





# TEARING STRENGTH, NO CUTOUT

SAMPLE J41 = 67. GRAMS                      SAMPLE K19 = 151. GRAMS  
 SAMPLE J41 = 659 MILLINEWTON           SAMPLE K19 = 1486 MILLINEWTON



TENSILE BREAKING STRENGTH, KILOGNEWTONS PER METER - PACKAGING PAPER  
TAPPI STANDARDS T404 CS-76 AND T494 CS-70, TENSILE BREAKING STRENGTH, PENDULUM AND CRE TYPES

| LAB CODE | SAMPLE J15<br>149 GRAMS PER SQUARE METER |      |       |     |        | SAMPLE K31<br>105 GRAMS PER SQUARE METER |       |       |     |        | TEST D. = 20 |   |       |
|----------|--|------|-------|-----|--------|--|-------|-------|-----|--------|--------------|---|-------|
|          | MEAN                                     | DEV  | N.DEV | SDR | R. SDR | MEAN                                     | DEV   | N.DEV | SDR | R. SDR | VAR          | F | LAB   |
| L100     | 8.74                                     | .16  | .48   | .25 | .79    | 8.92                                     | .34   | 1.13  | .38 | .83    | 19E          | Ø | L100  |
| L107     | 8.97                                     | .39  | 1.19  | .28 | .87    | 8.92                                     | .33   | 1.10  | .36 | .80    | 19A          | Ø | L107  |
| L122     | 8.69                                     | .11  | .33   | .32 | 1.00   | 8.69                                     | .11   | .37   | .43 | .94    | 19A          | Ø | L122  |
| L126     | 8.48                                     | -.10 | -.30  | .25 | .80    | 8.65                                     | .06   | .21   | .47 | 1.04   | 19A          | Ø | L126  |
| L151     | 8.76                                     | .18  | .56   | .37 | 1.17   | 8.47                                     | -.11  | -.37  | .40 | .88    | 19A          | Ø | L151  |
| L167     | 9.63                                     | 1.05 | 3.17  | .33 | 1.06   | 9.93                                     | 1.35  | 4.45  | .49 | 1.09   | 19G          | # | L167  |
| L182I    | 8.12                                     | -.46 | -1.39 | .27 | .85    | 8.35                                     | -.23  | -.76  | .41 | .92    | 19D          | Ø | L182I |
| L182L    | 8.54                                     | -.04 | -.13  | .33 | 1.05   | 8.56                                     | -.02  | -.08  | .46 | 1.01   | 19T          | Ø | L182L |
| L207     | 8.59                                     | .01  | .03   | .33 | 1.05   | 8.50                                     | -.08  | -.26  | .49 | 1.09   | 19A          | Ø | L207  |
| L217A    | 8.45                                     | -.13 | -.39  | .24 | .77    | 8.85                                     | .27   | .88   | .34 | .76    | 19A          | Ø | L217A |
| L217P    | 8.51                                     | -.07 | -.20  | .45 | 1.42   | 8.89                                     | .31   | 1.01  | .37 | .81    | 19P          | Ø | L217P |
| L224     | 8.40                                     | -.18 | -.55  | .34 | 1.07   | 9.00                                     | .42   | 1.37  | .42 | .93    | 19A          | * | L224  |
| L225     | 8.65                                     | .07  | .20   | .21 | .67    | 8.55                                     | -.03  | -.09  | .56 | 1.24   | 19P          | Ø | L225  |
| L234L    | 8.43                                     | -.15 | -.44  | .39 | 1.22   | 8.66                                     | .08   | .27   | .43 | .94    | 19P          | Ø | L234L |
| L237A    | 8.30                                     | -.28 | -.85  | .44 | 1.41   | 7.09                                     | -1.49 | -4.91 | .60 | 1.33   | 19Q          | # | L237A |
| L237B    | 5.32                                     | .74  | 2.22  | .36 | 1.14   | 9.02                                     | .44   | 1.43  | .63 | 1.40   | 19A          | Ø | L237B |
| L238A    | 8.82                                     | .24  | .72   | .38 | 1.20   | 8.55                                     | -.04  | -.12  | .43 | .94    | 15T          | Ø | L238A |
| L243     | 8.37                                     | -.21 | -.63  | .27 | .86    | 8.72                                     | .14   | .45   | .33 | .72    | 19A          | Ø | L243  |
| L257A    | 8.56                                     | .01  | .03   | .34 | 1.08   | 8.48                                     | -.10  | -.34  | .36 | .80    | 19P          | Ø | L257A |
| L257C    | 8.53                                     | -.05 | -.16  | .24 | .76    | 8.55                                     | -.03  | -.11  | .41 | .91    | 19P          | Ø | L257C |
| L264A    | 8.79                                     | .21  | .63   | .41 | 1.29   | 8.69                                     | .11   | .35   | .51 | 1.12   | 19A          | Ø | L264A |
| L264P    | 9.18                                     | .60  | 1.80  | .28 | .89    | 9.10                                     | .51   | 1.69  | .42 | .93    | 19P          | Ø | L264P |
| L265     | 8.11                                     | -.47 | -1.41 | .22 | .69    | 8.62                                     | .04   | .12   | .42 | .93    | 19A          | Ø | L265  |
| L267     | 8.52                                     | -.06 | -.17  | .33 | 1.05   | 8.92                                     | .34   | 1.11  | .42 | .93    | 19A          | Ø | L267  |
| L273     | 6.68                                     | .11  | .32   | .37 | 1.16   | 8.75                                     | .17   | .57   | .49 | 1.07   | 19P          | Ø | L273  |
| L280     | 7.75                                     | -.83 | -2.51 | .49 | 1.56   | 7.87                                     | -.71  | -2.35 | .56 | 1.24   | 19G          | * | L280  |
| L281     | 8.77                                     | .19  | .57   | .35 | 1.09   | 8.91                                     | .33   | 1.08  | .41 | .90    | 19G          | Ø | L281  |
| L305     | 8.77                                     | .19  | .57   | .23 | .74    | 8.35                                     | -.24  | -.78  | .35 | .78    | 19V          | Ø | L305  |
| L312     | 8.80                                     | .22  | .66   | .26 | .83    | 8.66                                     | .08   | .27   | .34 | .74    | 19D          | Ø | L312  |
| L318     | 8.11                                     | -.47 | -1.42 | .25 | .81    | 8.04                                     | -.54  | -1.79 | .39 | .87    | 19G          | Ø | L318  |
| L324     | 8.57                                     | -.01 | -.02  | .29 | .92    | 8.66                                     | .08   | .26   | .42 | .92    | 19A          | Ø | L324  |
| L336     | 5.03                                     | .45  | 1.36  | .38 | 1.20   | 8.63                                     | .05   | .17   | .67 | 1.47   | 19G          | Ø | L336  |
| L356     | 9.03                                     | .45  | 1.35  | .26 | .81    | 8.74                                     | .16   | .51   | .51 | 1.12   | 19P          | Ø | L356  |
| L366     | 8.69                                     | -.49 | -1.46 | .50 | 1.58   | 8.35                                     | -.23  | -.76  | .39 | .87    | 19P          | Ø | L366  |
| L565     | 8.66                                     | .08  | .24   | .19 | .59    | 8.49                                     | -.09  | -.30  | .31 | .68    | 19T          | Ø | L565  |
| L568     | 8.22                                     | -.36 | -1.08 | .42 | 1.34   | 7.94                                     | -.65  | -2.13 | .29 | .63    | 19P          | Ø | L568  |
| L575     | 8.54                                     | -.04 | -.13  | .23 | .74    | 8.50                                     | -.08  | -.27  | .36 | .80    | 19G          | Ø | L575  |
| L576     | 8.44                                     | -.14 | -.43  | .24 | .78    | 8.32                                     | -.26  | -.87  | .55 | 1.22   | 19A          | Ø | L576  |
| L580     | 8.94                                     | .36  | 1.09  | .31 | .98    | 8.60                                     | .02   | .06   | .42 | .93    | 19G          | Ø | L580  |
| L581     | 8.76                                     | .18  | .56   | .29 | .91    | 8.79                                     | .21   | .68   | .44 | .97    | 19A          | Ø | L581  |
| L582     | 7.91                                     | -.67 | -2.03 | .35 | 1.12   | 7.95                                     | -.63  | -2.08 | .57 | 1.25   | 19A          | Ø | L582  |
| L604     | 8.45                                     | -.13 | -.40  | .43 | 1.36   | 8.35                                     | -.23  | -.76  | .53 | 1.17   | 19P          | Ø | L604  |
| L606     | 8.16                                     | -.42 | -1.28 | .28 | .90    | 8.27                                     | -.31  | -1.03 | .51 | 1.13   | 19P          | Ø | L606  |
| L610     | 8.54                                     | -.04 | -.13  | .34 | 1.09   | 8.38                                     | -.20  | -.67  | .43 | .96    | 19A          | Ø | L610  |
| L622     | 8.90                                     | .33  | .98   | .32 | 1.01   | 8.76                                     | .18   | .59   | .56 | 1.24   | 19Ø          | Ø | L622  |
| L650     | 9.06                                     | .48  | 1.44  | .46 | 1.44   | 9.13                                     | .54   | 1.79  | .56 | 1.23   | 19G          | Ø | L650  |
| L676     | 8.35                                     | -.23 | -.68  | .31 | .99    | 8.11                                     | -.47  | -1.56 | .94 | 2.08   | 19A          | Ø | L676  |

GR. MEAN = 8.58 KILOGNEWTON/M      GRAND MEAN = 8.58 KILOGNEWTON/M      TEST DETERMINATIONS = 20  
SD MEANS = .33 KILOGNEWTON/M      SD OF MEANS = .30 KILOGNEWTON/M      45 LABS IN GRAND MEANS  
AVERAGE SDR = .32 KILOGNEWTON/M      AVERAGE SDR = .45 KILOGNEWTON/M  
GR. MEAN = 49.00 LB/INCH      GRAND MEAN = 49.01 LB/INCH

L251      7.63      -.95      -2.85      .45      1.43      7.66      -.92      -3.04      .70      1.56      19I      \*      L251  
TOTAL NUMBER OF LABORATORIES REPORTING = 48

Best values: J15 8.6 ± 0.5 kilonewton per meter  
K31 8.6 ± 0.5 kilonewton per meter


The following laboratories were omitted from the grand means because of extreme test results: 167, 237A

TENSILE BREAKING STRENGTH, KILOWEIGHTS PER METER - PACKAGING PAPER  
TAPPI STANDARDS T404 GS-76 AND T494 GS-70, TENSILE BREAKING STRENGTH, PENDULUM AND CRE TYPES

| LAB CODE     | F | MEANS |      | COORDINATES |       | AVG   |     | PROPERTY---TEST         | INSTRUMENT---CONDITIONS           |
|--------------|---|-------|------|-------------|-------|-------|-----|-------------------------|-----------------------------------|
|              |   | J45   | K31  | MAJOR       | MINOR | R.SDR | VAR |                         |                                   |
| L251         | * | 7.63  | 7.66 | -1.32       | -0.07 | 1.49  | 19I | TENSILE STRENGTH,       | PACKAGING PAPER, CRE, 20C, 65% RH |
| L280         | * | 7.75  | 7.87 | -1.10       | .02   | 1.40  | 19G | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L582         | Ø | 7.91  | 7.95 | -.92        | -0.03 | 1.18  | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L366         | Ø | 8.09  | 8.35 | -.52        | .15   | 1.22  | 19P | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L318         | Ø | 8.11  | 8.04 | -.71        | -.10  | .84   | 19G | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L265         | Ø | 8.11  | 8.62 | -.33        | .34   | .81   | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L182I        | Ø | 8.12  | 8.35 | -.50        | .13   | .89   | 19D | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L606         | Ø | 8.16  | 8.27 | -.52        | .05   | 1.01  | 19P | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L568         | Ø | 8.22  | 7.94 | -.70        | -.25  | .99   | 19P | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L237A        | # | 8.30  | 7.09 | -1.20       | -.93  | 1.37  | 19Q | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L676         | Ø | 8.35  | 8.11 | -.48        | -.21  | 1.54  | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L243         | Ø | 8.37  | 8.72 | -.07        | .24   | .79   | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L224         | * | 8.40  | 9.00 | .14         | .43   | 1.00  | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L234L        | Ø | 8.43  | 8.66 | -.06        | .16   | 1.08  | 19P | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L576         | Ø | 8.44  | 8.32 | -.28        | -.10  | 1.00  | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L604         | Ø | 8.45  | 8.35 | -.25        | -.09  | 1.27  | 19P | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L217A        | Ø | 8.45  | 8.85 | .08         | .29   | .76   | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L126         | Ø | 8.48  | 8.65 | -.03        | .11   | .92   | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L217P        | Ø | 8.51  | 8.89 | .15         | .27   | 1.12  | 19P | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L267         | Ø | 8.52  | 8.92 | .18         | .29   | .99   | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L257C        | Ø | 8.53  | 8.55 | -.06        | .01   | .83   | 19P | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L182L        | Ø | 8.54  | 8.56 | -.05        | .01   | 1.03  | 19T | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L610         | Ø | 8.54  | 8.38 | -.17        | -.12  | 1.03  | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L575         | Ø | 8.54  | 8.50 | -.09        | -.03  | .77   | 19G | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L324         | Ø | 8.57  | 8.66 | .05         | .06   | .92   | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L207         | Ø | 8.59  | 8.50 | -.05        | -.07  | 1.07  | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L257A        | Ø | 8.59  | 8.48 | -.06        | -.08  | .94   | 19P | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L225         | Ø | 8.65  | 8.55 | .03         | -.07  | .95   | 19P | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L565         | Ø | 8.66  | 8.49 | -.00        | -.12  | .64   | 19T | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L273         | Ø | 8.68  | 8.75 | .19         | .06   | 1.12  | 19P | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L122         | Ø | 8.69  | 8.69 | .16         | .01   | .97   | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L100         | Ø | 8.74  | 8.92 | .35         | .15   | .81   | 19E | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L151         | Ø | 8.76  | 8.47 | .06         | -.21  | 1.02  | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L581         | Ø | 8.76  | 8.79 | .28         | .03   | .94   | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L305         | Ø | 8.77  | 8.35 | -.02        | -.30  | .76   | 19V | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L281         | Ø | 8.77  | 8.91 | .36         | .12   | 1.00  | 19G | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L264A        | Ø | 8.79  | 8.69 | .23         | -.05  | 1.21  | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L312         | Ø | 8.80  | 8.66 | .22         | -.08  | .79   | 19D | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L238A        | Ø | 8.82  | 8.55 | .16         | -.19  | 1.07  | 19T | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L622         | Ø | 8.90  | 8.76 | .36         | -.08  | 1.12  | 19G | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L580         | Ø | 8.94  | 8.60 | .28         | -.23  | .95   | 19G | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L107         | Ø | 8.97  | 8.92 | .52         | -.01  | .84   | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L355         | Ø | 9.03  | 8.74 | .44         | -.18  | .96   | 19P | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L336         | Ø | 9.03  | 8.63 | .37         | -.26  | 1.34  | 19G | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L650         | Ø | 9.06  | 9.13 | .72         | .09   | 1.34  | 19G | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L264P        | Ø | 9.18  | 9.10 | .79         | -.01  | .91   | 19P | TENSILE STRENGTH,       | PACKAGING PAPER, PENDULUM TESTER  |
| L2378        | Ø | 9.32  | 9.02 | .84         | -.16  | 1.27  | 19A | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| L167         | # | 9.63  | 9.93 | 1.68        | .32   | 1.08  | 19G | TENSILE STRENGTH,       | PACKAGING PAPER, LOAD CELL (CRE)  |
| GMEANS:      |   | 8.58  | 8.58 |             |       | 1.00  |     |                         |                                   |
| 95% ELLIPSE: |   |       |      | 1.07        | .44   |       |     | WITH GAMMA = 41 DEGREES |                                   |

# TENSILE STRENGTH, PACKAGING PAPERS

SAMPLE J15 = 8.58 KILONEWTON/M    SAMPLE K31 = 8.58 KILONEWTON/M  
 SAMPLE J15 = 49.0 LB/INCH            SAMPLE K31 = 49.0 LB/INCH



TENSILE BREAKING STRENGTH, KILONEWTONS PER METER  
TAPPI STANDARD T494 G9-70, TENSILE BREAKING PROPERTIES OF PAPER & PAPERBOARD (CONSTANT RATE OF ELONGATION)

| LAB CODE | SAMPLE J04<br>73 GRAMS PER SQUARE METER |       |        |       |        | SAMPLE J08<br>85 GRAMS PER SQUARE METER |      |        |     |        | TEST D. = 20 |   |       |
|----------|---|-------|--------|-------|--------|---|------|--------|-----|--------|--------------|---|-------|
|          | MEAN                                    | DEV   | N. DEV | SDR   | R. SDR | MEAN                                    | DEV  | N. DEV | SDR | R. SDR | VAR          | F | LAB   |
| L100     | 3.62                                    | 0.05  | 0.28   | .17   | .99    | 6.22                                    | .14  | .46    | .19 | .51    | 20E          | 0 | L100  |
| L105     | 3.55                                    | 0.12  | 0.67   | .20   | 1.16   | 6.46                                    | .38  | 1.27   | .55 | 1.47   | 20A          | * | L105  |
| L122     | 3.89                                    | .22   | 1.23   | .15   | .86    | 6.27                                    | .18  | .63    | .40 | 1.06   | 20A          | 0 | L122  |
| L124C    | 3.52                                    | 0.15  | 0.86   | .21   | 1.24   | 5.82                                    | 0.27 | 0.92   | .39 | 1.05   | 20A          | 0 | L124C |
| L125     | 3.86                                    | .19   | 1.05   | .19   | 1.15   | 6.17                                    | .08  | .29    | .65 | 1.74   | 20C          | 0 | L125  |
| L131     | 3.97                                    | .30   | 1.66   | .11   | .64    | 6.54                                    | .46  | 1.54   | .33 | .88    | 20E          | 0 | L131  |
| L141T    | 3.78                                    | .11   | .61    | .11   | .68    | 6.16                                    | .07  | .23    | .38 | 1.01   | 20A          | 0 | L141T |
| L143     | 3.36                                    | 0.32  | 1.77   | .17   | 1.00   | 5.41                                    | 0.67 | 2.28   | .31 | .83    | 20E          | 0 | L143  |
| L148     | 3.74                                    | .07   | .40    | .17   | 1.01   | 5.99                                    | 0.10 | 0.35   | .24 | .64    | 20A          | 0 | L148  |
| L155     | 3.79                                    | .12   | .65    | .12   | .69    | 6.22                                    | .13  | .45    | .42 | 1.11   | 20A          | 0 | L155  |
| L163     | 3.81                                    | .14   | .76    | .19   | 1.11   | 6.41                                    | .32  | 1.08   | .16 | .42    | 20D          | 0 | L163  |
| L167     | 4.02                                    | .35   | 1.94   | .22   | 1.29   | 6.67                                    | .58  | 1.97   | .50 | 1.32   | 20G          | 0 | L167  |
| L176     | 3.39                                    | 0.29  | 1.60   | .19   | 1.13   | 5.64                                    | 0.45 | 1.53   | .34 | .91    | 20E          | 0 | L176  |
| L185     | 3.73                                    | .06   | .32    | .22   | 1.29   | 6.30                                    | .21  | .70    | .31 | .83    | 20C          | 0 | L185  |
| L190R    | 3.64                                    | 0.03  | 0.16   | .10   | .59    | 6.02                                    | 0.07 | 0.24   | .45 | 1.20   | 20A          | 0 | L190R |
| L223B    | 3.73                                    | .06   | .32    | .15   | .88    | 6.25                                    | .16  | .55    | .28 | .74    | 20A          | 0 | L223B |
| L226C    | 3.92                                    | .25   | 1.38   | .27   | 1.59   | 6.40                                    | .31  | 1.04   | .67 | 1.79   | 20C          | 0 | L226C |
| L230     | 3.80                                    | .12   | .70    | .16   | .93    | 6.45                                    | .36  | 1.23   | .17 | .46    | 20G          | 0 | L230  |
| L243     | 3.79                                    | .11   | .63    | .13   | .79    | 6.09                                    | 0.00 | 0.01   | .38 | 1.01   | 20A          | 0 | L243  |
| L255     | 3.82                                    | .15   | .82    | .12   | .73    | 6.33                                    | .25  | .83    | .20 | .53    | 20A          | 0 | L255  |
| L260     | 3.57                                    | 0.10  | 0.56   | .13   | .74    | 6.06                                    | 0.03 | 0.09   | .25 | .67    | 20A          | 0 | L260  |
| L261     | 3.80                                    | .13   | .73    | .18   | 1.04   | 6.41                                    | .32  | 1.09   | .32 | .86    | 20A          | 0 | L261  |
| L278     | 3.60                                    | 0.07  | 0.42   | .17   | 1.00   | 6.15                                    | .07  | .22    | .29 | .77    | 20A          | 0 | L278  |
| L291     | 3.19                                    | 0.48  | 2.70   | .24   | 1.41   | 5.63                                    | 0.46 | 1.56   | .54 | 1.45   | 20A          | * | L291  |
| L309     | 20.39                                   | 16.72 | 93.55  | 17.22 | 101.65 | 5.64                                    | 0.44 | 1.50   | .19 | .52    | 20E          | # | L309  |
| L315     | 3.61                                    | 0.06  | 0.35   | .16   | .96    | 6.07                                    | 0.02 | 0.05   | .39 | 1.03   | 20A          | 0 | L315  |
| L318     | 3.52                                    | 0.15  | 0.86   | .12   | .71    | 5.63                                    | 0.45 | 1.54   | .48 | 1.29   | 20G          | 0 | L318  |
| L325     | 3.52                                    | 0.16  | 0.87   | .26   | 1.53   | 5.90                                    | 0.19 | 0.64   | .28 | .76    | 20E          | 0 | L325  |
| L328     | 3.65                                    | 0.02  | 0.12   | .16   | .92    | 5.89                                    | 0.20 | 0.66   | .35 | .93    | 20A          | 0 | L328  |
| L331     | 3.50                                    | 0.17  | 0.97   | .20   | 1.18   | 5.48                                    | 0.61 | 2.05   | .45 | 1.21   | 20A          | 0 | L331  |
| L333     | 3.75                                    | .08   | .46    | .16   | .97    | 6.13                                    | .04  | .13    | .40 | 1.08   | 20A          | 0 | L333  |
| L344     | 3.79                                    | .11   | .64    | .14   | .82    | 6.03                                    | 0.06 | 0.20   | .60 | 1.59   | 20A          | 0 | L344  |
| L352     | 3.56                                    | 0.11  | 0.61   | .22   | 1.29   | 5.84                                    | 0.25 | 0.86   | .44 | 1.17   | 20A          | 0 | L352  |
| L360     | 1.26                                    | 2.41  | 13.49  | .09   | .53    | 2.13                                    | 3.96 | 13.41  | .08 | .22    | 20B          | # | L360  |
| L372     | .34                                     | 3.33  | 18.62  | .03   | .17    | 6.09                                    | .01  | .02    | .52 | 1.38   | 20A          | # | L372  |
| L378     | 3.73                                    | .06   | .31    | .19   | 1.12   | 5.75                                    | 0.34 | 1.14   | .56 | 1.51   | 20A          | 0 | L378  |
| L390     | 3.83                                    | .16   | .88    | .21   | 1.23   | 6.37                                    | .28  | .94    | .35 | .93    | 20A          | 0 | L390  |
| L442     | 3.51                                    | 0.16  | 0.88   | .11   | .66    | 5.91                                    | 0.18 | 0.61   | .33 | .87    | 20G          | 0 | L442  |
| L557     | 3.40                                    | 0.27  | 1.50   | .18   | 1.06   | 5.93                                    | 0.16 | 0.53   | .27 | .71    | 20A          | 0 | L557  |
| L558     | .96                                     | 2.71  | 15.18  | .18   | 1.06   | 1.32                                    | 4.77 | 16.13  | .13 | .35    | 20A          | # | L558  |
| L559     | 3.52                                    | 0.15  | 0.83   | .11   | .67    | 6.17                                    | .08  | .27    | .18 | .49    | 20A          | 0 | L559  |
| L563A    | 3.50                                    | 0.18  | 0.98   | .22   | 1.29   | 5.79                                    | 0.30 | 1.00   | .91 | 2.42   | 20A          | 0 | L563A |
| L575     | 3.84                                    | .16   | .92    | .17   | 1.00   | 6.46                                    | .37  | 1.25   | .25 | .67    | 20G          | 0 | L575  |
| L587     | 3.75                                    | .08   | .42    | .18   | 1.05   | NO DATA REPORTED FOR SAMPLE J08         |      |        |     |        | 20A          | M | L587  |
| L592     | 3.66                                    | 0.01  | 0.06   | .16   | .95    | 6.10                                    | .01  | .05    | .29 | .79    | 20A          | 0 | L592  |
| L616     | 1.17                                    | 2.50  | 14.01  | .16   | .96    | .40                                     | 5.69 | 19.24  | .08 | .21    | 20D          | # | L616  |
| L618     | 3.79                                    | .11   | .64    | .21   | 1.24   | 6.10                                    | .01  | .03    | .46 | 1.23   | 20A          | 0 | L618  |

GR. MEAN = 3.67 KILONEWTON/M      GRAND MEAN = 6.09 KILONEWTON/M      TEST DETERMINATIONS = 20  
SD MEANS = .18 KILONEWTON/M      SD OF MEANS = .30 KILONEWTON/M      41 LABS IN GRAND MEANS  
AVERAGE SDR = .17 KILONEWTON/M      AVERAGE SDR = .37 KILONEWTON/M  
GR. MEAN = 12.386 LB/15 MM      GRAND MEAN = 20.534 LB/15 MM

|      |      |      |      |     |      |      |      |      |     |      |     |   |      |
|------|------|------|------|-----|------|------|------|------|-----|------|-----|---|------|
| L139 | 3.72 | .05  | .28  | .20 | 1.17 | 6.02 | 0.07 | 0.23 | .30 | .81  | 20H | * | L139 |
| L251 | 3.20 | 0.47 | 2.63 | .36 | 2.12 | 5.57 | 0.52 | 1.74 | .41 | 1.10 | 20I | * | L251 |

TOTAL NUMBER OF LABORATORIES REPORTING = 49

Best values: J04 3.7 ± 0.3 kilonewton per meter  
J08 6.1 ± 0.4 kilonewton per meter

The following laboratories were omitted from the grand means because of extreme test results: 309, 372, 616

Data from the following laboratories appear to be off by a multiplicative factor: 360, 558

ANALYSIS T20-1 TABLE 2


TENSILE BREAKING STRENGTH, KILOGNEWTONS PER METER

TAPPI STANDARD T494 G3-70, TENSILE BREAKING PROPERTIES OF PAPER & PAPERBOARD (CONSTANT RATE OF ELONGATION)

| LAB<br>CODE  | F | MEANS |      | COORDINATES |        | AVG<br>E.SDR            | VAR | PROPERTY          | TEST                       | INSTRUMENT      | CONDITIONS |
|--------------|---|-------|------|-------------|--------|-------------------------|-----|-------------------|----------------------------|-----------------|------------|
|              |   | J04   | J08  | MAJOR       | MINOR  |                         |     |                   |                            |                 |            |
| L372         | # | .34   | 6.09 | -1.56       | 2.94   | .77                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L558         | # | .96   | 1.32 | -5.48       | .15    | .70                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L616         | # | 1.17  | .40  | -6.19       | -0.47  | .58                     | 20D | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L360         | # | 1.26  | 2.13 | -4.63       | .26    | .37                     | 20B | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L291         | * | 3.19  | 5.63 | -0.63       | .21    | 1.43                    | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L251         | * | 3.20  | 5.57 | -0.68       | .17    | 1.61                    | 20I | TENSILE STRENGTH, | PRINTING PAPER, CRE, 20 C, | 65% RH          |            |
| L143         | Ø | 3.36  | 5.41 | -0.74       | -0.04  | .92                     | 20E | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L176         | Ø | 3.39  | 5.64 | -0.53       | .04    | 1.02                    | 20E | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L557         | Ø | 3.40  | 5.93 | -0.26       | .16    | .89                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L563A        | Ø | 3.50  | 5.79 | -0.34       | .02    | 1.86                    | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L331         | Ø | 3.50  | 5.48 | -0.62       | -0.13  | 1.20                    | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L442         | Ø | 3.51  | 5.91 | -0.23       | .05    | .77                     | 20G | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L325         | Ø | 3.52  | 5.90 | -0.24       | .05    | 1.15                    | 20E | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L315         | Ø | 3.52  | 5.63 | -0.47       | -0.08  | 1.00                    | 20G | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L124C        | Ø | 3.52  | 5.82 | -0.31       | .01    | 1.15                    | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L559         | Ø | 3.52  | 6.17 | .00         | .17    | .58                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L105         | * | 3.55  | 6.46 | .27         | .28    | 1.32                    | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L352         | Ø | 3.56  | 5.84 | -0.27       | -0.02  | 1.23                    | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L260         | Ø | 3.57  | 6.06 | -0.07       | .08    | .71                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L278         | Ø | 3.60  | 6.15 | .02         | .10    | .89                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L315         | Ø | 3.61  | 6.07 | -0.04       | .05    | 1.00                    | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L100         | Ø | 3.62  | 6.22 | .10         | .11    | .75                     | 20E | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L190R        | Ø | 3.64  | 6.02 | -0.08       | -0.01  | .90                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L328         | Ø | 3.65  | 5.89 | -0.18       | -0.07  | .92                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L592         | Ø | 3.66  | 6.10 | .01         | .02    | .87                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L139         | * | 3.72  | 6.02 | -0.04       | -0.08  | .99                     | 20H | TENSILE STRENGTH, | PRINTING PAPER, CRE, SHORT | TEST SPAN       |            |
| L378         | Ø | 3.73  | 5.75 | -0.27       | -0.21  | 1.31                    | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L223R        | Ø | 3.73  | 6.25 | .17         | .03    | .81                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L185         | Ø | 3.73  | 6.30 | .21         | .05    | 1.06                    | 20C | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L148         | Ø | 3.74  | 5.99 | -0.06       | -0.11  | .83                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L587         | M | 3.75  |      |             |        | 1.05                    | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L333         | Ø | 3.75  | 6.13 | .07         | -0.05  | 1.02                    | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L141T        | Ø | 3.78  | 6.16 | .11         | -0.06  | .84                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L243         | Ø | 3.79  | 6.09 | .05         | -0.10  | .90                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L344         | Ø | 3.79  | 6.03 | .00         | -0.13  | 1.20                    | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L618         | Ø | 3.79  | 6.10 | .06         | -0.10  | 1.24                    | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L159         | Ø | 3.79  | 6.22 | .17         | -0.04  | .90                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L230         | Ø | 3.80  | 6.45 | .38         | .06    | .70                     | 20G | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L261         | Ø | 3.80  | 6.41 | .34         | .04    | .95                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L163         | Ø | 3.81  | 6.41 | .35         | .03    | .77                     | 20D | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L255         | Ø | 3.82  | 6.33 | .29         | -0.01  | .63                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L390         | Ø | 3.83  | 6.37 | .32         | -0.01  | 1.08                    | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L575         | Ø | 3.84  | 6.46 | .40         | .03    | .84                     | 20G | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L125         | Ø | 3.86  | 6.17 | .16         | -0.13  | 1.45                    | 20C | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L122         | Ø | 3.89  | 6.27 | .27         | -0.11  | .96                     | 20A | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L226C        | Ø | 3.92  | 6.40 | .39         | -0.07  | 1.69                    | 20C | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L131         | Ø | 3.97  | 6.54 | .54         | -0.05  | .76                     | 20E | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L167         | Ø | 4.02  | 6.67 | .68         | -0.03  | 1.31                    | 20G | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| L309         | # | 20.39 | 5.64 | 7.49        | -14.96 | 51.08                   | 20E | TENSILE STRENGTH, | PRIMARYLY PRINTING PAPERS, | LOAD CELL (CRE) |            |
| GMEANS:      |   | 3.67  | 6.09 |             |        | 1.00                    |     |                   |                            |                 |            |
| 95% ELLIPSE: |   |       |      | .85         | .26    | WITH GAMMA = 61 DEGREES |     |                   |                            |                 |            |

# TENSILE STRENGTH, CRE TYPE

SAMPLE J04 = 3.67 KILONEWTON/M    SAMPLE J08 = 6.09 KILONEWTON/M  
 SAMPLE J04 = 12.39 LB/15 MM    SAMPLE J08 = 20.53 LB/15 MM



ANALYSIS T20-2 TABLE 1

TENSILE BREAKING STRENGTH, KILOWEIGHTS PER METER

TAPPI STANDARD T404 69-76, TENSILE BREAKING STRENGTH OF PAPER AND PAPERBOARD (PENDULUM-TYPE TESTER)

| LAB CODE | SAMPLE J04 MEAN | PRINTING 73 GRAMS PER SQUARE METER |       |     |       | SAMPLE J08 MEAN | PRINTING 85 GRAMS PER SQUARE METER |       |     |       | TEST D. ° 20 |   |       |
|----------|-----------------|------------------------------------|-------|-----|-------|-----------------|------------------------------------|-------|-----|-------|--------------|---|-------|
|          |                 | DEV                                | N.DEV | SDR | R.SDR |                 | DEV                                | N.DEV | SDR | R.SDR | VAR          | F | LAB   |
| L103     | 3.88            | .12                                | .59   | .12 | .60   | 6.48            | .25                                | .64   | .25 | .58   | 20R          | Ø | L103  |
| L108     | 3.70            | -.05                               | -.24  | .19 | .93   | 6.50            | .28                                | .70   | .18 | .43   | 20P          | Ø | L108  |
| L121     | 3.90            | .15                                | .69   | .16 | .79   | 6.28            | .05                                | .14   | .51 | 1.19  | 20P          | Ø | L121  |
| L124P    | 3.54            | -.21                               | -.99  | .23 | 1.12  | 5.93            | -.30                               | -.74  | .44 | 1.02  | 20P          | Ø | L124P |
| L128     | 3.81            | .05                                | .26   | .13 | .63   | 6.34            | .12                                | .29   | .41 | .96   | 20T          | Ø | L128  |
| L148     | 3.73            | -.02                               | -.10  | .17 | .83   | 6.03            | -.19                               | -.48  | .27 | .63   | 20P          | Ø | L148  |
| L162     | 3.47            | -.28                               | -1.34 | .30 | 1.45  | 6.20            | -.03                               | -.07  | .36 | .85   | 20*          | Ø | L162  |
| L182L    | 3.69            | -.07                               | -.31  | .20 | .96   | 6.07            | -.15                               | -.38  | .51 | 1.19  | 20T          | Ø | L182L |
| L189     | 4.06            | .30                                | 1.44  | .18 | .87   | 6.83            | .61                                | 1.52  | .62 | 1.45  | 20R          | Ø | L189  |
| L191P    | 3.90            | .15                                | .69   | .19 | .94   | 6.50            | .27                                | .69   | .35 | .82   | 20P          | Ø | L191P |
| L195     | 3.83            | .08                                | .38   | .16 | .79   | 6.17            | -.06                               | -.14  | .28 | .66   | 20R          | Ø | L195  |
| L211     | 2.81            | -.94                               | -4.46 | .21 | 1.00  | 4.99            | -1.23                              | -3.10 | .28 | .65   | 20R          | # | L211  |
| L212     | 3.28            | -.47                               | -2.22 | .25 | 1.20  | 5.53            | -.70                               | -1.75 | .31 | .72   | 20R          | Ø | L212  |
| L213     | 3.51            | -.24                               | -1.15 | .22 | 1.08  | 6.22            | -.01                               | -.01  | .39 | .92   | 20T          | Ø | L213  |
| L218     | 3.81            | .05                                | .26   | .15 | .71   | 6.33            | .11                                | .27   | .32 | .74   | 20P          | Ø | L218  |
| L242     | 3.70            | -.05                               | -.25  | .18 | .85   | 5.66            | -.56                               | -1.40 | .63 | 1.47  | 20Y          | Ø | L242  |
| L249     | 3.64            | -.12                               | -.56  | .19 | .93   | 5.96            | -.26                               | -.66  | .67 | 1.57  | 20P          | Ø | L249  |
| L259     | 4.00            | .25                                | 1.16  | .19 | .91   | 6.30            | .08                                | .19   | .59 | 1.38  | 20P          | Ø | L259  |
| L262     | 3.82            | .07                                | .32   | .20 | .96   | 6.88            | .66                                | 1.65  | .24 | .56   | 20R          | Ø | L262  |
| L275     | 3.68            | -.08                               | -.37  | .28 | 1.33  | 6.47            | .24                                | .61   | .54 | 1.27  | 20R          | Ø | L275  |
| L279P    | 3.84            | .09                                | .42   | .47 | 2.28  | 6.85            | .62                                | 1.56  | .42 | .98   | 20P          | Ø | L279P |
| L285     | 3.50            | -.26                               | -1.21 | .14 | .67   | 4.77            | -1.45                              | -3.65 | .16 | .37   | 20P          | # | L285  |
| L311     | 3.78            | .03                                | .15   | .18 | .88   | 5.51            | -.71                               | -1.78 | .39 | .91   | 20V          | Ø | L311  |
| L330     | 3.69            | -.07                               | -.31  | .21 | 1.01  | 6.22            | -.00                               | -.00  | .55 | 1.28  | 20P          | Ø | L330  |
| L356     | 4.02            | .27                                | 1.26  | .16 | .79   | 6.45            | .23                                | .58   | .56 | 1.30  | 20P          | Ø | L356  |
| L362     | 3.75            | -.01                               | -.03  | .29 | 1.42  | 6.32            | .09                                | .23   | .39 | .91   | 20R          | Ø | L362  |
| L370     | 3.79            | .03                                | .16   | .12 | .58   | 6.46            | .24                                | .60   | .39 | .90   | 20P          | Ø | L370  |
| L376     | 3.68            | -.07                               | -.32  | .18 | .88   | 5.72            | -.51                               | -1.28 | .55 | 1.28  | 20P          | Ø | L376  |
| L393     | 3.95            | .19                                | .92   | .15 | .73   | 6.46            | .24                                | .60   | .37 | .86   | 20P          | Ø | L393  |
| L484     | 3.53            | -.22                               | -1.04 | .25 | 1.19  | 5.51            | -.71                               | -1.79 | .55 | 1.28  | 20U          | Ø | L484  |
| L554     | 3.98            | .23                                | 1.09  | .22 | 1.06  | 6.75            | .53                                | 1.32  | .32 | .74   | 20P          | Ø | L554  |
| L556     | 4.13            | .38                                | 1.79  | .20 | .95   | 6.27            | .04                                | .11   | .66 | 1.55  | 20P          | Ø | L556  |
| L563P    | 4.04            | .29                                | 1.36  | .20 | .95   | 6.78            | .56                                | 1.39  | .49 | 1.14  | 20P          | Ø | L563P |
| L585     | 3.32            | -.44                               | -2.07 | .15 | .73   | 5.71            | -.51                               | -1.28 | .30 | .69   | 20V          | Ø | L585  |
| L599     | 3.40            | -.35                               | -1.65 | .35 | 1.69  | 5.70            | -.52                               | -1.31 | .32 | .75   | 20V          | Ø | L599  |

GR. MEAN = 3.75 KILOWEIGHT/M      GRAND MEAN = 6.22 KILOWEIGHT/M      TEST DETERMINATIONS = 20  
SD MEANS = .21 KILOWEIGHT/M      SD OF MEANS = .40 KILOWEIGHT/M      33 LABS IN GRAND MEANS  
AVERAGE SDR = .21 KILOWEIGHT/M      AVERAGE SDR = .43 KILOWEIGHT/M

GR. MEAN = 12.660 LB/15 MM      GRAND MEAN = 20.989 LB/15 MM  
TOTAL NUMBER OF LABORATORIES REPORTING = 35

Best values: J04 3.7 ± 0.4 kilonewton per meter  
J08 6.3 ± 0.6 kilonewton per meter

The following laboratories were omitted from the grand means because of extreme test results: 211, 285


TENSILE BREAKING STRENGTH, KILONEWTONS PER METER

TAPPI STANDARD T404 68-76, TENSILE BREAKING STRENGTH OF PAPER AND PAPERBOARD (PENDULUM-TYPE TESTER)

| LAB<br>CODE | P | MEANS        |      | COORDINATES |       | AVG                     |     | PROPERTY==TEST    | INSTRUMENT===CONDITIONS                    |
|-------------|---|--------------|------|-------------|-------|-------------------------|-----|-------------------|--|
|             |   | J04          | J08  | MAJOR       | MINOR | R.SDR                   | VAR |                   |  |
| L211        | # | 2.81         | 4.99 | -1.50       | .40   | .82                     | 20R | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L212        | Ø | 3.28         | 5.53 | -.82        | .17   | .96                     | 20R | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L585        | Ø | 3.32         | 5.71 | -.64        | .21   | .71                     | 20V | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L599        | Ø | 3.40         | 5.70 | -.62        | .12   | 1.22                    | 20V | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L162        | Ø | 3.47         | 6.20 | -.13        | .25   | 1.15                    | 20* | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L285        | # | 3.50         | 4.77 | -1.44       | -.32  | .52                     | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L213        | Ø | 3.51         | 6.22 | -.10        | .22   | 1.00                    | 20T | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L484        | Ø | 3.53         | 5.51 | -.74        | -.07  | 1.23                    | 20U | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L124P       | Ø | 3.54         | 5.93 | -.35        | .08   | 1.07                    | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L249        | Ø | 3.64         | 5.96 | -.29        | .01   | 1.25                    | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L275        | Ø | 3.68         | 6.47 | .19         | .17   | 1.30                    | 20R | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L376        | Ø | 3.68         | 5.72 | -.50        | -.13  | 1.08                    | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L162L       | Ø | 3.69         | 6.07 | -.17        | .00   | 1.07                    | 20T | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L33C        | Ø | 3.69         | 6.22 | -.03        | .06   | 1.15                    | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L242        | Ø | 3.70         | 5.66 | -.54        | -.17  | 1.16                    | 20Y | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L108        | Ø | 3.70         | 6.50 | .24         | .15   | .68                     | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L148        | Ø | 3.73         | 6.03 | -.18        | -.05  | .73                     | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L362        | Ø | 3.75         | 6.32 | .08         | .04   | 1.16                    | 20R | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L311        | Ø | 3.78         | 5.51 | -.64        | -.30  | .89                     | 20V | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L370        | Ø | 3.79         | 6.46 | .23         | .06   | .74                     | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L128        | Ø | 3.81         | 6.34 | .13         | -.01  | .80                     | 20T | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L218        | Ø | 3.81         | 6.33 | .12         | -.01  | .72                     | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L262        | Ø | 3.82         | 6.88 | .63         | .19   | .76                     | 20R | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L195        | Ø | 3.83         | 6.17 | -.02        | -.10  | .72                     | 20R | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L279P       | Ø | 3.84         | 6.85 | .61         | .15   | 1.63                    | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L103        | Ø | 3.88         | 6.48 | .28         | -.02  | .59                     | 20R | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L191P       | Ø | 3.90         | 6.50 | .31         | -.03  | .88                     | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L121        | Ø | 3.90         | 6.28 | .11         | -.11  | .99                     | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L393        | Ø | 3.95         | 6.46 | .30         | -.09  | .80                     | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L554        | Ø | 3.98         | 6.75 | .57         | -.01  | .90                     | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L259        | Ø | 4.00         | 6.30 | .16         | -.20  | 1.15                    | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L356        | Ø | 4.02         | 6.45 | .31         | -.16  | 1.04                    | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L563P       | Ø | 4.04         | 6.78 | .62         | -.05  | 1.04                    | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L185        | Ø | 4.06         | 6.83 | .68         | -.05  | 1.16                    | 20R | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| L556        | Ø | 4.13         | 6.27 | .18         | -.33  | 1.25                    | 20P | TENSILE STRENGTH, | PRIMARILY PRINTING PAPERS, PENDULUM TESTER |
| GMEANS:     |   | 3.75         | 6.22 |             |       | 1.00                    |     |                   |  |
|             |   | 95% ELLIPSE: |      | 1.11        | .38   | WITH GAMMA = 67 DEGREES |     |                   |  |

# TENSILE STRENGTH, PENDULUM TYPE

SAMPLE J04 = 3.75 KILONEWTN/M    SAMPLE J08 = 6.22 KILONEWTN/M  
 SAMPLE J04 = 12.7 LB/15 MM        SAMPLE J08 = 21.0 LB/15 MM



TENSILE ENERGY ABSORPTION, JOULES PER SQUARE METER - PACKAGING PAPER  
TAPPI STANDARD T494 G9-70, TENSILE BREAKING PROPERTIES OF PAPER & PAPERBOARD (CONSTANT RATE OF ELONGATION)

| LAB<br>CODE | SAMPLE<br>J15<br>MEAN | PRINTING<br>149 GRAMS PER SQUARE METER |                    |      |      | R <sub>s</sub> SDR | SAMPLE<br>K31<br>MEAN | PRINTING<br>105 GRAMS PER SQUARE METER |                    |      |  | R <sub>s</sub> SDR | TEST D. = 20 |       |     |
|-------------|-----------------------|--|--------------------|------|------|--------------------|-----------------------|--|--------------------|------|--|--------------------|--------------|-------|-----|
|             |                       | DEV                                    | N <sub>o</sub> DEV | SDR  |      |                    |                       | DEV                                    | N <sub>o</sub> DEV | SDR  |  |                    | VAR          | F     | LAB |
| L122        | 132.2                 | 10.5                                   | .93                | 11.3 | .90  | 80.2               | 4.1                   | .51                                    | 9.5                | .94  |  | 25P                | Ø            | L122  |     |
| L126        | 121.1                 | 9.5                                    | 0.05               | 9.1  | .73  | 76.6               | .5                    | .07                                    | 9.9                | .98  |  | 25G                | Ø            | L126  |     |
| L151        | 124.6                 | 3.0                                    | .27                | 17.4 | 1.39 | 82.5               | 6.4                   | .81                                    | 13.4               | 1.32 |  | 25F                | Ø            | L151  |     |
| L182        | 115.3                 | 6.4                                    | 0.56               | 10.7 | .85  | 71.5               | 4.6                   | 0.58                                   | 9.1                | .90  |  | 25B                | Ø            | L182  |     |
| L234B       | 123.0                 | 1.4                                    | .12                | 14.8 | 1.18 | 87.3               | 11.2                  | 1.40                                   | 11.4               | 1.12 |  | 25H                | Ø            | L234B |     |
| L237B       | 107.5                 | 14.1                                   | 1.24               | 10.7 | .86  | 69.2               | 7.0                   | 0.87                                   | 10.1               | 1.00 |  | 25H                | Ø            | L237B |     |
| L243        | 120.0                 | 1.7                                    | 0.15               | 9.0  | .72  | 74.2               | 1.9                   | 0.23                                   | 6.9                | .68  |  | 25Z                | Ø            | L243  |     |
| L264        | 111.1                 | 10.5                                   | 0.93               | 15.6 | 1.24 | 66.5               | 9.6                   | 1.20                                   | 10.4               | 1.03 |  | 25F                | Ø            | L264  |     |
| L267        | 124.7                 | 3.0                                    | .27                | 11.8 | .94  | 83.2               | 7.1                   | .89                                    | 7.7                | .76  |  | 25F                | Ø            | L267  |     |
| L273        | 136.4                 | 14.8                                   | 1.30               | 13.1 | 1.04 | 85.6               | 9.5                   | 1.19                                   | 10.3               | 1.02 |  | 25F                | Ø            | L273  |     |
| L280        | 106.7                 | 14.9                                   | 1.31               | 18.4 | 1.47 | 69.4               | 6.7                   | 0.84                                   | 12.8               | 1.26 |  | 25B                | Ø            | L280  |     |
| L312        | 147.1                 | 25.4                                   | 2.24               | 12.3 | .98  | 87.5               | 11.4                  | 1.43                                   | 10.8               | 1.07 |  | 25J                | Ø            | L312  |     |
| L318        | 129.3                 | 7.7                                    | .68                | 12.1 | .97  | 76.4               | .3                    | .03                                    | 8.6                | .85  |  | 25A                | Ø            | L318  |     |
| L580        | 115.6                 | 6.0                                    | 0.53               | 11.7 | .93  | 68.1               | 8.0                   | 1.00                                   | 6.1                | .61  |  | 25C                | Ø            | L580  |     |
| L604        | 87.2                  | 34.4                                   | 3.03               | 14.8 | 1.18 | 72.0               | 4.2                   | 0.52                                   | 12.4               | 1.23 |  | 25A                | #            | L604  |     |
| L676        | 109.9                 | 11.7                                   | 1.03               | 10.0 | .80  | 63.3               | 12.8                  | 1.60                                   | 14.7               | 1.46 |  | 25F                | Ø            | L676  |     |

GR. MEAN = 121.6 JOULES/SQ M      GRAND MEAN = 76.1 JOULES/SQ M      TEST DETERMINATIONS = 20  
 SD MEANS = 11.3 JOULES/SQ M      SD OF MEANS = 8.0 JOULES/SQ M      15 LABS IN GRAND MEANS  
 AVERAGE SDR = 12.5 JOULES/SQ M      AVERAGE SDR = 10.1 JOULES/SQ M  
 GR. MEAN = 8.332 FT. LB/SQ FT      GRAND MEAN = 5.214 FT. LB/SQ FT  
 TOTAL NUMBER OF LABORATORIES REPORTING = 16  
 Best values: J15 120 ± 16 joules per square meter  
 K31 76 ± 11 joules per square meter


The following laboratories were omitted from the grand means because of extreme test results: 604

TENSILE ENERGY ABSORPTION, JOULES PER SQUARE METER - PACKAGING PAPER  
TAPPI STANDARD T494 G9-70, TENSILE BREAKING PROPERTIES OF PAPER & PAPERBOARD (CONSTANT RATE OF ELONGATION)

| LAB<br>CODE | F | MEANS        |      | COORDINATES |       | AVG                     |     | PROPERTY            | TEST INSTRUMENT                      | CONDITIONS |
|-------------|---|--------------|------|-------------|-------|-------------------------|-----|---------------------|--------------------------------------|------------|
|             |   | J15          | K31  | MAJOR       | MINOR | R <sub>s</sub> SDR      | VAR |                     |                                      |            |
| L604        | # | 87.2         | 72.0 | -31.0       | 15.5  | 1.20                    | 25A | TENSILE ENERGY ABS. | PACKAGING PAPER, PLAT/FLAT JAWS      |            |
| L280        | Ø | 106.7        | 69.4 | -16.1       | 2.6   | 1.36                    | 25B | TENSILE ENERGY ABS. | PACKAGING PAPER, LINE/FLAT JAWS      |            |
| L237B       | Ø | 107.5        | 69.2 | -15.6       | 1.9   | .93                     | 25H | TENSILE ENERGY ABS. | PACKAGING PAPER, 2-PIN STRAIN GAGE   |            |
| L676        | Ø | 109.9        | 63.3 | -16.8       | 4.2   | 1.13                    | 25F | TENSILE ENERGY ABS. | PACKAGING PAPER, LINE/FLAT JAWS      |            |
| L264        | Ø | 111.1        | 66.5 | -14.1       | 2.2   | 1.13                    | 25F | TENSILE ENERGY ABS. | PACKAGING PAPER, LINE/FLAT JAWS      |            |
| L182        | Ø | 115.3        | 71.5 | -7.8        | 0.4   | .88                     | 25B | TENSILE ENERGY ABS. | PACKAGING PAPER, LINE/FLAT JAWS      |            |
| L580        | Ø | 115.6        | 68.1 | -9.4        | 3.4   | .77                     | 25C | TENSILE ENERGY ABS. | PACKAGING PAPER, LINE/LINE JAWS      |            |
| L243        | Ø | 120.0        | 74.2 | -2.4        | 0.6   | .70                     | 25Z | TENSILE ENERGY ABS. | PACKAGING PAPER, LINE/LINE JAWS      |            |
| L126        | Ø | 121.1        | 76.6 | 0.1         | .7    | .85                     | 25G | TENSILE ENERGY ABS. | PACKAGING PAPER, LINE/LINE JAWS      |            |
| L234B       | Ø | 123.0        | 87.3 | 7.3         | 8.6   | 1.15                    | 25H | TENSILE ENERGY ABS. | PACKAGING PAPER, 2-PIN STRAIN GAGE   |            |
| L151        | Ø | 124.6        | 82.5 | 6.1         | 3.7   | 1.36                    | 25F | TENSILE ENERGY ABS. | PACKAGING PAPER, LINE/FLAT JAWS      |            |
| L267        | Ø | 124.7        | 83.2 | 6.4         | 4.3   | .85                     | 25F | TENSILE ENERGY ABS. | PACKAGING PAPER, LINE/FLAT JAWS      |            |
| L318        | Ø | 129.3        | 76.4 | 6.5         | 4.0   | .91                     | 25A | TENSILE ENERGY ABS. | PACKAGING PAPER, FLAT/FLAT JAWS      |            |
| L122        | Ø | 132.2        | 80.2 | 11.0        | 2.4   | .92                     | 25P | TENSILE ENERGY ABS. | PACKAGING PAPER, PATTERNED FLAT JAWS |            |
| L273        | Ø | 136.4        | 85.6 | 17.5        | 0.2   | 1.03                    | 25F | TENSILE ENERGY ABS. | PACKAGING PAPER, LINE/FLAT JAWS      |            |
| L312        | Ø | 147.1        | 87.5 | 27.5        | 4.4   | 1.03                    | 25J | TENSILE ENERGY ABS. | PACKAGING PAPER, LINE/FLAT JAWS      |            |
| GMEANS:     |   | 121.6        | 76.1 |             |       | 1.00                    |     |                     |                                      |            |
|             |   | 95% ELLIPSE: |      | 38.3        | 10.6  | WITH GAMMA = 33 DEGREES |     |                     |                                      |            |

T.E.A., PACKAGING PAPERS

SAMPLE J15 = 122. JOULES/SQ M      SAMPLE K31 = 76.      JOULES/SQ M  
 SAMPLE J15 = 8.33 FT.LB/SQ FT      SAMPLE K31 = 5.21      FT.LB/SQ FT



TENSILE ENERGY ABSORPTION, JOULES PER SQUARE METER - PRINTING PAPER  
TAPPI STANDARD T494 6S-70, TENSILE BREAKING PROPERTIES OF PAPER & PAPERBOARD (CONSTANT RATE OF ELONGATION)

| LAB CODE | SAMPLE J04 |      | PRINTING 73 GRAMS PER SQUARE METER |     |       |                                 | SAMPLE J08 |       | PRINTING 85 GRAMS PER SQUARE METER |       |     |   | TEST D. = 20 |  |  |
|----------|------------|------|------------------------------------|-----|-------|---------------------------------|------------|-------|------------------------------------|-------|-----|---|--------------|--|--|
|          | MEAN       | DEV  | N.DEV                              | SDR | R.SDR | MEAN                            | DEV        | N.DEV | SDR                                | R.SDR | VAR | F | LAB          |  |  |
| L100     | 34.8       | -2.9 | -1.12                              | 3.9 | .96   | 78.0                            | 2.1        | .32   | 6.1                                | .82   | 26A | Ø | L100         |  |  |
| L122     | 39.9       | 2.2  | .84                                | 3.5 | .87   | 79.2                            | 3.4        | .51   | 10.8                               | 1.44  | 26L | Ø | L122         |  |  |
| L139     | 36.0       | -1.8 | -.68                               | 5.9 | 1.46  | 68.6                            | -7.3       | -1.09 | 7.6                                | 1.03  | 26H | Ø | L139         |  |  |
| L159     | 40.3       | 2.6  | 1.00                               | 4.2 | 1.04  | 82.0                            | 6.2        | .93   | 8.6                                | 1.15  | 26F | Ø | L159         |  |  |
| L163     | 36.5       | -1.2 | -.48                               | 4.1 | 1.01  | 78.9                            | 3.1        | .46   | 5.5                                | .73   | 26J | Ø | L163         |  |  |
| L167     | 40.2       | 2.5  | .97                                | 2.2 | .54   | 66.7                            | -9.1       | -1.37 | 5.0                                | .67   | 26D | Ø | L167         |  |  |
| L185     | 34.5       | -3.2 | -1.24                              | 5.4 | 1.34  | 69.9                            | -5.9       | -.89  | 7.8                                | 1.04  | 26C | Ø | L185         |  |  |
| L255     | 43.2       | 5.5  | 2.14                               | 3.3 | .82   | 87.3                            | 11.4       | 1.72  | 5.9                                | .80   | 26P | Ø | L255         |  |  |
| L309     | 38.2       | .5   | .21                                | 5.5 | 1.35  | 69.8                            | -6.0       | -.90  | 5.4                                | .72   | 26J | Ø | L309         |  |  |
| L318     | 38.4       | .7   | .26                                | 3.5 | .87   | 72.2                            | -3.6       | -.54  | 10.9                               | 1.46  | 26A | Ø | L318         |  |  |
| L393     | 36.3       | -1.4 | -.54                               | 3.5 | .87   | 80.8                            | 5.0        | .75   | 5.0                                | .67   | 26V | Ø | L393         |  |  |
| L442     | 38.6       | .9   | .34                                | 3.8 | .93   | 81.7                            | 5.9        | .89   | 9.2                                | 1.23  | 26B | Ø | L442         |  |  |
| L575     | 36.6       | -1.1 | -.43                               | 4.5 | 1.11  | 79.8                            | 4.0        | .60   | 7.4                                | 1.00  | 26A | Ø | L575         |  |  |
| L587     | 35.4       | -2.3 | -.91                               | 5.0 | 1.24  | NO DATA REPORTED FOR SAMPLE J08 |            |       |                                    |       | 26C | Ø | L587         |  |  |
| L592     | 34.5       | -3.3 | -1.27                              | 3.4 | .85   | 66.6                            | -9.2       | -1.38 | 9.2                                | 1.24  | 26H | Ø | L592         |  |  |


GR. MEAN = 37.7 JOULES/SQ M                      GRAND MEAN = 75.8 JOULES/SQ M                      TEST DETERMINATIONS = 20  
SD MEANS = 2.6 JOULES/SQ M                      SD OF MEANS = 6.6 JOULES/SQ M                      14 LABS IN GRAND MEANS  
AVERAGE SDR = 4.1 JOULES/SQ M                      AVERAGE SDR = 7.4 JOULES/SQ M  
GR. MEAN = 2.584 FT.LB/SQ FT                      GRAND MEAN = 5.194 FT.LB/SQ FT  
TOTAL NUMBER OF LABORATORIES REPORTING = 15  
Best values: J04 38 ± 5 joules per square meter  
J08 76 ± 10 joules per square meter

TENSILE ENERGY ABSORPTION, JOULES PER SQUARE METER - PRINTING PAPER  
TAPPI STANDARD T494 6S-70, TENSILE BREAKING PROPERTIES OF PAPER & PAPERBOARD (CONSTANT RATE OF ELONGATION)

| LAB CODE | F | MEANS        |      | COORDINATES |       | AVG                     |     | PROPERTY            | TEST INSTRUMENT  | CONDITIONS          |
|----------|---|--------------|------|-------------|-------|-------------------------|-----|---------------------|------------------|---------------------|
|          |   | J04          | J08  | MAJOR       | MINOR | R.SDR                   | VAR |                     |                  |                     |
| L592     | Ø | 34.5         | 66.6 | -9.6        | 1.4   | 1.04                    | 26H | TENSILE ENERGY ABS. | PRINTING PAPERS, | 2-PIN STRAIN GAGE   |
| L185     | Ø | 34.5         | 69.9 | -6.4        | 1.9   | 1.19                    | 26C | TENSILE ENERGY ABS. | PRINTING PAPERS, | LINE/LINE JAWS      |
| L100     | Ø | 34.8         | 78.0 | 1.5         | 3.2   | .89                     | 26A | TENSILE ENERGY ABS. | PRINTING PAPERS, | PLAT/PLAT JAWS      |
| L587     | M | 35.4         |      |             |       | 1.24                    | 26C | TENSILE ENERGY ABS. | PRINTING PAPERS, | LINE/LINE JAWS      |
| L139     | Ø | 36.0         | 68.6 | -7.5        | .3    | 1.24                    | 26H | TENSILE ENERGY ABS. | PRINTING PAPERS, | 2-PIN STRAIN GAGE   |
| L393     | Ø | 36.3         | 80.8 | 4.6         | 2.3   | .77                     | 26V | TENSILE ENERGY ABS. | PRINTING PAPERS, | LINE/FLAT JAWS      |
| L163     | Ø | 36.5         | 78.9 | 2.8         | 1.8   | .87                     | 26J | TENSILE ENERGY ABS. | PRINTING PAPERS, | LINE/FLAT JAWS      |
| L575     | Ø | 36.6         | 79.8 | 3.7         | 1.9   | 1.05                    | 26A | TENSILE ENERGY ABS. | PRINTING PAPERS, | FLAT/PLAT JAWS      |
| L309     | Ø | 38.2         | 69.8 | -5.8        | -1.7  | 1.03                    | 26J | TENSILE ENERGY ABS. | PRINTING PAPERS, | LINE/PLAT JAWS      |
| L318     | Ø | 38.4         | 72.2 | -3.4        | -1.4  | 1.17                    | 26A | TENSILE ENERGY ABS. | PRINTING PAPERS, | FLAT/FLAT JAWS      |
| L442     | Ø | 38.6         | 81.7 | 6.0         | .3    | 1.08                    | 26B | TENSILE ENERGY ABS. | PRINTING PAPERS, | LINE/PLAT JAWS      |
| L122     | Ø | 39.9         | 79.2 | 3.7         | -1.4  | 1.16                    | 26L | TENSILE ENERGY ABS. | PRINTING PAPERS, | PATTERNED FLAT JAWS |
| L167     | Ø | 40.2         | 66.7 | -8.5        | -4.2  | .60                     | 26D | TENSILE ENERGY ABS. | PRINTING PAPERS, | 2-PIN STRAIN GAGE   |
| L159     | Ø | 40.3         | 82.0 | 6.6         | -1.3  | 1.10                    | 26F | TENSILE ENERGY ABS. | PRINTING PAPERS, | LINE/FLAT JAWS      |
| L255     | Ø | 43.2         | 87.3 | 12.3        | -3.1  | .81                     | 26P | TENSILE ENERGY ABS. | PRINTING PAPERS, | PATTERNED FLAT JAWS |
| GMEANS:  |   | 37.7         | 75.8 |             |       | 1.00                    |     |                     |                  |                     |
|          |   | 95% ELLIPSE: |      | 19.6        | 6.5   | WITH GAMMA = 78 DEGREES |     |                     |                  |                     |

T.E.A., PRINTING PAPERS

SAMPLE J04 = 37.7 JOULES/SQ M    SAMPLE J08 = 75.8 JOULES/SQ M  
 SAMPLE J04 = 2.58 FT.LB/SQ FT    SAMPLE J08 = 5.19 FT.LB/SQ FT






ELONGATION TO BREAK, PERCENT - PACKAGING PAPER  
TAPPI STANDARD T494 68-70, TENSILE BREAKING PROPERTIES OF PAPER & PAPERBOARD (CONSTANT RATE OF ELONGATION)

| LAB<br>CODE | P | MEANS        |       | COORDINATES |       | AVG                     |     | PROPERTY---TEST INSTRUMENT---     | CONDITIONS                |
|-------------|---|--------------|-------|-------------|-------|-------------------------|-----|-----------------------------------|---------------------------|
|             |   | J15          | K31   | MAJOR       | MINOR | R. SDR                  | VAR |                                   |                           |
| L100        | Ø | 2.005        | 1.375 | -.138       | .017  | .83                     | 28A | ELONGATION, PACKAGING PAPER, LOAD | CELL, PLAT/FLAT JAWS      |
| L324        | Ø | 2.020        | 1.390 | -.117       | .018  | .65                     | 28P | ELONGATION, PACKAGING PAPER, LOAD | CELL, PATTERNED FLAT JAWS |
| L265        | Ø | 2.034        | 1.522 | -.016       | .105  | .99                     | 28A | ELONGATION, PACKAGING PAPER, LOAD | CELL, PLAT/FLAT JAWS      |
| L580        | Ø | 2.055        | 1.415 | -.074       | .012  | 1.16                    | 28C | ELONGATION, PACKAGING PAPER, LOAD | CELL, LINE/LINE JAWS      |
| L243        | Ø | 2.084        | 1.354 | -.094       | -.052 | .67                     | 28C | ELONGATION, PACKAGING PAPER, LOAD | CELL, LINE/LINE JAWS      |
| L264        | Ø | 2.085        | 1.405 | -.059       | -.015 | 1.38                    | 28B | ELONGATION, PACKAGING PAPER, LOAD | CELL, LINE/FLAT JAWS      |
| L126        | Ø | 2.056        | 1.421 | -.040       | -.011 | .90                     | 28C | ELONGATION, PACKAGING PAPER, LOAD | CELL, LINE/LINE JAWS      |
| L182        | Ø | 2.056        | 1.376 | -.071       | -.044 | .91                     | 28B | ELONGATION, PACKAGING PAPER, LOAD | CELL, LINE/PLAT JAWS      |
| L336        | Ø | 2.124        | 1.461 | .008        | -.001 | 1.28                    | 28A | ELONGATION, PACKAGING PAPER, LOAD | CELL, PLAT/PLAT JAWS      |
| L582        | Ø | 2.167        | 1.517 | .077        | .010  | 1.19                    | 28A | ELONGATION, PACKAGING PAPER, LOAD | CELL, PLAT/FLAT JAWS      |
| L267        | Ø | 2.200        | 1.554 | .127        | .015  | .86                     | 28B | ELONGATION, PACKAGING PAPER, LOAD | CELL, LINE/FLAT JAWS      |
| L581        | Ø | 2.208        | 1.577 | .148        | .025  | .93                     | 28A | ELONGATION, PACKAGING PAPER, LOAD | CELL, PLAT/FLAT JAWS      |
| L280        | Ø | 2.219        | 1.554 | .141        | .002  | 1.40                    | 28B | ELONGATION, PACKAGING PAPER, LOAD | CELL, LINE/FLAT JAWS      |
| L122        | Ø | 2.253        | 1.473 | .110        | -.081 | .87                     | 28P | ELONGATION, PACKAGING PAPER, LOAD | CELL, PATTERNED FLAT JAWS |
| L151        | # | 2.280        | 1.860 | .394        | .183  | 1.85                    | 28B | ELONGATION, PACKAGING PAPER, LOAD | CELL, LINE/PLAT JAWS      |
| L318        | # | 2.464        | 1.546 | .314        | -.172 | .92                     | 28A | ELONGATION, PACKAGING PAPER, LOAD | CELL, PLAT/FLAT JAWS      |
| L312        | # | 2.565        | 1.750 | .527        | -.092 | 1.02                    | 28B | ELONGATION, PACKAGING PAPER, LOAD | CELL, LINE/FLAT JAWS      |
| L676        | # | 2.645        | 2.090 | .818        | .101  | 2.88                    | 28B | ELONGATION, PACKAGING PAPER, LOAD | CELL, LINE/FLAT JAWS      |
| GMEANS:     |   | 2.118        | 1.457 |             |       | 1.00                    |     |                                   |                           |
|             |   | 95% ELLIPSE: |       | .294        | .125  | WITH GAMMA = 43 DEGREES |     |                                   |                           |

# ELONGATION TO BREAK, PACKAGING PAPER

SAMPLE J15 = 2.12 PERCENT

SAMPLE K31 = 1.46 PERCENT



ELONGATION TO BREAK, PERCENT - PRINTING PAPER  
TAPPI STANDARD T494 68-70, TENSILE BREAKING PROPERTIES OF PAPER & PAPERBOARD (CONSTANT RATE OF ELONGATION)

| LAB CODE                                    | SAMPLE J04 |                               |                 |      |                            | SAMPLE J08                      |                               |                 |      |                          | TEST D. = 20 |     |                        |      |
|---|------------|-------------------------------|-----------------|------|----------------------------|---------------------------------|-------------------------------|-----------------|------|--------------------------|--------------|-----|------------------------|------|
|   | MEAN       | 73 GRAMS PER SQUARE METER DEV | PRINTING N. DEV | SQR  | R. SDR                     | MEAN                            | 85 GRAMS PER SQUARE METER DEV | PRINTING N. DEV | SQR  | R. SDR                   | VAR          | F   | LAB                    |      |
| L100  | 1.470      | -.070                         | -.35            | .142 | 1.19                       | 1.855                           | .013                          | .07             | .094 | .63                      | 29A          | 0   | L100                   |      |
| L105  | 1.075      | -.465                         | -2.32           | .143 | 1.20                       | 1.437                           | -.405                         | -2.22           | .197 | 1.31                     | 29A          | 0   | L105                   |      |
| L122  | 1.560      | .021                          | .10             | .089 | .74                        | 1.912                           | .070                          | .39             | .160 | 1.06                     | 29F          | 0   | L122                   |      |
| L141T                                       | 1.495      | -.045                         | -.22            | .107 | .90                        | 1.766                           | -.076                         | -.42            | .140 | .93                      | 29D          | 0   | L141T                  |      |
| L176  | 1.465      | -.075                         | -.37            | .179 | 1.50                       | 1.914                           | .072                          | .40             | .158 | 1.05                     | 29B          | 0   | L176                   |      |
| L185  | 1.454      | -.086                         | -.43            | .148 | 1.24                       | 1.758                           | -.084                         | -.46            | .111 | .74                      | 29C          | 0   | L185                   |      |
| L190R                                       | 1.541      | .001                          | .01             | .091 | .77                        | 1.779                           | -.063                         | -.35            | .168 | 1.12                     | 29A          | 0   | L190R                  |      |
| L255  | 1.785      | .245                          | 1.22            | .081 | .68                        | 2.125                           | .283                          | 1.55            | .089 | .59                      | 29F          | 0   | L255                   |      |
| L278  | 1.592      | .052                          | .26             | .132 | 1.11                       | 1.945                           | .103                          | .57             | .155 | 1.03                     | 29A          | 0   | L278                   |      |
| L309  | 1.778      | .238                          | 1.19            | .160 | 1.35                       | 2.042                           | .200                          | 1.10            | .114 | .76                      | 29A          | 0   | L309                   |      |
| L318  | 1.712      | .172                          | .86             | .120 | 1.01                       | 1.979                           | .137                          | .76             | .157 | 1.05                     | 29A          | 0   | L318                   |      |
| L344  | 1.437      | -.102                         | -.51            | .138 | 1.15                       | 1.662                           | -.180                         | -.99            | .211 | 1.41                     | 29A          | 0   | L344                   |      |
| L372  | 1.246      | -.294                         | -1.46           | .067 | .57                        | 1.513                           | -.329                         | -1.81           | .223 | 1.49                     | 29B          | 0   | L372                   |      |
| L378  | 1.920      | .381                          | 1.89            | .152 | 1.28                       | 1.974                           | .132                          | .73             | .216 | 1.44                     | 29A          | 0   | L378                   |      |
| L442  | 1.657      | .117                          | .58             | .106 | .89                        | 1.987                           | .145                          | .80             | .130 | .87                      | 29B          | 0   | L442                   |      |
| L575  | 1.497      | -.043                         | -.21            | .116 | .97                        | 1.904                           | .062                          | .34             | .131 | .87                      | 29A          | 0   | L575                   |      |
| L587  | 1.460      | -.080                         | -.40            | .127 | 1.07                       | NO DATA REPORTED FOR SAMPLE J08 |                               |                 |      |                          |              | 29C | 0                      | L587 |
| L592  | 1.492      | -.047                         | -.24            | .089 | .75                        | 1.759                           | -.083                         | -.45            | .163 | 1.08                     | 29D          | 0   | L592                   |      |
| GR. MEAN = 1.540 PERCENT                    |            | AVERAGE SDR = .119 PERCENT    |                 |      | GRAND MEAN = 1.842 PERCENT |                                 | AVERAGE SDR = .150 PERCENT    |                 |      | TEST DETERMINATIONS = 20 |              |     | 17 LABS IN GRAND MEANS |      |
| SD MEANS = .201 PERCENT                     |            |                               |                 |      | SD OF MEANS = .182 PERCENT |                                 |                               |                 |      |                          |              |     |                        |      |
| L242  | 1.920      | .380                          | 1.89            | .182 | 1.53                       | 2.070                           | .228                          | 1.25            | .172 | 1.15                     | 29R          | 0   | L242                   |      |
| L484  | 1.460      | -.080                         | -.40            | .229 | 1.92                       | 1.750                           | -.092                         | -.50            | .238 | 1.58                     | 29R          | 0   | L484                   |      |
| TOTAL NUMBER OF LABORATORIES REPORTING = 20 |            |                               |                 |      |                            |                                 |                               |                 |      |                          |              |     |                        |      |
| Best values: J04 1.50 ± 0.28 percent        |            |                               |                 |      |                            |                                 |                               |                 |      |                          |              |     |                        |      |
| J08 1.86 ± 0.34 percent                     |            |                               |                 |      |                            |                                 |                               |                 |      |                          |              |     |                        |      |

ANALYSIS T29-1 TABLE 2

ELONGATION TO BREAK, PERCENT - PRINTING PAPER


TAPPI STANDARD T494 GS-70, TENSILE BREAKING PROPERTIES OF PAPER & PAPERBOARD (CONSTANT RATE OF ELONGATION)

| LAB<br>CODE | F | MEANS        |       | COORDINATES |       | AVG                     |     | PROPERTY---TEST INSTRUMENT---CONDITIONS                     |
|-------------|---|--------------|-------|-------------|-------|-------------------------|-----|---|
|             |   | J04          | J08   | MAJOR       | MINOR | R.SDR                   | VAR |   |
| L105        | Ø | 1.075        | 1.437 | -.616       | .009  | 1.25                    | 29A | ELONGATION, PRINTING PAPERS, LOAD CELL, FLAT/FLAT JAWS      |
| L372        | Ø | 1.246        | 1.513 | -.439       | -.049 | 1.03                    | 29B | ELONGATION, PRINTING PAPERS, LOAD CELL, LINE/FLAT JAWS      |
| L344        | Ø | 1.437        | 1.662 | -.196       | -.065 | 1.28                    | 29A | ELONGATION, PRINTING PAPERS, LOAD CELL, FLAT/FLAT JAWS      |
| L185        | Ø | 1.454        | 1.758 | -.120       | -.005 | .99                     | 29C | ELONGATION, PRINTING PAPERS, LOAD CELL, LINE/LINE JAWS      |
| L484        | * | 1.460        | 1.750 | -.121       | -.015 | 1.75                    | 29R | ELONGATION, PRINTING PAPERS, PENDULUM, FLAT/FLAT JAWS       |
| L587        | M | 1.460        |       |             |       | 1.07                    | 29C | ELONGATION, PRINTING PAPERS, LOAD CELL, LINE/LINE JAWS      |
| L176        | Ø | 1.465        | 1.914 | -.008       | .104  | 1.28                    | 29B | ELONGATION, PRINTING PAPERS, LOAD CELL, LINE/FLAT JAWS      |
| L100        | Ø | 1.470        | 1.855 | -.043       | .056  | .91                     | 29A | ELONGATION, PRINTING PAPERS, LOAD CELL, FLAT/FLAT JAWS      |
| L592        | Ø | 1.492        | 1.759 | -.090       | -.030 | .92                     | 29D | ELONGATION, PRINTING PAPERS, LOAD CELL, 2-PIN STRAIN GAGE   |
| L141T       | Ø | 1.495        | 1.766 | -.084       | -.026 | .92                     | 29D | ELONGATION, PRINTING PAPERS, LOAD CELL, 2-PIN STRAIN GAGE   |
| L575        | Ø | 1.497        | 1.904 | .010        | .074  | .92                     | 29A | ELONGATION, PRINTING PAPERS, LOAD CELL, FLAT/FLAT JAWS      |
| L150E       | Ø | 1.541        | 1.779 | -.041       | -.048 | .94                     | 29A | ELONGATION, PRINTING PAPERS, LOAD CELL, FLAT/FLAT JAWS      |
| L122        | Ø | 1.560        | 1.912 | .062        | .039  | .90                     | 29P | ELONGATION, PRINTING PAPERS, LOAD CELL, PATTERNED FLAT JAWS |
| L278        | Ø | 1.592        | 1.945 | .108        | .042  | 1.07                    | 29A | ELONGATION, PRINTING PAPERS, LOAD CELL, FLAT/FLAT JAWS      |
| L442        | Ø | 1.657        | 1.987 | .184        | .030  | .88                     | 29B | ELONGATION, PRINTING PAPERS, LOAD CELL, LINE/FLAT JAWS      |
| L318        | Ø | 1.712        | 1.979 | .220        | -.012 | 1.03                    | 29A | ELONGATION, PRINTING PAPERS, LOAD CELL, FLAT/FLAT JAWS      |
| L309        | Ø | 1.778        | 2.042 | .311        | -.010 | 1.05                    | 29A | ELONGATION, PRINTING PAPERS, LOAD CELL, FLAT/FLAT JAWS      |
| L255        | Ø | 1.785        | 2.125 | .371        | .047  | .64                     | 29P | ELONGATION, PRINTING PAPERS, LOAD CELL, PATTERNED FLAT JAWS |
| L242        | * | 1.920        | 2.070 | .435        | -.084 | 1.34                    | 29R | ELONGATION, PRINTING PAPERS, PENDULUM, FLAT/FLAT JAWS       |
| L378        | * | 1.920        | 1.974 | .372        | -.155 | 1.36                    | 29A | ELONGATION, PRINTING PAPERS, LOAD CELL, FLAT/FLAT JAWS      |
| GMEANS:     |   | 1.540        | 1.842 |             |       | 1.00                    |     |   |
|             |   | 95% ELLIPSE: |       | .740        | .173  | WITH GAMMA = 41 DEGREES |     |   |

# ELONGATION TO BREAK, PRINTING PAPER

SAMPLE J04 = 1.54 PERCENT

SAMPLE J08 = 1.84 PERCENT



TAPPI COLLABORATIVE REFERENCE PROGRAM  
ANALYSIS T30-1 TABLE 1  
FOLDING ENDURANCE (MIT), DOUBLE FOLDS  
TAPPI STANDARD T511 SU-69

| LAB CODE                                    | SAMPLE J29 MEAN | PRINTING 102 GRAMS PER SQUARE METER |        |      |        | SAMPLE J31 MEAN | PRINTING 86 GRAMS PER SQUARE METER |                    |      |        | TEST D. = 15 |                          |       |  |
|---|-----------------|-------------------------------------|--------|------|--------|-----------------|------------------------------------|--------------------|------|--------|--------------|--------------------------|-------|--|
|   |                 | DEV                                 | N. DEV | SDR  | R. SDR |                 | DEV                                | N. DEV             | SDR  | R. SDR | VAR          | F                        | LAB   |  |
| L100M                                       | 16.4            | -7.9                                | -1.13  | 4.3  | .46    | 69.1            | -3.9                               | -0.26              | 12.5 | .70    | 30M          | 0                        | L100M |  |
| L100N                                       | 15.9            | -8.4                                | -1.20  | 2.4  | .26    | 77.3            | 4.3                                | .29                | 8.0  | .45    | 30N          | 0                        | L100N |  |
| L105  | 22.2            | -2.1                                | -.29   | 14.8 | 1.59   | 75.2            | 2.3                                | .15                | 9.3  | .52    | 30M          | 0                        | L105  |  |
| L121  | 24.5            | .2                                  | .03    | 21.0 | 2.24   | 78.6            | 5.7                                | .38                | 15.1 | .84    | 30M          | 0                        | L121  |  |
| L122  | 31.8            | 7.5                                 | 1.08   | 21.5 | 2.30   | 68.5            | -4.4                               | -.29               | 35.3 | 1.97   | 30M          | 0                        | L122  |  |
| L124  | 28.9            | 4.7                                 | .67    | 19.0 | 2.03   | 62.7            | -10.2                              | -.68               | 10.7 | .60    | 30N          | 0                        | L124  |  |
| L150  | 30.6            | 6.3                                 | .91    | 17.9 | 1.91   | 80.4            | 7.5                                | .50                | 22.4 | 1.26   | 30M          | 0                        | L150  |  |
| L159  | 38.9            | 14.6                                | 2.09   | 25.5 | 2.72   | 85.4            | 12.5                               | .83                | 21.0 | 1.17   | 30M          | 0                        | L159  |  |
| L162  | 22.7            | -1.6                                | -.23   | 12.5 | 1.33   | 64.8            | -8.1                               | -.54               | 22.3 | 1.24   | 30M          | 0                        | L162  |  |
| L163  | 30.7            | 6.4                                 | .92    | 10.4 | 1.11   | 55.3            | -17.7                              | -1.17              | 19.1 | 1.07   | 30N          | 0                        | L163  |  |
| L176  | 27.0            | 2.7                                 | .39    | 5.0  | .54    | 67.9            | -5.0                               | -.33               | 13.8 | .77    | 30N          | 0                        | L176  |  |
| L182M                                       | 28.5            | 4.3                                 | .61    | 22.2 | 2.37   | 92.9            | 19.9                               | 1.32               | 19.6 | 1.09   | 30M          | 0                        | L182M |  |
| L185  | 23.9            | -.4                                 | -.06   | 7.5  | .80    | 81.5            | 8.5                                | .57                | 15.7 | .88    | 30N          | 0                        | L185  |  |
| L190C                                       | 29.3            | 5.0                                 | .72    | 4.5  | .48    | 72.1            | 0.8                                | -.05               | 18.7 | 1.05   | 30N          | 0                        | L190C |  |
| L212  | 18.8            | -5.5                                | -.78   | 5.2  | .56    | 62.3            | -10.6                              | -.70               | 11.4 | .64    | 30M          | 0                        | L212  |  |
| L223F                                       | 21.2            | -3.1                                | -.44   | 9.0  | .97    | 73.7            | .8                                 | .05                | 16.8 | .94    | 30M          | 0                        | L223F |  |
| L230  | 19.5            | -4.8                                | -.69   | 5.9  | .63    | 64.9            | -8.0                               | -.53               | 22.0 | 1.23   | 30N          | 0                        | L230  |  |
| L232  | 28.0            | 3.7                                 | .54    | 7.7  | .82    | 92.9            | 19.9                               | 1.32               | 31.6 | 1.77   | 30N          | 0                        | L232  |  |
| L236  | 18.3            | -6.0                                | -.86   | 5.3  | .57    | 80.4            | 7.5                                | .50                | 11.2 | .63    | 30N          | 0                        | L236  |  |
| L238A                                       | 21.2            | -3.1                                | -.44   | 6.0  | .64    | 62.8            | -10.1                              | -.67               | 25.1 | 1.40   | 30N          | 0                        | L238A |  |
| L238B                                       | 16.0            | -8.3                                | -1.18  | 5.0  | .53    | 58.0            | -14.9                              | -.99               | 13.2 | .74    | 30D          | 0                        | L238B |  |
| L243  | 24.3            | .0                                  | .00    | 7.5  | .80    | 93.2            | 20.3                               | 1.34               | 18.5 | 1.03   | 30D          | 0                        | L243  |  |
| L254  | 13.4            | -10.9                               | -1.56  | 4.3  | .46    | 47.2            | -25.7                              | -1.71              | 11.9 | .66    | 30M          | 0                        | L254  |  |
| L262  | 20.1            | -4.1                                | -.59   | 6.0  | .64    | 70.3            | -2.6                               | -.17               | 14.6 | .82    | 30N          | 0                        | L262  |  |
| L275  | 18.7            | -5.6                                | -.80   | 5.9  | .63    | 92.9            | 20.0                               | 1.33               | 21.2 | 1.19   | 30N          | 0                        | L275  |  |
| L278  | 15.6            | -8.7                                | -1.24  | 2.8  | .30    | 48.1            | -24.9                              | -1.65              | 12.7 | .71    | 30C          | 0                        | L278  |  |
| L279  | 20.3            | -4.0                                | -.57   | 8.4  | .90    | 50.6            | -22.3                              | -1.48              | 30.7 | 1.72   | 30N          | 0                        | L279  |  |
| L285A                                       | 23.9            | -.3                                 | -.05   | 7.4  | .79    | 81.5            | 8.6                                | .57                | 17.3 | .97    | 30N          | 0                        | L285A |  |
| L285B                                       | 22.4            | -1.9                                | -.27   | 7.7  | .82    | 92.1            | 19.2                               | 1.27               | 30.9 | 1.73   | 30N          | 0                        | L285B |  |
| L299  | 20.8            | -3.5                                | -.49   | 6.2  | .66    | 79.1            | 6.1                                | .41                | 17.4 | .97    | 30N          | 0                        | L299  |  |
| L320  | 43.1            | 18.9                                | 2.71   | 33.7 | 3.61   | 83.8            | 10.8                               | .72                | 26.2 | 1.47   | 30N          | *                        | L320  |  |
| L326N                                       | 16.3            | -7.9                                | -1.13  | 4.7  | .50    | 43.7            | -29.2                              | -1.94              | 14.7 | .82    | 30N          | 0                        | L326N |  |
| L339  | 18.9            | -5.3                                | -.76   | 4.8  | .52    | 69.0            | -3.9                               | -.26               | 13.4 | .75    | 30N          | 0                        | L339  |  |
| L366A                                       | 25.7            | 1.5                                 | .21    | 6.8  | .73    | 74.0            | 1.1                                | .07                | 25.4 | 1.42   | 30N          | 0                        | L366A |  |
| L376  | 16.1            | -8.2                                | -1.17  | 4.5  | .48    | 56.1            | -16.9                              | -1.12              | 10.8 | .60    | 30N          | 0                        | L376  |  |
| L378  | 23.2            | -1.1                                | -.15   | 5.7  | .61    | 93.9            | 20.9                               | 1.39               | 14.9 | .83    | 30N          | 0                        | L378  |  |
| L388  | 22.8            | -1.5                                | -.21   | 5.2  | .55    | 86.3            | 13.3                               | .88                | 12.5 | .70    | 30N          | 0                        | L388  |  |
| L390  | 25.7            | 1.4                                 | .20    | 14.3 | 1.53   | 72.7            | 0.2                                | -.01               | 29.3 | 1.64   | 30N          | 0                        | L390  |  |
| L393  | 17.3            | -6.9                                | -.99   | 3.5  | .38    | 61.1            | -11.9                              | -.79               | 18.4 | 1.03   | 30M          | 0                        | L393  |  |
| L396M                                       | 33.1            | 8.9                                 | 1.27   | 7.7  | .83    | 113.5           | 40.5                               | 2.69               | 24.3 | 1.36   | 30N          | *                        | L396M |  |
| L565  | 28.0            | 3.7                                 | .54    | 13.7 | 1.47   | 59.4            | -13.5                              | -.90               | 13.5 | .75    | 30N          | 0                        | L565  |  |
| L589  | 35.2            | 10.9                                | 1.57   | 22.7 | 2.43   | 62.1            | -10.8                              | -.72               | 9.1  | .51    | 30N          | 0                        | L589  |  |
| L599  | 27.1            | 2.9                                 | .41    | 8.8  | .94    | 51.1            | 18.2                               | 1.21               | 21.1 | 1.18   | 30C          | 0                        | L599  |  |
| L622  | 51.1            | 26.8                                | 3.84   | 33.6 | 3.60   | 86.9            | 14.0                               | .93                | 26.1 | 1.46   | 30M          | X                        | L622  |  |
| L670  | 40.9            | 16.7                                | 2.39   | 32.4 | 3.47   | 60.8            | -12.1                              | -.81               | 22.5 | 1.26   | 30N          | *                        | L670  |  |
| GR. MEAN =                                  | 24.3            | DOUBLE FOLDS                        |        |      |        | GRAND MEAN =    | 72.9                               | DOUBLE FOLDS       |      |        |              | TEST DETERMINATIONS = 15 |       |  |
| SD MEANS =                                  | 7.0             | DOUBLE FOLDS                        |        |      |        | SD OF MEANS =   | 15.1                               | DOUBLE FOLDS       |      |        |              | 44 LABS IN GRAND MEANS   |       |  |
|   |                 | AVERAGE SDR = 9.3                   |        |      |        |                 |                                    | AVERAGE SDR = 17.9 |      |        |              | DOUBLE FOLDS             |       |  |
| L182S                                       | 25.8            | 1.5                                 | .22    | 27.8 | 2.98   | 148.9           | 76.0                               | 5.04               | 44.7 | 2.50   | 30S          | *                        | L182S |  |
| L190D                                       | 26.7            | 2.5                                 | .36    | 6.9  | .74    | 158.0           | 85.1                               | 5.65               | 40.1 | 2.24   | 30S          | *                        | L190D |  |
| L280  | 15.8            | -8.5                                | -1.21  | 4.0  | .43    | 49.8            | -23.1                              | -1.54              | 15.3 | .86    | 30K          | *                        | L280  |  |
| L326S                                       | 22.3            | -2.0                                | -.28   | 6.0  | .64    | 120.3           | 47.3                               | 3.14               | 32.8 | 1.83   | 30S          | *                        | L326S |  |
| L396S                                       | 23.3            | -1.0                                | -.14   | 3.7  | .39    | 29.9            | -43.1                              | -2.86              | 6.8  | .38    | 30T          | *                        | L396S |  |
| TOTAL NUMBER OF LABORATORIES REPORTING = 50 |                 |                                     |        |      |        |                 |                                    |                    |      |        |              |                          |       |  |

Best values: J29 23 double folds  
J31 75 double folds

The ISO (International Standards Organization) is proposing that MIT folding endurance be reported as the logarithm (to the base 10) of the double fold instead of the double fold as in the past.

Please see page 43 of this report for a demonstration of this proposal.


| LAB<br>CODE | F | MEANS        |       | COORDINATES |       | AVG   |     | PROPERTY---TEST INSTRUMENT---CONDITIONS                  |
|-------------|---|--------------|-------|-------------|-------|-------|-----|--|
|             |   | J29          | J31   | MAJOR       | MINOR | R.SDR | VAR |  |
| L254        | Ø | 13.4         | 47.2  | -27.3       | 5.9   | .56   | 30M | FOLDING ENDURANCE, MIT, WITH CENTRIFUGAL FAN             |
| L278        | Ø | 15.6         | 48.1  | -26.0       | 3.9   | .51   | 30C | FOLDING ENDURANCE, MIT, CIRCULATING FAN IN CEILING       |
| L280        | * | 15.8         | 49.8  | -24.3       | 4.1   | .64   | 30K | FOLDING ENDURANCE, KÖELER-MOLIN                          |
| L100N       | Ø | 15.9         | 77.3  | 2.7         | 9.0   | .35   | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L238B       | Ø | 16.0         | 58.0  | -16.2       | 5.4   | .63   | 30D | FOLDING ENDURANCE, MIT, MODIFIED DRIVE TO REDUCE HEATING |
| L376        | Ø | 16.1         | 56.1  | -18.1       | 5.0   | .54   | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L326N       | Ø | 16.3         | 43.7  | -30.2       | 2.4   | .66   | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L100M       | Ø | 16.4         | 69.1  | -5.2        | 7.0   | .58   | 30M | FOLDING ENDURANCE, MIT, WITH CENTRIFUGAL FAN             |
| L393        | Ø | 17.3         | 61.1  | -12.9       | 4.6   | .70   | 30M | FOLDING ENDURANCE, MIT, WITH CENTRIFUGAL FAN             |
| L236        | Ø | 18.3         | 80.4  | 6.2         | 7.3   | .60   | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L275        | Ø | 18.7         | 92.9  | 18.6        | 9.2   | .91   | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L212        | Ø | 18.8         | 62.3  | -11.4       | 3.4   | .60   | 30M | FOLDING ENDURANCE, MIT, WITH CENTRIFUGAL FAN             |
| L339        | Ø | 18.9         | 69.0  | -4.8        | 4.5   | .63   | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L230        | Ø | 19.5         | 64.9  | -8.7        | 3.2   | .93   | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L262        | Ø | 20.1         | 70.3  | -3.3        | 3.6   | .73   | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L279        | Ø | 20.3         | 50.6  | -22.7       | 0.2   | 1.31  | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L299        | Ø | 20.8         | 79.1  | 5.4         | 4.5   | .82   | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L223F       | Ø | 21.2         | 73.7  | .2          | 3.1   | .95   | 30M | FOLDING ENDURANCE, MIT, WITH CENTRIFUGAL FAN             |
| L238A       | Ø | 21.2         | 62.8  | -10.5       | 1.1   | 1.02  | 30M | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L105        | Ø | 22.2         | 75.2  | 1.8         | 2.4   | 1.05  | 30M | FOLDING ENDURANCE, MIT, WITH CENTRIFUGAL FAN             |
| L326S       | * | 22.3         | 120.3 | 46.2        | 10.6  | 1.24  | 30S | FOLDING ENDURANCE, SCHÖPPER, LEIPZIG                     |
| L285B       | Ø | 22.4         | 92.1  | 18.5        | 5.3   | 1.28  | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L162        | Ø | 22.7         | 64.8  | -8.3        | .1    | 1.29  | 30M | FOLDING ENDURANCE, MIT, WITE CENTRIFUGAL FAN             |
| L388        | Ø | 22.8         | 86.3  | 12.8        | 3.9   | .63   | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L378        | Ø | 23.2         | 93.9  | 20.4        | 4.9   | .72   | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L396S       | * | 23.3         | 29.9  | -42.5       | -6.9  | .39   | 30T | FOLDING ENDURANCE, SCHÖPPER, TMI                         |
| L185        | Ø | 23.9         | 81.5  | 8.3         | 1.9   | .84   | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L285A       | Ø | 23.9         | 81.5  | 8.4         | 1.9   | .88   | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L243        | Ø | 24.3         | 93.2  | 19.9        | 3.7   | .92   | 30D | FOLDING ENDURANCE, MIT, MODIFIED DRIVE TO REDUCE HEATING |
| L121        | Ø | 24.5         | 78.6  | 5.6         | .8    | 1.54  | 30M | FOLDING ENDURANCE, MIT, WITH CENTRIFUGAL FAN             |
| L390        | Ø | 25.7         | 72.7  | .1          | -1.4  | 1.58  | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L366A       | Ø | 25.7         | 74.0  | 1.3         | -1.3  | 1.07  | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L182S       | * | 25.8         | 148.9 | 75.0        | 12.4  | 2.74  | 30S | FOLDING ENDURANCE, SCHÖPPER, LEIPZIG                     |
| L190D       | * | 26.7         | 158.0 | 84.1        | 13.2  | 1.49  | 30S | FOLDING ENDURANCE, SCHÖPPER, LEIPZIG                     |
| L176        | Ø | 27.0         | 67.9  | -4.4        | -3.6  | .65   | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L599        | Ø | 27.1         | 91.1  | 18.4        | .5    | 1.06  | 30C | FOLDING ENDURANCE, MIT, CIRCULATING FAN IN CEILING       |
| L232        | Ø | 28.0         | 92.9  | 20.3        | 0.0   | 1.29  | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L565        | Ø | 28.0         | 59.4  | -12.6       | -6.2  | 1.11  | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L182M       | Ø | 28.5         | 92.9  | 20.4        | -0.6  | 1.73  | 30M | FOLDING ENDURANCE, MIT, WITH CENTRIFUGAL FAN             |
| L124        | Ø | 28.9         | 62.7  | -9.2        | -6.5  | 1.32  | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L190C       | Ø | 29.3         | 72.1  | .1          | -5.1  | .76   | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L150        | Ø | 30.6         | 80.4  | 8.5         | -4.9  | 1.58  | 30M | FOLDING ENDURANCE, MIT, WITH CENTRIFUGAL FAN             |
| L163        | Ø | 30.7         | 55.3  | -16.2       | -9.5  | 1.09  | 30M | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L122        | Ø | 31.8         | 68.5  | -2.9        | -8.2  | 2.13  | 30M | FOLDING ENDURANCE, MIT, WITH CENTRIFUGAL FAN             |
| L396M       | * | 33.1         | 113.5 | 41.5        | -1.3  | 1.09  | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L589        | Ø | 35.2         | 62.1  | -8.6        | -12.7 | 1.47  | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L159        | Ø | 38.9         | 85.4  | 14.9        | -12.1 | 1.95  | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L670        | * | 40.9         | 60.8  | -8.9        | -18.6 | 2.36  | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L320        | * | 43.1         | 83.8  | 14.1        | -16.6 | 2.54  | 30N | FOLDING ENDURANCE, MIT, NO CENTRIFUGAL FAN               |
| L622        | X | 51.1         | 86.9  | 18.7        | -23.8 | 2.53  | 30M | FOLDING ENDURANCE, MIT, WITE CENTRIFUGAL FAN             |
| GMEANS:     |   | 24.3         | 72.9  |             |       | 1.00  |     |  |
|             |   | 95% ELLIPSE: |       | 39.2        | 16.7  |       |     | WITH GAMMA = 79 DEGREES                                  |

# FOLDING ENDURANCE (MIT)

SAMPLE J29 = 24. DOUBLE FOLDS

SAMPLE J31 = 73. DOUBLE FOLDS

DOUBLE FOLDS



ANALYSIS T30-2 TABLE 1  
 FOLDING ENDURANCE (MIT)  
 DATA IS LOG(BASE 10) OF THE DOUBLE FOLD MEASUREMENT

| LAB CODE | SAMPLE J29 102 GRAMS PER SQUARE METER |       |       |      |       | SAMPLE J31 86 GRAMS PER SQUARE METER |       |       |      |       | TEST D. = 15 |   |       |
|----------|---------------------------------------|-------|-------|------|-------|--------------------------------------|-------|-------|------|-------|--------------|---|-------|
|          | MEAN                                  | DEV   | N.DEV | SDR  | R.SDR | MEAN                                 | DEV   | N.DEV | SDR  | R.SDR | VAR          | F | LAB   |
| L100M    | 1.202                                 | -.141 | -1.26 | .110 | .71   | 1.833                                | -.006 | -.06  | .078 | .66   | 30M          | 0 | L100M |
| L100N    | 1.196                                 | -.147 | -1.31 | .066 | .42   | 1.886                                | .047  | .49   | .044 | .38   | 30N          | 0 | L100N |
| L105     | 1.291                                 | -.051 | -.46  | .207 | 1.33  | 1.873                                | .034  | .36   | .053 | .45   | 30M          | 0 | L105  |
| L121     | 1.296                                 | -.046 | -.41  | .264 | 1.70  | 1.888                                | .049  | .50   | .088 | .75   | 30M          | 0 | L121  |
| L122     | 1.429                                 | .087  | .78   | .254 | 1.64  | 1.760                                | -.078 | -.81  | .295 | 2.51  | 30M          | 0 | L122  |
| L124     | 1.392                                 | .050  | .45   | .242 | 1.56  | 1.791                                | -.047 | -.49  | .077 | .65   | 30N          | 0 | L124  |
| L150     | 1.428                                 | .085  | .76   | .226 | 1.46  | 1.888                                | .050  | .51   | .128 | 1.09  | 30M          | 0 | L150  |
| L159     | 1.523                                 | .181  | 1.62  | .234 | 1.50  | 1.919                                | .081  | .83   | .107 | .91   | 30N          | 0 | L159  |
| L162     | 1.307                                 | -.036 | -.32  | .203 | 1.31  | 1.785                                | -.053 | -.55  | .162 | 1.38  | 30M          | 0 | L162  |
| L163     | 1.467                                 | .124  | 1.11  | .131 | .84   | 1.718                                | -.121 | -1.25 | .152 | 1.30  | 30N          | 0 | L163  |
| L176     | 1.424                                 | .082  | .73   | .081 | .52   | 1.823                                | -.015 | -.16  | .091 | .78   | 30N          | 0 | L176  |
| L182M    | 1.389                                 | .047  | .42   | .219 | 1.41  | 1.959                                | .121  | 1.25  | .088 | .75   | 30M          | 0 | L182M |
| L185     | 1.356                                 | .014  | .12   | .145 | .93   | 1.903                                | .064  | .67   | .087 | .74   | 30N          | 0 | L185  |
| L190C    | 1.461                                 | .119  | 1.07  | .068 | .44   | 1.847                                | .008  | .08   | .100 | .85   | 30N          | 0 | L190C |
| L212     | 1.259                                 | -.084 | -.75  | .121 | .78   | 1.788                                | -.051 | -.52  | .078 | .67   | 30M          | 0 | L212  |
| L223F    | 1.303                                 | -.040 | -.35  | .134 | .86   | 1.858                                | .019  | .20   | .095 | .81   | 30M          | 0 | L223F |
| L230     | 1.270                                 | -.072 | -.64  | .135 | .87   | 1.792                                | -.046 | -.48  | .132 | 1.13  | 30N          | 0 | L230  |
| L232     | 1.433                                 | .091  | .82   | .110 | .71   | 1.931                                | .092  | .95   | .210 | 1.78  | 30N          | 0 | L232  |
| L236     | 1.246                                 | -.096 | -.86  | .116 | .75   | 1.901                                | .063  | .65   | .059 | .50   | 30N          | 0 | L236  |
| L238A    | 1.309                                 | -.033 | -.30  | .127 | .82   | 1.761                                | -.078 | -.81  | .195 | 1.66  | 30N          | 0 | L238A |
| L238B    | 1.183                                 | -.159 | -1.43 | .145 | .93   | 1.752                                | -.087 | -.90  | .109 | .93   | 30D          | 0 | L238B |
| L243     | 1.368                                 | .026  | .23   | .123 | .79   | 1.962                                | .123  | 1.27  | .085 | .73   | 30D          | 0 | L243  |
| L254     | 1.104                                 | -.238 | -2.13 | .150 | .96   | 1.662                                | -.177 | -1.83 | .105 | .89   | 30M          | 0 | L254  |
| L262     | 1.286                                 | -.056 | -.50  | .128 | .82   | 1.839                                | .000  | .00   | .086 | .73   | 30N          | 0 | L262  |
| L275     | 1.253                                 | -.089 | -.80  | .126 | .81   | 1.957                                | .118  | 1.22  | .105 | .90   | 30N          | 0 | L275  |
| L278     | 1.186                                 | -.156 | -1.40 | .080 | .52   | 1.668                                | -.171 | -1.77 | .113 | .97   | 30C          | 0 | L278  |
| L279     | 1.275                                 | -.067 | -.60  | .168 | 1.08  | 1.621                                | -.217 | -2.25 | .289 | 2.46  | 30N          | 0 | L279  |
| L285A    | 1.361                                 | .018  | .17   | .129 | .83   | 1.898                                | .059  | .61   | .123 | 1.05  | 30N          | 0 | L285A |
| L285B    | 1.329                                 | -.014 | -.12  | .140 | .90   | 1.937                                | .098  | 1.01  | .169 | 1.44  | 30N          | 0 | L285B |
| L299     | 1.299                                 | -.043 | -.39  | .135 | .87   | 1.887                                | .048  | .50   | .107 | .91   | 30N          | 0 | L299  |
| L320     | 1.519                                 | .176  | 1.58  | .319 | 2.06  | 1.897                                | .058  | .60   | .170 | 1.45  | 30N          | 0 | L320  |
| L326N    | 1.197                                 | -.145 | -1.30 | .119 | .77   | 1.620                                | -.219 | -2.27 | .138 | 1.18  | 30N          | 0 | L326N |
| L339     | 1.264                                 | -.078 | -.70  | .110 | .71   | 1.832                                | -.007 | -.07  | .081 | .69   | 30N          | 0 | L339  |
| L366A    | 1.395                                 | .052  | .47   | .124 | .80   | 1.847                                | .008  | .09   | .142 | 1.21  | 30N          | 0 | L366A |
| L376     | 1.189                                 | -.153 | -1.37 | .126 | .81   | 1.742                                | -.097 | -1.00 | .078 | .66   | 30N          | 0 | L376  |
| L378     | 1.353                                 | .011  | .10   | .107 | .69   | 1.967                                | .129  | 1.33  | .070 | .60   | 30N          | 0 | L378  |
| L388     | 1.348                                 | .005  | .05   | .097 | .63   | 1.932                                | .093  | .96   | .061 | .52   | 30N          | 0 | L388  |
| L390     | 1.369                                 | .027  | .24   | .177 | 1.14  | 1.834                                | -.005 | -.05  | .155 | 1.32  | 30N          | 0 | L390  |
| L393     | 1.230                                 | -.112 | -1.00 | .089 | .57   | 1.765                                | -.074 | -.76  | .142 | 1.21  | 30M          | 0 | L393  |
| L396M    | 1.509                                 | .166  | 1.49  | .106 | .68   | 2.046                                | .207  | 2.15  | .089 | .76   | 30N          | 0 | L396M |
| L565     | 1.405                                 | .063  | .56   | .190 | 1.23  | 1.763                                | -.076 | -.78  | .101 | .86   | 30N          | 0 | L565  |
| L589     | 1.466                                 | .124  | 1.11  | .268 | 1.73  | 1.789                                | -.050 | -.52  | .065 | .56   | 30N          | 0 | L589  |
| L599     | 1.412                                 | .070  | .63   | .141 | .91   | 1.949                                | .110  | 1.14  | .099 | .84   | 30C          | 0 | L599  |
| L622     | 1.634                                 | .292  | 2.61  | .254 | 1.63  | 1.918                                | .079  | .82   | .150 | 1.28  | 30M          | * | L622  |
| L670     | 1.487                                 | .145  | 1.30  | .341 | 2.20  | 1.755                                | -.083 | -.86  | .166 | 1.41  | 30N          | 0 | L670  |

GR. MEAN = 1.342 LOG(10) FOLD      GRAND MEAN = 1.839 LOG(10) FOLD      TEST DETERMINATIONS = 15  
 SD MEANS = .112 LOG(10) FOLD      SD OF MEANS = .097 LOG(10) FOLD      45 LABS IN GRAND MEANS  
 AVERAGE SDR = .155 LOG(10) FOLD      AVERAGE SDR = .117 LOG(10) FOLD

|       |       |       |       |      |      |       |       |       |      |      |     |   |       |
|-------|-------|-------|-------|------|------|-------|-------|-------|------|------|-----|---|-------|
| L182S | 1.312 | -.031 | -.27  | .251 | 1.61 | 2.154 | .316  | 3.27  | .133 | 1.13 | 30S | * | L182S |
| L190D | 1.412 | .070  | .63   | .120 | .77  | 2.185 | .346  | 3.58  | .113 | .97  | 30S | * | L190D |
| L280  | 1.185 | -.157 | -1.41 | .113 | .73  | 1.670 | -.169 | -1.74 | .177 | 1.51 | 30K | * | L280  |
| L326S | 1.332 | -.010 | -.09  | .122 | .79  | 2.063 | .224  | 2.32  | .131 | 1.11 | 30S | * | L326S |
| L396S | 1.362 | .019  | .17   | .068 | .44  | 1.464 | -.374 | -3.87 | .101 | .86  | 30T | * | L396S |

TOTAL NUMBER OF LABORATORIES REPORTING = 50

The ISO (International Standards Organization) is proposing that MIT folding endurance be reported as the logarithm (to the base 10) of the double fold instead of the double fold as in the past.

Analysis T30-1 in this report is the same as in the past with no changes. This analysis, T30-2, shows the data as the ISO proposes. This analysis used the raw data reported for T30-1. The raw data are converted to the logarithm (base 10) as shown in the example to the right, and then the mean of the converted data is calculated and reported as ISO folding endurance.


| Raw data<br>(Folding number<br>in double folds) | log (base 10)<br>of raw data |
|---|------------------------------|
| 207   | 2.32                         |
| 166   | 2.22                         |
| 151   | 2.18                         |
| 332   | 2.52                         |
| 260   | 2.41                         |
| 137   | 2.14                         |
| 199   | 2.30                         |
| 230   | 2.36                         |
| 210   | 2.31                         |

FOLDING ENDURANCE (MIT)  
DATA IS LOG(BASE 10) OF THE DOUBLE FOLD MEASUREMENT

| LAB<br>CODE | F | MEANS         |       | COORDINATES |       | AVG<br>R. SDR | VAR | PROPERTY | TEST INSTRUMENT | CONDITIONS                            |
|-------------|---|---------------|-------|-------------|-------|---------------|-----|----------|-----------------|---------------------------------------|
|             |   | J29           | J31   | MAJOR       | MINOR |               |     |          |                 |                                       |
| L254        | Ø | 1.104         | 1.662 | -.296       | -.006 | .93           | 30M | FOLDING  | ENDURANCE,      | MIT, WITE CENTRIFUGAL FAN             |
| L238B       | Ø | 1.183         | 1.752 | -.180       | .022  | .93           | 30D | FOLDING  | ENDURANCE,      | MIT, MODIFIED DRIVE TO REDUCE HEATING |
| L280        | * | 1.185         | 1.670 | -.226       | -.046 | 1.12          | 30K | FOLDING  | ENDURANCE,      | KÖBLER-MÖLIN                          |
| L278        | Ø | 1.186         | 1.668 | -.226       | -.048 | .74           | 30C | FOLDING  | ENDURANCE,      | MIT, CIRCULATING FAN IN CEILING       |
| L376        | Ø | 1.189         | 1.742 | -.181       | .010  | .74           | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L100N       | Ø | 1.196         | 1.886 | -.092       | .124  | .40           | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L326N       | Ø | 1.197         | 1.620 | -.245       | -.094 | .97           | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L100M       | Ø | 1.202         | 1.833 | -.118       | .077  | .69           | 30M | FOLDING  | ENDURANCE,      | MIT, WITH CENTRIFUGAL FAN             |
| I393        | Ø | 1.230         | 1.765 | -.134       | .005  | .89           | 30M | FOLDING  | ENDURANCE,      | MIT, WITH CENTRIFUGAL FAN             |
| L236        | Ø | 1.246         | 1.901 | -.042       | .107  | .62           | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L275        | Ø | 1.253         | 1.957 | -.004       | .148  | .85           | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L212        | Ø | 1.259         | 1.788 | -.098       | .008  | .72           | 30M | FOLDING  | ENDURANCE,      | MIT, WITH CENTRIFUGAL FAN             |
| L339        | Ø | 1.264         | 1.832 | -.068       | .040  | .70           | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L230        | Ø | 1.270         | 1.792 | -.086       | .004  | 1.00          | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L279        | Ø | 1.275         | 1.621 | -.181       | -.138 | 1.77          | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L262        | Ø | 1.286         | 1.839 | -.046       | .033  | .78           | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L105        | Ø | 1.291         | 1.873 | -.022       | .058  | .89           | 30M | FOLDING  | ENDURANCE,      | MIT, WITH CENTRIFUGAL FAN             |
| L121        | Ø | 1.296         | 1.888 | -.009       | .066  | 1.22          | 30M | FOLDING  | ENDURANCE,      | MIT, WITH CENTRIFUGAL FAN             |
| L299        | Ø | 1.299         | 1.887 | -.007       | .064  | .89           | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L223F       | Ø | 1.303         | 1.858 | -.021       | .039  | .84           | 30M | FOLDING  | ENDURANCE,      | MIT, WITE CENTRIFUGAL FAN             |
| L162        | Ø | 1.307         | 1.785 | -.060       | -.023 | 1.34          | 30M | FOLDING  | ENDURANCE,      | MIT, WITE CENTRIFUGAL FAN             |
| L238A       | Ø | 1.309         | 1.761 | -.072       | -.044 | 1.24          | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L182S       | * | 1.312         | 2.154 | .159        | .275  | 1.37          | 30S | FOLDING  | ENDURANCE,      | SCHÖPPER, LEIPZIG                     |
| L285B       | Ø | 1.329         | 1.937 | .046        | .088  | 1.17          | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L326S       | * | 1.332         | 2.063 | .122        | .188  | .95           | 30S | FOLDING  | ENDURANCE,      | SCHÖPPER, LEIPZIG                     |
| L388        | Ø | 1.348         | 1.932 | .058        | .073  | .57           | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L378        | Ø | 1.353         | 1.967 | .084        | .098  | .64           | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L185        | Ø | 1.356         | 1.903 | .049        | .044  | .84           | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L285A       | Ø | 1.362         | 1.898 | .049        | .037  | .94           | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L396S       | * | 1.362         | 1.464 | -.202       | -.316 | .65           | 30T | FOLDING  | ENDURANCE,      | SCHÖPPER, TMI                         |
| L243        | Ø | 1.368         | 1.962 | .092        | .085  | .76           | 30D | FOLDING  | ENDURANCE,      | MIT, MODIFIED DRIVE TO REDUCE HEATING |
| L390        | Ø | 1.369         | 1.834 | .019        | -.019 | 1.23          | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L182M       | Ø | 1.389         | 1.959 | .108        | .071  | 1.08          | 30M | FOLDING  | ENDURANCE,      | MIT, WITE CENTRIFUGAL FAN             |
| L124        | Ø | 1.392         | 1.791 | .013        | -.068 | 1.10          | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L366A       | Ø | 1.395         | 1.847 | .048        | -.024 | 1.00          | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L555        | Ø | 1.405         | 1.763 | .007        | -.098 | 1.04          | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L599        | Ø | 1.412         | 1.949 | .121        | .049  | .87           | 30C | FOLDING  | ENDURANCE,      | MIT, CIRCULATING FAN IN CEILING       |
| L190D       | * | 1.412         | 2.185 | .258        | .241  | .87           | 30S | FOLDING  | ENDURANCE,      | SCHÖPPER, LEIPZIG                     |
| L176        | Ø | 1.424         | 1.823 | .058        | -.060 | .65           | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L150        | Ø | 1.428         | 1.888 | .058        | -.009 | 1.27          | 30M | FOLDING  | ENDURANCE,      | MIT, WITE CENTRIFUGAL FAN             |
| L122        | Ø | 1.429         | 1.760 | .025        | -.114 | 2.07          | 30M | FOLDING  | ENDURANCE,      | MIT, WITH CENTRIFUGAL FAN             |
| L232        | Ø | 1.433         | 1.931 | .128        | .022  | 1.25          | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L190C       | Ø | 1.461         | 1.847 | .101        | -.063 | .64           | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L589        | Ø | 1.466         | 1.789 | .072        | -.112 | 1.14          | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L163        | Ø | 1.467         | 1.718 | .031        | -.171 | 1.07          | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L670        | Ø | 1.487         | 1.755 | .070        | -.152 | 1.81          | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L396M       | Ø | 1.509         | 2.046 | .256        | .072  | .72           | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L320        | Ø | 1.519         | 1.897 | .177        | -.055 | 1.75          | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L159        | Ø | 1.523         | 1.919 | .194        | -.040 | 1.21          | 30N | FOLDING  | ENDURANCE,      | MIT, NO CENTRIFUGAL FAN               |
| L622        | * | 1.634         | 1.918 | .283        | -.105 | 1.46          | 30M | FOLDING  | ENDURANCE,      | MIT, WITH CENTRIFUGAL FAN             |
| GMEANS:     |   | 1.342         | 1.839 |             |       | 1.00          |     |          |                 |                                       |
|             |   | 95% BLLIPESE: |       | .322        | .200  |               |     |          |                 | WITE GAMMA * 35 DEGREES               |

# FOLDING ENDURANCE (MIT)

SAMPLE J29 = 1.34 LOG(10) FOLD    SAMPLE J31 = 1.84 LOG(10) FOLD



RESULTS EXPRESSED IN STANDARD GURLEY UNITS; MILLIGRAMS PER A 1X3 INCH SPECIMEN (ACTUAL LENGTH 3.5 INCHES)

| LAB CODE | SAMPLE H69 MEAN | PRINTING 96 GRAMS PER SQUARE METER |        |     |        | SAMPLE J25 MEAN | PRINTING 103 GRAMS PER SQUARE METER |        |     |        | TEST D. = 10 |   |       |
|----------|-----------------|------------------------------------|--------|-----|--------|-----------------|-------------------------------------|--------|-----|--------|--------------|---|-------|
|          |                 | DEV                                | N. DEV | SDR | R. SDR |                 | DEV                                 | N. DEV | SDR | R. SDR | VAR          | F | LAB   |
| L100     | 445.            | -7.                                | -.24   | 15. | .71    | 244.            | 3.                                  | .17    | 10. | .72    | 350          | 0 | L100  |
| L121     | 498.            | 46.                                | 1.68   | 15. | .71    | 268.            | 26.                                 | 1.57   | 15. | 1.09   | 350          | 0 | L121  |
| L132     | 396.            | -56.                               | -2.01  | 25. | 1.18   | 236.            | -6.                                 | -.34   | 8.  | .63    | 350          | * | L132  |
| L139     | 442.            | -10.                               | -.35   | 12. | .60    | 250.            | 8.                                  | .48    | 17. | 1.26   | 350          | 0 | L139  |
| L148     | 445.            | -6.                                | -.22   | 16. | .78    | 236.            | -5.                                 | -.32   | 15. | 1.14   | 350          | 0 | L148  |
| L159     | 437.            | -15.                               | -.53   | 19. | .93    | 229.            | -13.                                | -.77   | 16. | 1.15   | 350          | 0 | L159  |
| L162     | 5.              | -447.                              | -16.14 | 0.  | .01    | 5.              | -237.                               | -14.13 | 0.  | .02    | 350          | # | L162  |
| L163     | 442.            | -10.                               | -.34   | 37. | 1.78   | 227.            | -14.                                | -.85   | 23. | 1.68   | 350          | 0 | L163  |
| L183     | 517.            | 66.                                | 2.38   | 31. | 1.50   | 268.            | 26.                                 | 1.55   | 16. | 1.17   | 350          | 0 | L183  |
| L190C    | 394.            | -57.                               | -2.07  | 15. | .74    | 195.            | -47.                                | -2.78  | 12. | .91    | 350          | * | L190C |
| L195     | 493.            | 42.                                | 1.50   | 36. | 1.75   | 276.            | 34.                                 | 2.03   | 13. | .99    | 350          | 0 | L195  |
| L212     | 448.            | -3.                                | -.11   | 30. | 1.44   | 252.            | 10.                                 | .60    | 10. | .71    | 350          | 0 | L212  |
| L223     | 433.            | -18.                               | -.66   | 15. | .71    | 230.            | -11.                                | -.67   | 8.  | .62    | 350          | 0 | L223  |
| L224     | 470.            | 19.                                | .67    | 17. | .79    | 252.            | 10.                                 | .59    | 18. | 1.37   | 350          | 0 | L224  |
| L232     | 473.            | 21.                                | .76    | 19. | .90    | 235.            | -6.                                 | -.38   | 12. | .89    | 350          | 0 | L232  |
| L236     | 415.            | -36.                               | -1.30  | 28. | 1.36   | 207.            | -34.                                | -2.06  | 11. | .82    | 350          | 0 | L236  |
| L249     | 458.            | 7.                                 | .24    | 28. | 1.34   | 249.            | 8.                                  | .47    | 14. | 1.04   | 350          | 0 | L249  |
| L254     | 411.            | -41.                               | -1.46  | 15. | .70    | 222.            | -20.                                | -1.19  | 6.  | .46    | 350          | 0 | L254  |
| L260     | 444.            | -8.                                | -.27   | 14. | .67    | 244.            | 2.                                  | .11    | 5.  | .38    | 350          | 0 | L260  |
| L285     | 435.            | -16.                               | -.58   | 23. | 1.12   | 261.            | 20.                                 | 1.18   | 11. | .83    | 350          | 0 | L285  |
| L291     | 463.            | 12.                                | .42    | 19. | .93    | 246.            | 4.                                  | .23    | 23. | 1.67   | 350          | 0 | L291  |
| L308     | 461.            | 9.                                 | .33    | 35. | 1.67   | 237.            | -4.                                 | -.27   | 14. | 1.02   | 350          | 0 | L308  |
| L356     | 442.            | -8.                                | -.30   | 22. | 1.06   | 226.            | -16.                                | -.96   | 8.  | .57    | 350          | 0 | L356  |
| L376     | 469.            | 17.                                | .61    | 18. | .85    | 245.            | 3.                                  | .20    | 23. | 1.72   | 350          | 0 | L376  |
| L378     | 443.            | -9.                                | -.31   | 18. | .85    | 237.            | -5.                                 | -.28   | 25. | 1.85   | 350          | 0 | L378  |
| L382     | 467.            | 15.                                | .55    | 21. | .99    | 247.            | 5.                                  | .30    | 13. | .98    | 350          | 0 | L382  |
| L390     | 460.            | 8.                                 | .29    | 27. | 1.30   | 242.            | 0.                                  | .01    | 9.  | .68    | 350          | 0 | L390  |
| L396     | 445.            | -7.                                | -.24   | 15. | .70    | 248.            | 7.                                  | .40    | 9.  | .69    | 350          | 0 | L396  |
| L600     | 465.            | 13.                                | .48    | 12. | .57    | 245.            | 4.                                  | .21    | 8.  | .56    | 350          | 0 | L600  |
| L648     | 489.            | 38.                                | 1.37   | 13. | .60    | 252.            | 11.                                 | .64    | 6.  | .43    | 350          | 0 | L648  |
| L650     | 443.            | -9.                                | -.31   | 14. | .68    | 244.            | 2.                                  | .11    | 20. | 1.50   | 350          | 0 | L650  |

GR. MEAN = 452. GURLEY UNITS      GRAND MEAN = 242. GURLEY UNITS      TEST DETERMINATIONS = 10  
SD MEANS = 28. GURLEY UNITS      SD OF MEANS = 17. GURLEY UNITS      30 LABS IN GRAND MEANS  
AVERAGE SDR = 21. GURLEY UNITS      AVERAGE SDR = 13. GURLEY UNITS

L213      477.      26.      .94      31.      1.51      235.      -7.      -.41      9.      .67      350      0      L213  
TOTAL NUMBER OF LABORATORIES REPORTING = 32

Best values: H69 450 ± 50 Gurley units  
J25 240 ± 30 Gurley units

Data from the following laboratories appear to be off by a multiplicative factor: 162

ANALYSIS T35-1 TABLE 2


GURLEY STIFFNESS

RESULTS EXPRESSED IN STANDARD GURLEY UNITS: MILLIGRAMS FOR A 1X3 INCH SPECIMEN (ACTUAL LENGTH 3.5 INCHES)

| LAB<br>CODE | P | MEANS        |      | COORDINATES |       | AVG   |     | PROPERTY                | TEST INSTRUMENT | CONDITIONS                                |
|-------------|---|--------------|------|-------------|-------|-------|-----|-------------------------|-----------------|---|
|             |   | H69          | J25  | MAJOR       | MINOR | R.SDR | VAR |                         |                 |   |
| L162        | # | 5.           | 5.   | -506.       | -1.   | .01   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L190C       | * | 394.         | 195. | -72.        | -14.  | .83   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L132        | * | 396.         | 236. | -52.        | 21.   | .90   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L254        | Ø | 411.         | 222. | -45.        | 1.    | .58   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L236        | Ø | 415.         | 207. | -48.        | -14.  | 1.09  | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L223        | Ø | 433.         | 230. | -21.        | -2.   | .66   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L285        | Ø | 435.         | 261. | -5.         | 25.   | .97   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L159        | Ø | 437.         | 229. | -19.        | -5.   | 1.04  | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L139        | Ø | 442.         | 250. | -5.         | 12.   | .93   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L163        | Ø | 442.         | 227. | -15.        | -8.   | 1.73  | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L650        | Ø | 443.         | 244. | -7.         | 6.    | 1.09  | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L378        | Ø | 443.         | 237. | -10.        | -0.   | 1.35  | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L356        | Ø | 443.         | 226. | -15.        | -10.  | .81   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L260        | Ø | 444.         | 244. | -6.         | 5.    | .52   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L396        | Ø | 445.         | 248. | -3.         | 9.    | .69   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L100        | Ø | 445.         | 244. | -4.         | 6.    | .71   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L148        | Ø | 445.         | 236. | -8.         | -2.   | .96   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L212        | Ø | 448.         | 252. | 2.          | 10.   | 1.08  | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L249        | Ø | 458.         | 249. | 10.         | 4.    | 1.19  | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L390        | Ø | 460.         | 242. | 7.          | -4.   | .99   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L308        | Ø | 461.         | 237. | 6.          | -8.   | 1.35  | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L291        | Ø | 463.         | 246. | 12.         | -2.   | 1.30  | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L600        | Ø | 465.         | 245. | 13.         | -3.   | .57   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L382        | Ø | 467.         | 247. | 16.         | -3.   | .99   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L376        | Ø | 465.         | 245. | 17.         | -5.   | 1.29  | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L224        | Ø | 470.         | 252. | 21.         | 0.    | 1.08  | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L232        | Ø | 473.         | 235. | 16.         | -15.  | .90   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L213        | * | 477.         | 235. | 20.         | -18.  | 1.09  | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 TEST PIECE), 20 C, 65% RH  |
| L648        | Ø | 480.         | 252. | 39.         | -8.   | .52   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L195        | Ø | 492.         | 276. | 53.         | 11.   | 1.37  | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L121        | Ø | 498.         | 268. | 53.         | 2.    | .90   | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| L183        | Ø | 517.         | 268. | 70.         | -8.   | 1.34  | 350 | STIFFNESS,              | GURLEY          | (UNITS: MG/1X3 -ACTUALLY 3.5= TEST PIECE) |
| GMEANS:     |   | 452.         | 242. |             |       | 1.00  |     |                         |                 |   |
|             |   | 95% ELLIPSE: |      | 81.         | 25.   |       |     | WITH GAMMA = 27 DEGREES |                 |   |

# STIFFNESS, GURLEY

SAMPLE H69 = 452. GURLEY UNITS    SAMPLE J25 = 242. GURLEY UNITS



ANALYSIS T36-1 TABLE 1

TABER STIFFNESS

TAPPI STANDARD T489 09-76, RESULTS EXPRESSED IN GRAM CENTIMETERS

| LAB CODE | SAMPLE J10 MEAN | PRINTING 149 GRAMS PER SQUARE METER |        |      |        | SAMPLE J69 MEAN | PRINTING 149 GRAMS PER SQUARE METER |        |      |        | TEST D. = 10 |   |       |
|----------|-----------------|-------------------------------------|--------|------|--------|-----------------|-------------------------------------|--------|------|--------|--------------|---|-------|
|          |                 | DEV                                 | N. DEV | SDR  | R. SDR |                 | DEV                                 | N. DEV | SDR  | R. SDR | VAR          | F | LAB   |
| L107A    | 16.63           | .11                                 | .10    | 1.18 | 1.56   | 6.52            | .56                                 | .55    | .17  | .49    | 36T          | Ø | L107A |
| L122     | 15.76           | -.76                                | -.75   | .54  | .72    | 6.34            | .38                                 | .37    | .42  | 1.22   | 36T          | Ø | L122  |
| L123     | 16.20           | -.32                                | -.32   | 2.04 | 2.71   | 6.80            | .84                                 | .82    | .63  | 1.83   | 36T          | Ø | L123  |
| L126     | 15.65           | -.67                                | -.86   | .32  | .42    | 4.50            | -1.46                               | -1.43  | .18  | .53    | 36T          | Ø | L126  |
| L150     | 16.70           | .18                                 | .17    | .82  | 1.09   | 6.60            | .64                                 | .63    | .52  | 1.50   | 36T          | Ø | L150  |
| L163     | 17.00           | .48                                 | .47    | .41  | .54    | 5.43            | -.52                                | -.51   | .30  | .88    | 36T          | Ø | L163  |
| L1738    | 15.40           | -1.12                               | -1.10  | .52  | .68    | 6.20            | .24                                 | .24    | .42  | 1.22   | 36T          | Ø | L1738 |
| L176     | 17.10           | .58                                 | .57    | .39  | .52    | 5.04            | -.92                                | -.90   | .13  | .37    | 36T          | Ø | L176  |
| L182     | 17.22           | .70                                 | .68    | .75  | .99    | 6.16            | .20                                 | .20    | .26  | .76    | 36T          | Ø | L182  |
| L207     | 16.89           | .37                                 | .36    | .57  | .75    | 6.93            | .97                                 | .95    | .44  | 1.29   | 36T          | Ø | L207  |
| L212     | 14.85           | -1.67                               | -1.64  | .53  | .70    | 4.95            | -1.01                               | -.99   | .14  | .42    | 36T          | Ø | L212  |
| L228     | 17.30           | .78                                 | .76    | 1.34 | 1.77   | 10.60           | 4.64                                | 4.54   | .84  | 2.44   | 36T          | # | L228  |
| L230     | 18.20           | 1.68                                | 1.65   | 2.20 | 2.91   | 6.00            | .04                                 | .04    | .82  | 2.36   | 36T          | Ø | L230  |
| L236     | 51.00           | 34.48                               | 33.88  | 2.67 | 3.53   | 21.40           | 15.44                               | 15.11  | 1.17 | 3.40   | 36T          | # | L236  |
| L242     | 16.35           | -.17                                | -.17   | .65  | .86    | 6.30            | .34                                 | .34    | .20  | .57    | 36T          | Ø | L242  |
| L243     | 16.85           | .33                                 | .32    | .88  | 1.17   | 8.05            | 2.09                                | 2.05   | .13  | .37    | 36T          | Ø | L243  |
| L260     | 16.67           | .15                                 | .15    | .35  | .47    | 5.92            | -.03                                | -.03   | .17  | .49    | 36T          | Ø | L260  |
| L262     | 17.90           | 1.38                                | 1.35   | 1.05 | 1.39   | 6.50            | .94                                 | .92    | .21  | .61    | 36T          | Ø | L262  |
| L281     | 17.12           | .60                                 | .59    | .34  | .45    | 4.87            | -1.08                               | -1.06  | .25  | .72    | 36T          | Ø | L281  |
| L318     | 15.62           | -.90                                | -.88   | .49  | .65    | 6.12            | .17                                 | .16    | .21  | .62    | 36T          | Ø | L318  |
| L324     | 17.45           | .93                                 | .91    | .50  | .66    | 4.85            | -1.10                               | -1.07  | .14  | .41    | 36T          | Ø | L324  |
| L339     | 15.18           | -1.34                               | -1.32  | .38  | .51    | 3.98            | -1.98                               | -1.94  | .59  | 1.70   | 36T          | Ø | L339  |
| L388     | 27.45           | 10.93                               | 10.74  | 3.13 | 4.15   | 15.70           | 9.74                                | 9.53   | 1.69 | 4.88   | 36T          | # | L388  |
| L442     | 16.56           | .04                                 | .04    | 1.26 | 1.67   | 6.77            | .81                                 | .80    | 1.07 | 3.10   | 36T          | Ø | L442  |
| L484     | 13.58           | -2.54                               | -2.50  | .64  | .85    | 3.88            | -2.08                               | -2.03  | .19  | .56    | 36T          | Ø | L484  |
| L570     | 18.00           | 1.48                                | 1.45   | .67  | .88    | 7.00            | 1.04                                | 1.02   | .00  | .00    | 36T          | Ø | L570  |
| L580     | 17.40           | .88                                 | .86    | .70  | .93    | 6.40            | .44                                 | .43    | .52  | 1.50   | 36T          | Ø | L580  |
| L616     | 22.00           | 5.48                                | 5.38   | 2.49 | 3.30   | 5.80            | -.16                                | -.15   | .79  | 2.29   | 36T          | # | L616  |
| L651     | 16.40           | -.12                                | -.12   | .70  | .93    | 6.40            | .44                                 | .43    | .52  | 1.50   | 36T          | Ø | L651  |

GR. MEAN = 16.52 TABER UNITS      GRAND MEAN = 5.96 TABER UNITS      TEST DETERMINATIONS = 10  
 SD MEANS = 1.02 TABER UNITS      SD OF MEANS = 1.02 TABER UNITS      25 LABS IN GRAND MEANS  
 AVERAGE SDR = .76 TABER UNITS      AVERAGE SDR = .35 TABER UNITS

TOTAL NUMBER OF LABORATORIES REPORTING = 29

Best values: J10 16.6 ± 1.5 Taber units  
 J69 6.1 ± 1.6 Taber units

The following laboratories were omitted from the grand means because of extreme test results: 228, 388, 616


Data from the following laboratories appear to be off by a multiplicative factor: 236

TAPPI STANDARD T489 OS-76, RESULTS EXPRESSED IN GRAM CENTIMETERS

| LAB<br>CODE | F | MEANS        |       | COORDINATES |        | AVG   |     | PROPERTY---TEST INSTRUMENT---CONDITIONS |
|-------------|---|--------------|-------|-------------|--------|-------|-----|---|
|             |   | J10          | J69   | MAJOR       | MINOR  | R.SDR | VAR |   |
| L484        | Ø | 13.98        | 3.88  | -3.27       | .34    | .70   | 36T | STIFFNESS, TABER                        |
| L212        | Ø | 14.85        | 4.95  | -1.89       | .48    | .56   | 36T | STIFFNESS, TABER                        |
| L339        | Ø | 15.18        | 3.98  | -2.35       | -.44   | 1.10  | 36T | STIFFNESS, TABER                        |
| L173B       | Ø | 15.40        | 6.20  | -.62        | .97    | .95   | 36T | STIFFNESS, TABER                        |
| L37.8       | Ø | 15.62        | 6.12  | -.51        | .76    | .63   | 36T | STIFFNESS, TABER                        |
| L126        | Ø | 15.65        | 4.50  | -1.65       | -.41   | .48   | 36T | STIFFNESS, TABER                        |
| L122        | Ø | 15.76        | 6.34  | -.26        | .81    | .97   | 36T | STIFFNESS, TABER                        |
| L123        | Ø | 16.20        | 6.80  | .37         | .82    | 2.27  | 36T | STIFFNESS, TABER                        |
| L242        | Ø | 16.35        | 6.30  | .12         | .36    | .71   | 36T | STIFFNESS, TABER                        |
| L651        | Ø | 16.40        | 6.40  | .23         | .40    | 1.21  | 36T | STIFFNESS, TABER                        |
| L442        | Ø | 16.56        | 6.77  | .60         | .55    | 2.38  | 36T | STIFFNESS, TABER                        |
| L107A       | Ø | 16.63        | 6.52  | .47         | .32    | 1.02  | 36T | STIFFNESS, TABER                        |
| L260        | Ø | 16.67        | 5.92  | .08         | -.13   | .48   | 36T | STIFFNESS, TABER                        |
| L150        | Ø | 16.70        | 6.60  | .58         | .33    | 1.29  | 36T | STIFFNESS, TABER                        |
| L243        | Ø | 16.85        | 6.65  | 1.72        | 1.24   | .77   | 36T | STIFFNESS, TABER                        |
| L207        | Ø | 16.89        | 6.93  | .95         | .42    | 1.02  | 36T | STIFFNESS, TABER                        |
| L163        | Ø | 17.00        | 5.43  | -.04        | -.71   | .71   | 36T | STIFFNESS, TABER                        |
| L176        | Ø | 17.10        | 5.04  | -.25        | -1.05  | .44   | 36T | STIFFNESS, TABER                        |
| L281        | Ø | 17.12        | 4.87  | -.35        | -1.19  | .58   | 36T | STIFFNESS, TABER                        |
| L182        | Ø | 17.22        | 6.16  | .63         | -.35   | .88   | 36T | STIFFNESS, TABER                        |
| L228        | # | 17.30        | 10.60 | 3.84        | 2.72   | 2.11  | 36T | STIFFNESS, TABER                        |
| L580        | Ø | 17.40        | 6.40  | .93         | -.31   | 1.21  | 36T | STIFFNESS, TABER                        |
| L324        | Ø | 17.45        | 4.86  | -.13        | -1.43  | .54   | 36T | STIFFNESS, TABER                        |
| L262        | Ø | 17.90        | 6.90  | 1.64        | -.31   | 1.00  | 36T | STIFFNESS, TABER                        |
| L570        | Ø | 18.00        | 7.00  | 1.78        | -.31   | .44   | 36T | STIFFNESS, TABER                        |
| L230        | Ø | 18.20        | 6.00  | 1.21        | -1.16  | 2.64  | 36T | STIFFNESS, TABER                        |
| L616        | # | 22.00        | 5.80  | 3.74        | -4.00  | 2.79  | 36T | STIFFNESS, TABER                        |
| L388        | # | 27.45        | 15.70 | 14.61       | -.90   | 4.51  | 36T | STIFFNESS, TABER                        |
| L236        | # | 51.00        | 21.40 | 35.24       | -13.61 | 3.46  | 36T | STIFFNESS, TABER                        |
| GMEANS:     |   | 16.52        | 5.96  |             |        | 1.00  |     |   |
|             |   | 95% ELLIPSE: |       | 3.32        | 1.96   |       |     | WITH GAMMA = 45 DEGREES                 |

# STIFFNESS, TABER

SAMPLE J10 = 16.5 TABER UNITS      SAMPLE J69 = 6.0 TABER UNITS



| LAB CODE                                    | SAMPLE H79 |        | PRINTING 151 GRAMS PER SQUARE METER |      |       |                                 | SAMPLE E60 |       | PRINTING 68 GRAMS PER SQUARE METER |       |     |   | TEST D. " 4 |  |  |
|---|------------|--------|-------------------------------------|------|-------|---------------------------------|------------|-------|------------------------------------|-------|-----|---|-------------|--|--|
|   | MEAN       | DEV    | N.DEV                               | SDR  | R.SDR | MEAN                            | DEV        | N.DEV | SDR                                | R.SDR | VAR | F | LAB         |  |  |
| L122  | 49.8       | =36.9  | =.72                                | 2.0  | .39   | 40.5                            | =34.5      | =.71  | 2.0                                | .41   | 49Q | # | L122        |  |  |
| L149  | 68.6       | =18.1  | =.35                                | 6.6  | 1.33  | 61.9                            | =13.6      | =.28  | 4.8                                | .98   | 49L | # | L149        |  |  |
| L182I                                       | 26.1       | =60.6  | =1.18                               | .6   | .11   | 17.5                            | =57.9      | =1.18 | .7                                 | .15   | 49S | # | L182I       |  |  |
| L190C                                       | 56.3       | =30.4  | =.59                                | 2.1  | .41   | 45.2                            | =30.2      | =.62  | 2.8                                | .57   | 49T | # | L190C       |  |  |
| L207  | 92.0       | 5.3    | .10                                 | 4.3  | .86   | NO DATA REPORTED FOR SAMPLE E60 |            |       |                                    |       | 49I | # | L207        |  |  |
| L242  | 50.7       | =36.0  | =.70                                | 5.5  | 1.10  | 38.5                            | =37.0      | =.75  | 4.0                                | .83   | 49P | # | L242        |  |  |
| L243  | 103.2      | 16.6   | .32                                 | 8.3  | 1.65  | 81.5                            | 6.0        | .12   | 7.1                                | 1.47  | 49U | # | L243        |  |  |
| L280  | 3.7        | =83.0  | =1.61                               | .0   | .00   | 3.7                             | =71.8      | =1.47 | .0                                 | .00   | 49V | # | L280        |  |  |
| L291  | 88.7       | 2.0    | .04                                 | 4.3  | .86   | 59.5                            | =15.9      | =.33  | 2.9                                | .60   | 49I | # | L291        |  |  |
| L388  | 118.8      | 32.1   | .62                                 | 8.8  | 1.76  | 140.4                           | 64.9       | 1.33  | 8.8                                | 1.81  | 49Q | # | L388        |  |  |
| L484  | 1460.0     | 1373.3 | 26.69                               | 40.0 | 8.00  | 1135.0                          | 1059.5     | 21.63 | 86.6                               | 17.80 | 49P | # | L484        |  |  |
| L564  | 42.8       | =43.9  | =.85                                | 3.2  | .65   | 45.6                            | =29.9      | =.61  | 4.6                                | .94   | 49D | # | L564        |  |  |
| L598  | 187.2      | 100.5  | 1.95                                | 7.8  | 1.56  | 165.9                           | 90.5       | 1.85  | 10.7                               | 2.20  | 49P | # | L598        |  |  |
| L616  | 182.5      | 95.8   | 1.86                                | 11.9 | 2.38  | 202.5                           | 127.0      | 2.59  | 8.7                                | 1.78  | 49M | # | L616        |  |  |
| L643  | 161.2      | 74.6   | 1.45                                | 5.8  | 1.17  | 133.5                           | 58.0       | 1.18  | 5.1                                | 1.04  | 49I | # | L643        |  |  |
| L651  | 400.0      | 313.3  | 6.09                                | .0   | .00   | 400.0                           | 324.5      | 6.63  | .0                                 | .00   | 49F | # | L651        |  |  |
| GR. MEAN = 86.7 KP CM/SEC                   |            |        | GRAND MEAN = 75.5 KP CM/SEC         |      |       | TEST DETERMINATIONS = 4         |            |       |                                    |       |     |   |             |  |  |
| SD MPANS = 51.5 KP CM/SEC                   |            |        | SD OF MEANS = 49.0 KP CM/SEC        |      |       | 11 LABS IN GRAND MEANS          |            |       |                                    |       |     |   |             |  |  |
| AVERAGE SDR = 5.0 KP CM/SEC                 |            |        | AVERAGE SDR = 4.9 KP CM/SEC         |      |       |                                 |            |       |                                    |       |     |   |             |  |  |
| TOTAL NUMBER OF LABORATORIES REPORTING = 16 |            |        |                                     |      |       |                                 |            |       |                                    |       |     |   |             |  |  |

Data from the following laboratories were omitted from the grand means because no viscosity values were reported: 484, 616, 651

Data from the following laboratories were omitted from the grand means because the values were outside the range of the instrument: 280

| LAB CODE | F | MEANS        |        | COORDINATES |        | AVG                     |     | PROPERTY                    | TEST INSTRUMENT | CONDITIONS |
|----------|---|--------------|--------|-------------|--------|-------------------------|-----|-----------------------------|-----------------|------------|
|          |   | H79          | E60    | MAJOR       | MINOR  | R.SDR                   | VAR |                             |                 |            |
| L280     | # | 3.7          | 3.7    | =109.6      | 5.1    | .00                     | 49U | SURFACE PICK STRENGTH, IGT, | OIL             |            |
| L182I    | # | 26.1         | 17.5   | =83.8       | =.3    | .13                     | 49Q | SURFACE PICK STRENGTH, IGT, | IGT OIL         |            |
| L564     | # | 42.8         | 45.6   | =52.4       | 8.6    | .75                     | 49D | SURFACE PICK STRENGTH, IGT, | INK             |            |
| L122     | # | 49.8         | 40.5   | =50.8       | .1     | .40                     | 49Q | SURFACE PICK STRENGTH, IGT, | IGT OIL         |            |
| L242     | # | 50.7         | 38.5   | =51.5       | =2.0   | .96                     | 49P | SURFACE PICK STRENGTH, IGT, | IGT OIL         |            |
| L190C    | # | 56.3         | 45.2   | =42.9       | =1.0   | .45                     | 49T | SURFACE PICK STRENGTH, IGT, | IPC FLUID       |            |
| L149     | # | 68.6         | 61.9   | =22.5       | 2.6    | 1.15                    | 49L | SURFACE PICK STRENGTH, IGT, | P18 FLUID       |            |
| L291     | # | 88.7         | 59.5   | =9.5        | =13.0  | .73                     | 49I | SURFACE PICK STRENGTH, IGT, | P18 FLUID       |            |
| L207     | # | 92.0         |        |             |        | .86                     | 49I | SURFACE PICK STRENGTH, IGT, | P18 FLUID       |            |
| L243     | # | 103.2        | 81.5   | 16.2        | =7.0   | 1.56                    | 49T | SURFACE PICK STRENGTH, IGT, | IPC FLUID       |            |
| L388     | # | 118.8        | 140.4  | 68.0        | 25.0   | 1.79                    | 49Q | SURFACE PICK STRENGTH, IGT, | IGT OIL         |            |
| L643     | # | 161.2        | 133.5  | 94.0        | =9.3   | 1.11                    | 49I | SURFACE PICK STRENGTH, IGT, | P18 FLUID       |            |
| L616     | # | 182.5        | 202.5  | 157.0       | 26.1   | 2.08                    | 49M | SURFACE PICK STRENGTH, IGT, | P18 FLUID       |            |
| L598     | # | 187.2        | 165.9  | 135.2       | =3.6   | 1.88                    | 49P | SURFACE PICK STRENGTH, IGT, | IGT OIL         |            |
| L651     | # | 400.0        | 400.0  | 450.7       | 19.5   | .00                     | 49F | SURFACE PICK STRENGTH, IGT, | INK             |            |
| L484     | # | 1460.0       | 1135.0 | 1725.4      | =177.6 | 12.90                   | 49P | SURFACE PICK STRENGTH, IGT, | IGT OIL         |            |
| GMEANS:  |   | 86.7         | 75.5   |             |        | 1.00                    |     |                             |                 |            |
|          |   | 95% ELLIPSE: |        | 216.3       | 31.1   | WITH GAMMA = 43 DEGREES |     |                             |                 |            |


# SURFACE PICK STRENGTH. IGT

SAMPLE H79 = 87. KP CM/SEC

KP CM/SEC

SAMPLE E60 = 75. KP CM/SEC

KP CM/SEC



ANALYSIS T50-1 TABLE 1  
 SURFACE PICK STRENGTH, WAX NUMBER  
 TAPPI STANDARD T459 69-75, SURFACE STRENGTH OF PAPER (WAX PICK TEST)

| LAB CODE | SAMPLE H79 MEAN | PRINTING 151 GRAMS PER SQUARE METER |        |      |        | R. SDR | SAMPLE J51 MEAN | PRINTING 89 GRAMS PER SQUARE METER |        |      |        | TEST D. 5 |       |     |
|----------|-----------------|-------------------------------------|--------|------|--------|--------|-----------------|------------------------------------|--------|------|--------|-----------|-------|-----|
|          |                 | DEV                                 | N. DEV | SDR  | R. SDR |        |                 | DEV                                | N. DEV | SDR  | R. SDR | VAR       | F     | LAB |
| L105     | 10.40           | .71                                 | .94    | .55  | 1.15   | 9.40   | .45             | .47                                | .55    | 1.21 | 50W    | 0         | L105  |     |
| L122     | 9.00            | -.69                                | -.93   | .00  | .00    | 8.20   | -.75            | -.78                               | 1.10   | 2.41 | 50W    | 0         | L122  |     |
| L162     | 11.00           | 1.31                                | 1.74   | .00  | .00    | 9.00   | .05             | .05                                | .00    | .00  | 50W    | 0         | L162  |     |
| L173A    | 8.40            | -1.29                               | -1.73  | .55  | 1.15   | 7.20   | -1.75           | -1.82                              | .45    | .99  | 50W    | 0         | L173A |     |
| L182W    | 10.20           | .51                                 | .68    | 1.10 | 2.29   | 8.60   | -.35            | -.37                               | .55    | 1.21 | 50W    | 0         | L182W |     |
| L183     | 9.80            | .11                                 | .14    | .45  | .94    | 9.00   | .05             | .05                                | .00    | .00  | 50W    | 0         | L183  |     |
| L195     | 9.20            | -.49                                | -.66   | .45  | .94    | 9.20   | .25             | .26                                | .45    | .99  | 50W    | 0         | L195  |     |
| L213     | 10.20           | .51                                 | .68    | .45  | .94    | 10.00  | 1.05            | 1.09                               | .00    | .00  | 50W    | 0         | L213  |     |
| L225     | 10.40           | .31                                 | .41    | .71  | 1.48   | 9.40   | .45             | .47                                | .55    | 1.21 | 50W    | 0         | L225  |     |
| L228     | 10.00           | .31                                 | .41    | .00  | .00    | 7.00   | -1.95           | -2.03                              | .00    | .00  | 50W    | 0         | L228  |     |
| L230     | 9.00            | -.69                                | -.93   | .00  | .00    | 9.20   | .25             | .26                                | .84    | 1.84 | 50W    | 0         | L230  |     |
| L236     | 10.20           | .51                                 | .68    | .45  | .94    | 9.40   | .45             | .47                                | .55    | 1.21 | 50W    | 0         | L236  |     |
| L243     | 8.40            | -1.29                               | -1.73  | .55  | 1.15   | 8.60   | -.35            | -.37                               | .55    | 1.21 | 50W    | 0         | L243  |     |
| L285     | 10.20           | .51                                 | .68    | 1.10 | 2.29   | 9.40   | .45             | .47                                | .55    | 1.21 | 50W    | 0         | L285  |     |
| L339     | 9.20            | -.49                                | -.66   | .45  | .94    | 8.00   | -.95            | -.99                               | .71    | 1.56 | 50W    | 0         | L339  |     |
| L366     | 9.20            | -.49                                | -.66   | .45  | .94    | 9.80   | .85             | .88                                | .45    | .99  | 50W    | 0         | L366  |     |
| L378     | 10.40           | .71                                 | .94    | .89  | 1.87   | 10.80  | 1.85            | 1.92                               | .45    | .99  | 50W    | 0         | L378  |     |
| L616     | 11.20           | 1.51                                | 2.01   | 1.30 | 2.73   | 13.60  | 4.65            | 4.84                               | .55    | 1.21 | 50W    | 0         | L616  |     |

GR. MEAN = 9.69 WAX NUMBER      GRAND MEAN = 8.95 WAX NUMBER      TEST DETERMINATIONS = 5  
 SD MEANS = .75 WAX NUMBER      SD OF MEANS = .96 WAX NUMBER      17 LABS IN GRAND MEANS  
 AVERAGE SDR = .48 WAX NUMBER      AVERAGE SDR = .45 WAX NUMBER  
 TOTAL NUMBER OF LABORATORIES REPORTING = 18

Best values: H79 9.8 ± 1.3 wax number  
 J51 9.0 ± 1.7 wax number

The following laboratories were omitted from the grand means because of extreme test results: 616

ANALYSIS T80-1 TABLE 2  
 SURFACE PICK STRENGTH, WAX NUMBER  
 TAPPI STANDARD T489 68-75, SURFACE STRENGTH OF PAPER (WAX PICK TEST)

| LAB<br>CODE | F | MEANS        |       | COORDINATES |       | AVG                     |     | PROPERTY---                                  | TEST INSTRUMENT--- | CONDITIONS |
|-------------|---|--------------|-------|-------------|-------|-------------------------|-----|--|--------------------|------------|
|             |   | H79          | J51   | MAJOR       | MINOR | R.SDR                   | VAR |  |                    |            |
| L243        | 6 | 8.40         | 8.60  | -0.95       | .94   | 1.18                    | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L173A       | 6 | 8.40         | 7.20  | -2.17       | .24   | 1.07                    | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L230        | 6 | 9.00         | 9.20  | -0.13       | .72   | .92                     | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L122        | 6 | 9.00         | 8.20  | -1.00       | .22   | 1.21                    | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L366        | 6 | 9.20         | 9.80  | .49         | .35   | .96                     | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L339        | 6 | 9.20         | 8.00  | -1.07       | -0.05 | 1.25                    | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L195        | 6 | 9.20         | 9.20  | -0.03       | .55   | .96                     | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L183        | 6 | 9.80         | 9.00  | .09         | -0.07 | .47                     | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L228        | 6 | 10.00        | 7.00  | -1.54       | -1.24 | .00                     | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L225        | 6 | 10.00        | 9.40  | .54         | -0.04 | 1.34                    | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L182W       | 6 | 10.20        | 8.60  | -0.05       | -0.61 | 1.75                    | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L213        | 6 | 10.20        | 10.00 | 1.16        | .09   | .47                     | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L236        | 6 | 10.20        | 9.40  | .64         | -0.21 | 1.07                    | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L285        | 6 | 10.20        | 9.40  | .64         | -0.21 | 1.75                    | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L378        | 6 | 10.40        | 10.80 | 1.95        | .31   | 1.43                    | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L115        | 6 | 10.40        | 9.40  | .74         | -0.39 | 1.18                    | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L162        | 6 | 11.00        | 9.00  | .69         | -1.11 | .00                     | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| L616        | # | 11.20        | 13.60 | 4.78        | 1.02  | 1.67                    | 50W | SURFACE PICK STRENGTH, WAX (TAPPI T459 6875) |                    |            |
| GMEANS:     |   | 9.69         | 8.95  |             |       | 1.00                    |     |  |                    |            |
|             |   | 95% ELLIPSE: |       | 2.95        | 1.72  | WITH GAMMA = 59 DEGREES |     |  |                    |            |


# SURFACE PICK STRENGTH, WAX.

SAMPLE H79 = 9.7

WAX NUMBER

SAMPLE J51 = 9.0

WAX NUMBER



TAPPI COLLABORATIVE REFERENCE PROGRAM  
ANALYSIS T91-1 TABLE 1  
CNCORA (CORRUGATING MEDIUM TEST-CMT)  
TAPPI STANDARD T809 6S-71

| LAB CODE | LINERBOARD |                                |        |     |        | KRAFT    |                                |        |     |        | TEST D. = 10 |   |      |
|----------|------------|--------------------------------|--------|-----|--------|----------|--------------------------------|--------|-----|--------|--------------|---|------|
|          | E72 MEAN   | 127 GRAMS PER SQUARE METER DEV | N. DEV | SDR | R. SDR | E83 MEAN | 126 GRAMS PER SQUARE METER DEV | N. DEV | SDR | R. SDR | VAR          | F | LAB  |
| L176     | 235.       | 10.                            | .62    | 19. | 1.47   | 306.     | 6.                             | .20    | 16. | .92    | 91P          | 0 | L176 |
| L182     | 234.       | 9.                             | .54    | 16. | 1.25   | 321.     | 21.                            | .68    | 8.  | .45    | 91N          | 0 | L182 |
| L185     | 243.       | 17.                            | 1.10   | 15. | 1.17   | 344.     | 45.                            | 1.42   | 12. | .69    | 91A          | 0 | L185 |
| L218     | 290.       | -35.                           | -2.23  | 11. | .82    | 278.     | -21.                           | -.67   | 16. | .91    | 91A          | 0 | L218 |
| L242     | 240.       | 15.                            | .95    | 9.  | .66    | 345.     | 46.                            | 1.46   | 11. | .65    | 91G          | 0 | L242 |
| L255     | 213.       | -12.                           | -.77   | 9.  | .72    | 237.     | -63.                           | -1.98  | 6.  | .33    | 91P          | 0 | L255 |
| L269     | 215.       | -10.                           | -.63   | 8.  | .60    | 302.     | 3.                             | .09    | 14. | .82    | 91P          | 0 | L269 |
| L280     | 226.       | 1.                             | .07    | 14. | 1.06   | 312.     | 13.                            | .40    | 26. | 1.46   | 91N          | 0 | L280 |
| L289     | 237.       | 12.                            | .74    | 13. | 1.02   | 248.     | -52.                           | -1.63  | 30. | 1.72   | 91P          | 0 | L289 |
| L329     | 212.       | -13.                           | -.83   | 15. | 1.15   | 301.     | 1.                             | .04    | 36. | 2.02   | 91P          | 0 | L329 |
| L393     | 212.       | -13.                           | -.83   | 14. | 1.06   | 178.     | -121.                          | -3.84  | 8.  | .46    | 91P          | # | L393 |
| L394     | 215.       | -11.                           | -.66   | 10. | .78    | 281.     | -19.                           | -.59   | 15. | .86    | 91P          | 0 | L394 |
| L484     | 223.       | -2.                            | -.14   | 6.  | .48    | 305.     | 6.                             | .18    | 14. | .81    | 91N          | 0 | L484 |
| L621     | 211.       | -14.                           | -.89   | 19. | 1.42   | 274.     | -25.                           | -.79   | 21. | 1.19   | 91P          | 0 | L621 |
| L622     | 244.       | 19.                            | 1.18   | 18. | 1.38   | 305.     | 5.                             | .17    | 29. | 1.63   | 91P          | 0 | L622 |
| L650     | 249.       | 23.                            | 1.46   | 12. | .88    | 343.     | 44.                            | 1.40   | 14. | .80    | 91N          | 0 | L650 |
| L665     | 218.       | -8.                            | -.49   | 15. | 1.14   | 288.     | -12.                           | -.37   | 13. | .73    | 91P          | 0 | L665 |

GR. MEAN = 225. NEWTONS  
SD MEANS = 16. NEWTONS  
AVERAGE SDR = 13. NEWTONS  
TOTAL NUMBER OF LABORATORIES REPORTING = 17

GRAND MEAN = 299. NEWTONS  
SD OF MEANS = 32. NEWTONS  
AVERAGE SDR = 18. NEWTONS  
GRAND MEAN = 67.29 POUNDS

TEST DETERMINATIONS = 10  
16 LABS IN GRAND MEANS

Best values: E72 225 ± 20 newtons  
E83 300 ± 50 newtons

The following laboratories were omitted from the grand means because of extreme test results: 393


TAPPI COLLABORATIVE REFERENCE PROGRAM  
ANALYSIS T91-1 TABLE 2  
CNCORA (CORRUGATING MEDIUM TEST-CMT)  
TAPPI STANDARD T809 6S-71

| LAB CODE | F | MEANS        |      | COORDINATES |       | AVG                     |     | PROPERTY                     | TEST INSTRUMENT          | CONDITIONS |
|----------|---|--------------|------|-------------|-------|-------------------------|-----|------------------------------|--------------------------|------------|
|          |   | E72          | E83  | MAJOR       | MINOR | R. SDR                  | VAR |                              |                          |            |
| L218     | 0 | 190.         | 276. | -32.        | 27.   | .86                     | 91A | FLAT CRUSH STRENGTH, CNCORA, | INSTRON                  |            |
| L501     | 0 | 211.         | 274. | -28.        | 5.    | 1.31                    | 91P | FLAT CRUSH STRENGTH, CNCORA, | TMI/HINDE & DAUCH        |            |
| L393     | # | 212.         | 178. | -119.       | -27.  | .76                     | 91P | FLAT CRUSH STRENGTH, CNCORA, | TMI/HINDE & DAUCH        |            |
| L329     | 0 | 212.         | 301. | -3.         | 13.   | 1.59                    | 91P | FLAT CRUSH STRENGTH, CNCORA, | TMI/HINDE & DAUCH        |            |
| L255     | 0 | 213.         | 237. | -63.        | -9.   | .53                     | 91P | FLAT CRUSH STRENGTH, CNCORA, | TMI/HINDE & DAUCH        |            |
| L394     | 0 | 215.         | 281. | -21.        | 4.    | .82                     | 91P | FLAT CRUSH STRENGTH, CNCORA, | TMI/HINDE & DAUCH        |            |
| L269     | 0 | 215.         | 302. | -1.         | 10.   | .71                     | 91P | FLAT CRUSH STRENGTH, CNCORA, | TMI/HINDE & DAUCH        |            |
| L665     | 0 | 218.         | 288. | -13.        | 4.    | .93                     | 91P | FLAT CRUSH STRENGTH, CNCORA, | TMI/HINDE & DAUCH        |            |
| L484     | 0 | 223.         | 305. | 5.          | 4.    | .64                     | 91N | FLAT CRUSH STRENGTH, CNCORA, | TMI/HINDE & DAUCH        |            |
| L280     | 0 | 226.         | 312. | 12.         | 3.    | 1.26                    | 91N | FLAT CRUSH STRENGTH, CNCORA, | TMI/HINDE & DAUCH        |            |
| L182     | 0 | 234.         | 321. | 23.         | -1.   | .85                     | 91N | FLAT CRUSH STRENGTH, CNCORA, | TMI/HINDE & DAUCH        |            |
| L176     | 0 | 235.         | 306. | 9.          | -7.   | 1.20                    | 91P | FLAT CRUSH STRENGTH, CNCORA, | TMI/HINDE & DAUCH        |            |
| L289     | 0 | 237.         | 248. | -45.        | -28.  | 1.37                    | 91P | FLAT CRUSH STRENGTH, CNCORA, | TMI/HINDE & DAUCH        |            |
| L242     | 0 | 240.         | 345. | 49.         | 1.    | .65                     | 91G | FLAT CRUSH STRENGTH, CNCORA, | GAYDON PLAT CRUSH TESTER |            |
| L185     | 0 | 243.         | 344. | 48.         | -2.   | .93                     | 91A | FLAT CRUSH STRENGTH, CNCORA, | INSTRON                  |            |
| L622     | 0 | 244.         | 305. | 11.         | -16.  | 1.50                    | 91P | FLAT CRUSH STRENGTH, CNCORA, | TMI/HINDE & DAUCH        |            |
| L650     | 0 | 249.         | 343. | 49.         | -8.   | .84                     | 91N | FLAT CRUSH STRENGTH, CNCORA, | TMI/HINDE & DAUCH        |            |
| GMEANS:  |   | 225.         | 299. |             |       | 1.00                    |     |                              |                          |            |
|          |   | 95% ELLIPSE: |      | 54.         | 35.   | WITH GAMMA = 70 DEGREES |     |                              |                          |            |

# CONCORA (CMT)

SAMPLE E72 = 225. NEWTONS  
 SAMPLE E72 = 50.7 POUNDS

SAMPLE E83 = 299. NEWTONS  
 SAMPLE E83 = 67.3 POUNDS



TAPPI COLLABORATIVE REFERENCE PROGRAM  
 ANALYSIS T96-1 TABLE 1  
 RING CRUSH (COMPRESSION RESISTANCE OF PAPERBOARD)  
 TAPPI STANDARD T818 69-76

| LAB CODE | SAMPLE E72 MEAN | LINERBOARD 127 GRAMS PER SQUARE METER |       |     |       | SAMPLE E83 MEAN | KRAFT 126 GRAMS PER SQUARE METER |       |     |       | TEST D. = 10 |   |      |
|----------|-----------------|---------------------------------------|-------|-----|-------|-----------------|----------------------------------|-------|-----|-------|--------------|---|------|
|          |                 | DEV                                   | N.DEV | SDR | R.SDR |                 | DEV                              | N.DEV | SDR | R.SDR | VAR          | F | LAB  |
| L107     | 367.            | 162.                                  | 6.29  | 2.  | .19   | 346.            | 192.                             | 11.33 | 67. | 6.62  | 96P          | # | L107 |
| L114     | 174.            | -31.                                  | -1.20 | 16. | 1.31  | 137.            | -17.                             | -0.98 | 11. | 1.08  | 96P          | Ø | L114 |
| L122     | 201.            | -4.                                   | -0.16 | 10. | .78   | 145.            | -9.                              | -0.54 | 9.  | .88   | 96P          | Ø | L122 |
| L124     | 174.            | -31.                                  | -1.22 | 23. | 1.87  | 141.            | -13.                             | -0.77 | 15. | 1.49  | 96P          | Ø | L124 |
| L126     | 196.            | -9.                                   | -0.36 | 14. | 1.09  | 150.            | -4.                              | -0.26 | 11. | 1.07  | 96P          | Ø | L126 |
| L141     | 218.            | 12.                                   | .48   | 11. | .98   | 169.            | 15.                              | .89   | 6.  | .56   | 96P          | # | L141 |
| L176     | 170.            | -36.                                  | -1.39 | 16. | 1.27  | 133.            | -21.                             | -1.25 | 17. | 1.64  | 96P          | Ø | L176 |
| L182     | 220.            | 15.                                   | .58   | 8.  | .61   | 161.            | 7.                               | .42   | 8.  | .81   | 96N          | Ø | L182 |
| L191     | 201.            | -4.                                   | -0.16 | 28. | 2.25  | 153.            | -1.                              | -0.04 | 27. | 2.68  | 96P          | Ø | L191 |
| L234     | 156.            | -49.                                  | -1.91 | 12. | .94   | 100.            | -54.                             | -3.18 | 14. | 1.42  | 96P          | # | L234 |
| L237     | 180.            | -25.                                  | -0.98 | 11. | .89   | 145.            | -9.                              | -0.51 | 7.  | .69   | 96P          | Ø | L237 |
| L242     | 260.            | 55.                                   | 2.13  | 14. | 1.11  | 183.            | 29.                              | 1.70  | 17. | 1.71  | 96G          | Ø | L242 |
| L303     | 225.            | 20.                                   | .76   | 11. | .89   | 166.            | 12.                              | .70   | 6.  | .58   | 96N          | Ø | L303 |
| L305     | 219.            | 14.                                   | .54   | 6.  | .44   | 144.            | -10.                             | -0.62 | 8.  | .83   | 96P          | # | L305 |
| L329     | 203.            | -2.                                   | -0.10 | 8.  | .67   | 154.            | -0.                              | -0.02 | 6.  | .63   | 96P          | Ø | L329 |
| L333     | 178.            | -27.                                  | -1.05 | 7.  | .54   | 136.            | -18.                             | -1.09 | 7.  | .66   | 96I          | Ø | L333 |
| L336     | 188.            | -17.                                  | -0.66 | 14. | 1.14  | 134.            | -20.                             | -1.19 | 5.  | .48   | 96P          | Ø | L336 |
| L350     | 218.            | 12.                                   | .48   | 11. | .89   | 165.            | 11.                              | .67   | 7.  | .68   | 96P          | Ø | L350 |
| L484     | 188.            | -18.                                  | -0.68 | 12. | .94   | 152.            | -2.                              | -0.13 | 9.  | .91   | 96R          | Ø | L484 |
| L553     | 229.            | 23.                                   | .91   | 15. | 1.18  | 175.            | 21.                              | 1.22  | 17. | 1.67  | 96P          | Ø | L553 |
| L570     | 195.            | -10.                                  | -0.41 | 5.  | .43   | 134.            | -20.                             | -1.19 | 6.  | .56   | 96P          | Ø | L570 |
| L603     | 246.            | 40.                                   | 1.57  | 17. | 1.32  | 185.            | 31.                              | 1.82  | 8.  | .78   | 96P          | Ø | L603 |
| L610     | 226.            | 21.                                   | .80   | 10. | .76   | 173.            | 18.                              | 1.09  | 10. | .99   | 96P          | Ø | L610 |
| L617     | 178.            | -27.                                  | -1.06 | 22. | 1.75  | 126.            | -28.                             | -1.64 | 12. | 1.21  | 96I          | Ø | L617 |
| L621     | 161.            | -44.                                  | -1.71 | 9.  | .73   | 137.            | -18.                             | -1.04 | 8.  | .83   | 96P          | Ø | L621 |
| L623     | 236.            | 31.                                   | 1.20  | 9.  | .74   | 178.            | 24.                              | 1.40  | 8.  | .83   | 96P          | Ø | L623 |
| L649     | 225.            | 20.                                   | .77   | 5.  | .42   | 161.            | 7.                               | .43   | 10. | .95   | 96P          | Ø | L649 |
| L650     | 237.            | 31.                                   | 1.22  | 8.  | .66   | 172.            | 18.                              | 1.07  | 7.  | .67   | 96N          | Ø | L650 |
| L663     | 197.            | -8.                                   | -0.30 | 11. | .90   | 152.            | -2.                              | -0.12 | 10. | .94   | 96P          | Ø | L663 |

GR. MEAN = 205. NEWTONS

SD MEANS = 26. NEWTONS

GRAND MEAN = 154. NEWTONS

SD OF MEANS = 17. NEWTONS

TEST DETERMINATIONS = 10

27 LABS IN GRAND MEANS

AVERAGE SDR = 13. NEWTONS

AVERAGE SDR = 10. NEWTONS

GR. MEAN = 46.15 POUNDS

TOTAL NUMBER OF LABORATORIES REPORTING = 29

GRAND MEAN = 34.66 POUNDS

Best values: E72 210 ± 38 newtons  
 E83 160 ± 25 newtons

The following laboratories were omitted from the grand means because of extreme test results: 107, 234


TAPPI COLLABORATIVE REFERENCE PROGRAM  
 ANALYSIS T96-1 TABLE 2  
 RING CRUSH (COMPRESSION RESISTANCE OF PAPERBOARD)  
 TAPPI STANDARD T818 08-76

| LAB CODE | F | MEANS        |      | COORDINATES |       | AVG R.SDR               | VAR | PROPERTY    | TEST INSTRUMENT   | CONDITIONS |
|----------|---|--------------|------|-------------|-------|-------------------------|-----|-------------|-------------------|------------|
|          |   | E72          | E83  | MAJOR       | MINOR |                         |     |             |                   |            |
| L234     | # | 150.         | 100. | -70.        | -19.  | 1.18                    | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L621     | 0 | 161.         | 137. | -46.        | 9.    | .78                     | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L176     | 0 | 170.         | 133. | -42.        | 1.    | 1.45                    | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L124     | 0 | 174.         | 141. | -34.        | 6.    | 1.68                    | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L114     | 0 | 174.         | 137. | -35.        | 2.    | 1.20                    | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L617     | 0 | 178.         | 126. | -38.        | -9.   | 1.48                    | 96I | RING CRUSH, | INSTRON           |            |
| L333     | 0 | 178.         | 136. | -33.        | -1.   | .60                     | 96I | RING CRUSH, | INSTRON           |            |
| L237     | 0 | 180.         | 145. | -26.        | 6.    | .79                     | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L484     | 0 | 188.         | 152. | -16.        | 8.    | .93                     | 96R | RING CRUSH, | REGMED            |            |
| L336     | 0 | 198.         | 134. | -25.        | -8.   | .81                     | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L570     | 0 | 195.         | 134. | -20.        | -12.  | .50                     | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L126     | 0 | 196.         | 150. | -10.        | 1.    | 1.08                    | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L663     | 0 | 197.         | 152. | -8.         | 2.    | .92                     | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L191     | 0 | 201.         | 153. | -4.         | 2.    | 2.47                    | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L122     | 0 | 201.         | 145. | -8.         | -5.   | .83                     | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L320     | 0 | 203.         | 154. | -2.         | 1.    | .65                     | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L350     | 0 | 218.         | 165. | 16.         | 3.    | .78                     | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L141     | 0 | 218.         | 169. | 19.         | 6.    | .72                     | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L305     | * | 219.         | 144. | 6.          | -16.  | .64                     | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L182     | 0 | 220.         | 161. | 17.         | -2.   | .71                     | 96N | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L303     | 0 | 225.         | 166. | 23.         | -0.   | .74                     | 96N | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L649     | 0 | 225.         | 161. | 21.         | -4.   | .68                     | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L610     | 0 | 226.         | 173. | 27.         | 4.    | .87                     | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L553     | 0 | 229.         | 175. | 31.         | 5.    | 1.43                    | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L623     | 0 | 236.         | 178. | 39.         | 3.    | .78                     | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L650     | 0 | 237.         | 172. | 36.         | -1.   | .66                     | 96N | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L603     | 0 | 246.         | 185. | 51.         | 4.    | 1.05                    | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| L242     | 0 | 260.         | 183. | 62.         | -5.   | 1.41                    | 96G | RING CRUSH, | GAYDON FLAT CRUSH | TESTER     |
| L1C7     | # | 367.         | 346. | 240.        | 76.   | 3.40                    | 96P | RING CRUSH, | TMI/HINDE &       | DAUCH      |
| MEANS:   |   | 205.         | 154. |             |       | 1.00                    |     |             |                   |            |
|          |   | 95% ELLIPSE: |      | 80.         | 16.   | WITH GAMMA = 32 DEGREES |     |             |                   |            |

# RING CRUSH

SAMPLE E72 = 205. NEWTONS  
 SAMPLE E72 = 46.1 POUNDS

SAMPLE E83 = 154. NEWTONS  
 SAMPLE E83 = 34.7 POUNDS



SUMMARY TABLE

| TEST METHOD  | SAMPLE CODE | GRAND MEAN | SD OF MEAN | AVER SDR | REPL CRP | LABS INCL | LABS PARTIC | REPL TAPPI | REPEAT | REPROD |
|--|-------------|------------|------------|----------|----------|-----------|-------------|------------|--------|--------|
| BURSTING STRENGTH, MODEL C<br>T10=1 PSI                | H63         | 16.69      | 1.32       | 1.04     | 15       | 42        | 47          | 10         | .91    | 3.70   |
|  | J39         | 28.89      | 2.11       | 1.48     |          |           |             |            | 1.30   | 5.88   |
| BURSTING STRENGTH, MODEL C=A<br>T10=2 PSI              | H63         | 16.66      | 1.62       | 1.14     | 15       | 31        | 32          | 10         | 1.00   | 4.53   |
|  | J39         | 28.70      | 1.93       | 1.47     |          |           |             |            | 1.29   | 5.40   |
| BURSTING STRENGTH, HIGH RANGE<br>T11=1 PSI             | E77         | 74.6       | 3.3        | 5.0      | 15       | 35        | 45          | 10         | 4.4    | 9.4    |
|  | K29         | 59.4       | 2.5        | 4.1      |          |           |             |            | 3.6    | 7.1    |
| TEARING STRENGTH, DEEP CUTOUT<br>T15=1 GRAMS           | E76         | 85.9       | 3.8        | 2.5      | 15       | 115       | 125         | 10         | 2.2    | 10.7   |
|  | E80         | 57.6       | 3.7        | 1.5      |          |           |             |            | 1.3    | 10.2   |
| TEARING STRENGTH, NO CUTOUT<br>T17=1 GRAMS             | J41         | 67.2       | 3.3        | 2.8      | 15       | 11        | 12          | 10         | 2.5    | 9.4    |
|  | K19         | 151.5      | 10.3       | 8.0      |          |           |             |            | 7.0    | 28.9   |
| TENSILE STRENGTH, PACKAGING PAPER<br>T19=1 KILONEWTN/M | J15         | 8.58       | .33        | .32      | 20       | 45        | 48          | 12         | .25    | .93    |
|  | K31         | 8.58       | .30        | .45      |          |           |             |            | .36    | .87    |
| TENSILE STRENGTH, CRE TYPE<br>T20=1 KILONEWTN/M        | J04         | 3.67       | .18        | .17      | 20       | 41        | 49          | 12         | .14    | .50    |
|  | J08         | 6.09       | .30        | .37      |          |           |             |            | .30    | .84    |
| TENSILE STRENGTH, PENDULUM TYPE<br>T20=2 KILONEWTN/M   | J04         | 3.75       | .21        | .21      | 20       | 33        | 35          | 12         | .17    | .59    |
|  | J08         | 6.22       | .40        | .43      |          |           |             |            | .34    | 1.12   |
| T.E.A., PACKAGING PAPERS<br>T25=1 JOULES/SQ M          | J15         | 121.6      | 11.3       | 12.5     | 20       | 15        | 16          | 12         | 10.0   | 32.1   |
|  | K31         | 76.1       | 8.0        | 10.1     |          |           |             |            | 8.1    | 22.7   |
| T.E.A., PRINTING PAPERS<br>T26=1 JOULES/SQ M           | J04         | 37.7       | 2.6        | 4.1      | 20       | 14        | 15          | 12         | 3.2    | 7.4    |
|  | J08         | 75.8       | 6.6        | 7.4      |          |           |             |            | 5.0    | 18.8   |
| ELONGATION TO BREAK, PACKAGING PAPER<br>T28=1 PERCENT  | J15         | 2.118      | .080       | .145     | 20       | 14        | 18          | 12         | .116   | .232   |
|  | K31         | 1.457      | .076       | .110     |          |           |             |            | .088   | .218   |
| ELONGATION TO BREAK, PRINTING PAPER<br>T29=1 PERCENT   | J04         | 1.540      | .201       | .119     | 20       | 17        | 20          | 12         | .095   | .560   |
|  | J08         | 1.842      | .182       | .150     |          |           |             |            | .120   | .510   |
| FOLDING ENDURANCE (MIT)<br>T30=1 DOUBLE FOLDS          | J29         | 24.3       | 7.0        | 9.3      | 15       | 44        | 50          | 10         | 8.2    | 19.9   |
|  | J31         | 72.9       | 15.1       | 17.9     |          |           |             |            | 15.7   | 42.7   |
| FOLDING ENDURANCE (MIT)<br>T30=2 LOG(10) FOLD          | J29         | 1.342      | .112       | .155     | 15       | 45        | 50          | 10         | .136   | .319   |
|  | J31         | 1.839      | .097       | .117     |          |           |             |            | .103   | .274   |
| STIFFNESS, GURLEY<br>T35=1 GURLEY UNITS                | H69         | 452.       | 28.        | 21.      | 10       | 30        | 32          | 10         | 18.    | 77.    |
|  | J25         | 242.       | 17.        | 13.      |          |           |             |            | 12.    | 46.    |
| STIFFNESS, TABER<br>T36=1 TABER UNITS                  | J10         | 16.52      | 1.02       | .76      | 10       | 25        | 29          | 5          | .94    | 2.90   |
|  | J69         | 5.96       | 1.02       | .35      |          |           |             |            | .43    | 2.85   |
| SURFACE PICK STRENGTH, IGT<br>T49=1 KP CM/SEC          | H79         | 86.7       | 51.5       | 5.0      | 4        | 11        | 16          | 4          | 6.9    | 142.5  |
|  | E60         | 75.5       | 49.0       | 4.9      |          |           |             |            | 6.7    | 135.7  |
| SURFACE PICK STRENGTH, WAX<br>T50=1 WAX NUMBER         | H79         | 9.69       | .75        | .48      | 5        | 17        | 18          | 5          | .59    | 2.07   |
|  | J51         | 8.95       | .96        | .45      |          |           |             |            | .56    | 2.66   |
| CONCORA (CNT)<br>T91=1 NEWTONS                         | B72         | 225.       | 16.        | 13.      | 10       | 16        | 17          | 10         | 11.    | 44.    |
|  | B83         | 299.       | 32.        | 18.      |          |           |             |            | 15.    | 88.    |
| RING CRUSH<br>T96=1 NEWTONS                            | E72         | 205.       | 26.        | 13.      | 10       | 27        | 29          | 10         | 11.    | 71.    |
|  | E83         | 154.       | 17.        | 10.      |          |           |             |            | 9.     | 47.    |

|   |   |  |                                 |
|---|---|--|---------------------------------|
| U.S. DEPT. OF COMM.<br>BIBLIOGRAPHIC DATA<br>SHEET  | 1. PUBLICATION OR REPORT NO.<br><br>TAPPI CRP 55S       | 2. Gov't Accession No.                           | 3. Recipient's Accession No.    |
| 4. TITLE AND SUBTITLE<br><br>Technical Association of the Pulp and Paper Industry<br>COLLABORATIVE REFERENCE PROGRAM FOR PAPER<br>Report #55S   |   | 5. Publication Date<br><br>January 10, 1978      | 6. Performing Organization Code |
| 7. AUTHOR(S)<br><br>R. G. Powell, J. Horlick  | 8. Performing Organ. Report No.<br><br>NBSIR 79-1358    |  |                                 |
| 9. PERFORMING ORGANIZATION NAME AND ADDRESS<br><br>NATIONAL BUREAU OF STANDARDS<br>DEPARTMENT OF COMMERCE<br>WASHINGTON, DC 20234   |   | 10. Project/Task/Work Unit No.                   | 11. Contract/Grant No.          |
| 12. SPONSORING ORGANIZATION NAME AND COMPLETE ADDRESS (Street, City, State, ZIP)<br><br>Collaborative Testing Services, Inc., 9241 Wood Glade Drive,<br>Great Falls, Virginia 22066; and Technical Association of<br>the Pulp and Paper Industry  |   | 13. Type of Report & Period Covered<br><br>Final | 14. Sponsoring Agency Code      |
| 15. SUPPLEMENTARY NOTES<br><br><input type="checkbox"/> Document describes a computer program; SF-185, FIPS Software Summary, is attached.  |   |  |                                 |
| 16. ABSTRACT (A 200-word or less factual summary of most significant information. If document includes a significant bibliography or literature survey, mention it here.)<br><br>Collaborative Reference Programs provide participating laboratories with the means for checking periodically the level and uniformity of their testing in comparison with that of other participating laboratories. An important by-product of the programs is the provision of realistic pictures of the state of the testing art. This is one of the periodic reports showing averages for each participant, within and between laboratory variability, and other information for participants and standards committees. |   |  |                                 |
| 17. KEY WORDS (six to twelve entries; alphabetical order; capitalize only the first letter of the first key word unless a proper name; separated by semicolons)<br><br>Collaborative reference program; Laboratory evaluation; Paper; Precision; Reference samples, Testing calibration   |   |  |                                 |
| 18. AVAILABILITY<br><br><input type="checkbox"/> Unlimited<br><br><input checked="" type="checkbox"/> For Official Distribution. Do Not Release to NTIS<br><br><input type="checkbox"/> Order From Sup. of Doc., U.S. Government Printing Office, Washington, DC 20402, SD Stock No. SN003-003-<br><br><input type="checkbox"/> Order From National Technical Information Service (NTIS), Springfield, VA, 22161  | 19. SECURITY CLASS<br>(THIS REPORT)<br><br>UNCLASSIFIED | 21. NO. OF<br>PRINTED PAGES<br><br>69            |                                 |
| 20. SECURITY CLASS<br>(THIS PAGE)<br><br>UNCLASSIFIED   |   | 22. Price  |                                 |



This diagram is composed of two full-size overlaid tracings. One tracing was made from the Thwing-Elmendorf tear tester with NO CUTOUT (old style). The other tracing was made from the Thwing-Elmendorf tear tester with DEEP CUTOUT. The cross hatched area represents the metal removed from the swinging sector when the deep cutout (new) style was created.

DEEP CUTOUT instrument  
is  $\frac{5}{8}$  inch across

NO CUTOUT instrument  
is  $1 \frac{1}{4}$  inch across

Note shape of pendulum  
sector with respect to  
an imaginary line drawn  
across the top of the  
specimen clamp

